


Service Manual

9" COLOR TV/MONITOR WITH
REMOTE CONTROL

MODEL NO: KRB-1576F

KRB 1569F



 **AudioSonic**

CTV-310B
MODEL NO: CTV-210B
OUTPUT: 50mV
DATE:
SUPPLY VOLTAGE : AC 230V/50HZ LOAD : 16 ohm
TEST:
GERERAL INFORMATION : TV 75 OHM INPUT ANT. SIFE VOLTAGE 0 dB =1uV

PAGE:1

DESCRIPTION	UNIT	LIMIT	NOMINAL	NO.1	NO.2	NO.3	NO.4	NO.5	NO.6
VL BAND									
TUNING RANGE	HIGH	MHZ	62.25	65.25					
	LOW	MHZ	48.25	45.25					
MAX/USABLE SENS	CH - 2	dB	32/46	26 / 40	/	/	/	/	/
	CH - 3	dB	32/46	26 / 40	/	/	/	/	/
	CH - 4	dB	32/46	26 / 40	/	/	/	/	/
IF REJ.	CH - 3	dB	40	50					
IMAGE REJ.	CH - 3	dB	40	50					
VHF BAND									
TUNING RANGE	HIGH	MHZ	224.25	228.00					
	LOW	MHZ	175.25	140.00					
MAX/USABLE SENS	CH - 5	dB	32/46	26 / 40	/	/	/	/	/
	CH - 9	dB	32/46	26 / 40	/	/	/	/	/
	CH - 12	dB	32/46	26 / 40	/	/	/	/	/
IF REJ.	CH - 9	dB	50	60					
IMAGE REJ.	CH - 9	dB	40	50					
UHF BAND									
TUNING RANGE	HIGH	MHZ	855.25	860.00					
	LOW	MHZ	471.25	435.00					
MAX/USABLE SENS	CH - 21	dB	36/52	32 / 46	/	/	/	/	/
	CH - 30	dB	36/52	32 / 46	/	/	/	/	/
	CH - 40	dB	36/52	32 / 46	/	/	/	/	/
	CH - 50	dB	36/52	32 / 46	/	/	/	/	/
	CH - 60	dB	36/52	32 / 46	/	/	/	/	/
IF REJ.	CH - 40	dB	40	50					
IMAGE REJ.	CH - 40	dB	30	40					
CATV TUNER TELEFUNKEN	CH		2900KHC S1->S20		/	/	/	/	/
	CH		3300KHC S1->S41		/	/	/	/	/
ADJ. PIX. ATT.	dB	20	30						
ADJ. SND. ATT.	dB	20	30						
SELF. SND. ATT.	dB	20±6							
CONTRAST RANGE	dB	4	6						

DESCRIPTION	UNIT	LIMIT	NOMINAL	NO.1	NO.2	NO.3	NO.4	NO.5	NO.6
SOUND									
MAX. OUTPUT	mW	700	1000.						
THD. OUTPUT 10 %	mW	500	700						
REF. THD	%	5	3						
S / N	dB	30	35						
AM SUPP.	dB	25	30						
MIN. HUM	mV	30	15						
RESPONSE FH 6 KHZ FL 125 HZ	dB	-3±6	-3±3						
	dB	-3±6	-3±3						
SIF. FREQ. ERROR	KHZ	±100	0						
LIMIT SENS.	dB	80	70						
PICTURE									
LINEARITY	VERT.	%	15	10					
	HOR.	%	25	15					
PINCUSHION	DIST.	%	2	1					
BARREL	DIST.	%	2	1					
KEYSTANE	DIST.	%	2	1					
V / H	RATIO	%	100±5	100%					
LUMINANCE	MAX	lux	200	250					
	MIN	lux	50	30					
VA TEST									
H. V.	MAX	KV	16±1	16					
H. V.	MIN	KV	15±1	15					
REG. VOLTAGE	V	10.8±0.5	10.8						
DELAY AGC. VOLTAGE	V	5±0.5	5						
REG. RIPPLE VOLTAGE	mV	30	15						
DC CONSUMPTION	W	46	44						
AC CONSUMPTION	W	65	59						

ALIGNMENT PROCEDURE

REGULATOR ADJUSTMENT

NOTE: MALADJUSTMENT OF THE LOW VOLTAGE REGULATOR OR THE HORIZONTAL OSCILLATOR MAY RESULT IN DAMAGE TO THE HORIZONTAL OUTPUT TRANSISTOR OR PULSE LIMITER DIODE.

THE FOLLOWING PROCEDURES ARE RECOMMENDED TO INSURE SAFE OPERATION.

1. CONNECT THE TV TO AC 110~240V THEN ADJUST THE AC SWITCHING MODE POWER REGULATOR SVR1 TO DC 12V.
2. CONNECT A DC DIGITAL VOLTMETER OR OTHER PRECISION ACCURACY VOLTMETER TO THE COLLECTOR OF THE REGULATOR OUTPUT TRANSISTOR QPD1.(T.P1)

HORIZONTAL OSCILLATOR ADJUSTMENT

1. POWER ADJUSTMENT
ADJUST THE REGULATOR VRD1 TO DC 10.8V.
2. VERTICAL HIGHTNESS ALIGNMENT
ADJUST THE VERTICAL HIGHTNESS VRV1 & VRV2, ENABLE THE CIRCLE OF PICTURE APPROACH TO CIRCLE.
3. HORIZONTAL POSITION ALIGNMENT
ADJUST HORIZONTAL POSITION VRH1, LET THE SQUARE SIGNAL IN THE CENTER OF THE SCREEN.
4. RF AGC ALIGNMENT
ADJUST VIF PROCESS AGC CONTROL VRI1 AT INPUT SIGNAL INTENSITY 50dB, THE SCREEN COULD LOOKING CLEAR AND 80dB, THE SCREEN DON'T INFLECT.
5. WHITE BALANCE ALIGNMENT
ADJUST THE VRY4, VRY5, AT CENTER POSITION. ADJUST SCREEN VR, LET THE SCREEN WILL BE LITTLE BRIGHTNESS. ADJUST VRY4 LET THE SCREEN TO BE YELLOW, AND THEN ADJUST VRY5 LET THE SCREEN APPROACH TO WHITE.
6. FOCUS ADJUSTMENT
ADJUST FOCUS VR, LET THE STRIP IN THE SCREEN TO BE CLEAR.
7. SCREEN ADJUSTMENT
ADJUST SCREEN VR LET THE BRIGHTNESS SUIT AS DESIRED.

GENERAL ALIGNMENT INSTRUCTIONS

1. VIDEO IF ALIGNMENT

TEST EQUIPMENT CONNECTION (SEE FIGURE).


OSCILLOSCOPE: CONNECT TO THE (1). IC01 PIN 13.

(2). ICR1 PIN 8.

SWEEP GENERATOR: CONNECT THROUGH A MATCHING PAD TO THE TEST POINT (T.P) OF THE TUNER.

MARKER GENERATOR: COUPLE LOOSELY TO THE OUTPUT CABLE OF SWEEP GENERATOR.

ADJUST SWEEP GENERATOR TO LOWEST SIGNAL LEVEL CONSISTENT WITH USABLE			
STEP	SWEEP FREQUENCY	MARKER FREQUENCY	REMARK
1) ADJUST VIF DETECTOR LI01 FOR MARKER POINT MAX.	25~45 MHz (45~65 MHz FOR JAPAN). 30~50 MHz FOR CCIR.	SYSTEM B,G,H, 38.9 MHz SYSTEM I 36.9 MHz SYSTEM M,N 45.75 MHz (58.75 MHz FOR JAPAN) (34.7 MHz FOR AUSTRARIA SYSTEM)	IN THE PARENTHESIS FOR AFC CORRECTION.
2) ADJUST VIF DETECTOR LI01 FOR MARKER POINT MAX.	25~45 MHz (45~65 MHz FOR JAPAN). 30~50 MHz FOR CCIR.	SYSTEM B,G,H, 38.9 MHz SYSTEM I 36.9 MHz SYSTEM M,N 45.75 MHz (58.75 MHz FOR JAPAN) (34.7 MHz FOR AUSTRARIA SYSTEM)	IN THE PARENTHESIS FOR AFC CORRECTION.



VIDEO IF ALIGNMENT CONNECTING FIGURE

2. SOUND IF ALIGNMENT

TEST EQUIPMENT CONNECTION

SIGNAL GENERATOR: CONNECT TO TEST POINT (T.P) OF THE TUNER THROUGH A MATCHING PAD.


OSCILLOSCOPE: CONNECT TO THE ICA1 PIN 2.

ALIGNMENT PROCEDURE


STEP	GENERATOR	SCOPE
DON'T ADJUST (PLEASE CHECK)	SYSTEM B,G,H, 33.4 MHz SYSTEM M,N 41.25 MHz (54.25 MHz FOR JAPAN) SYSTEM I 33.5 MHz. S SYSTEM D,K, 32.4 MHz, 1 KHz FM MOD DEVIATION 25 KHz 80 dB OUTPUT.	CONNECT TO THE ICA1 PIN 2

3. VERTICAL DEFLECTION ALIGNMENT

- (1) TUNE THE RECEIVER IN A TEST PATTERN.
- (2) ADJUST V-SIZE CONTROL VRV1 (300 ohm).
WHEN THE INSIDE OF THE LARGEST CIRCLE OF TEST PATTERN REACHES NEAR ROUND PATTERN. (SEE THE FIGURE)
- (3) IF THE PATTERN NOT AT CENTER POSITION, ADJUST V-POSITION CONTROL VRV2 (5K OHM).




BLOCK DIAGRAM



CTV-310 I /:

EXPLODE VIEW



9-G1-1007A▲SUNG WEI 08V0

REV.: 1

2008
 2007
 2006
 2005
 2004
 2003
 2002
 2001
 2000
 1999
 1998
 1997
 1996
 1995
 1994
 1993
 1992
 1991
 1990
 1989
 1988
 1987
 1986
 1985
 1984
 1983
 1982
 1981
 1980
 1979
 1978
 1977
 1976
 1975
 1974
 1973
 1972
 1971
 1970
 1969
 1968
 1967
 1966
 1965
 1964
 1963
 1962
 1961
 1960
 1959
 1958
 1957
 1956
 1955
 1954
 1953
 1952
 1951
 1950
 1949
 1948
 1947
 1946
 1945
 1944
 1943
 1942
 1941
 1940
 1939
 1938
 1937
 1936
 1935
 1934
 1933
 1932
 1931
 1930
 1929
 1928
 1927
 1926
 1925
 1924
 1923
 1922
 1921
 1920
 1919
 1918
 1917
 1916
 1915
 1914
 1913
 1912
 1911
 1910
 1909
 1908
 1907
 1906
 1905
 1904
 1903
 1902
 1901
 1900
 1899
 1898
 1897
 1896
 1895
 1894
 1893
 1892
 1891
 1890
 1889
 1888
 1887
 1886
 1885
 1884
 1883
 1882
 1881
 1880
 1879
 1878
 1877
 1876
 1875
 1874
 1873
 1872
 1871
 1870
 1869
 1868
 1867
 1866
 1865
 1864
 1863
 1862
 1861
 1860
 1859
 1858
 1857
 1856
 1855
 1854
 1853
 1852
 1851
 1850
 1849
 1848
 1847
 1846
 1845
 1844
 1843
 1842
 1841
 1840
 1839
 1838
 1837
 1836
 1835
 1834
 1833
 1832
 1831
 1830
 1829
 1828
 1827
 1826
 1825
 1824
 1823
 1822
 1821
 1820
 1819
 1818
 1817
 1816
 1815
 1814
 1813
 1812
 1811
 1810
 1809
 1808
 1807
 1806
 1805
 1804
 1803
 1802
 1801
 1800
 1799
 1798
 1797
 1796
 1795
 1794
 1793
 1792
 1791
 1790
 1789
 1788
 1787
 1786
 1785
 1784
 1783
 1782
 1781
 1780
 1779
 1778
 1777
 1776
 1775
 1774
 1773
 1772
 1771
 1770
 1769
 1768
 1767
 1766
 1765
 1764
 1763
 1762
 1761
 1760
 1759
 1758
 1757
 1756
 1755
 1754
 1753
 1752
 1751
 1750
 1749
 1748
 1747
 1746
 1745
 1744
 1743
 1742
 1741
 1740
 1739
 1738
 1737
 1736
 1735
 1734
 1733
 1732
 1731
 1730
 1729
 1728
 1727
 1726
 1725
 1724
 1723
 1722
 1721
 1720
 1719
 1718
 1717
 1716
 1715
 1714
 1713
 1712
 1711
 1710
 1709
 1708
 1707
 1706
 1705
 1704
 1703
 1702
 1701
 1700
 1699
 1698
 1697
 1696
 1695
 1694
 1693
 1692
 1691
 1690
 1689
 1688
 1687
 1686
 1685
 1684
 1683
 1682
 1681
 1680
 1679
 1678
 1677
 1676
 1675
 1674
 1673
 1672
 1671
 1670
 1669
 1668
 1667
 1666
 1665
 1664
 1663
 1662
 1661
 1660
 1659
 1658
 1657
 1656
 1655
 1654
 1653
 1652
 1651
 1650
 1649
 1648
 1647
 1646
 1645
 1644
 1643
 1642
 1641
 1640
 1639
 1638
 1637
 1636
 1635
 1634
 1633
 1632
 1631
 1630
 1629
 1628
 1627
 1626
 1625
 1624
 1623
 1622
 1621
 1620
 1619
 1618
 1617
 1616
 1615
 1614
 1613
 1612
 1611
 1610
 1609
 1608
 1607
 1606
 1605
 1604
 1603
 1602
 1601
 1600
 1599
 1598
 1597
 1596
 1595
 1594
 1593
 1592
 1591
 1590
 1589
 1588
 1587
 1586
 1585
 1584
 1583
 1582
 1581
 1580
 1579
 1578
 1577
 1576
 1575
 1574
 1573
 1572
 1571
 1570
 1569
 1568
 1567
 1566
 1565
 1564
 1563
 1562
 1561
 1560
 1559
 1558
 1557
 1556
 1555
 1554


[illegible]

SKIP IV/AV PRESET UN-A
SKX9 SKX8 SKX7 SKX6


100

CHASSIS ALIGNMENT POINTS


Main Chassis




Switch Power Chassis




SWITCH POWER P.C.B






CTV-210 B/U/F/DK			ACTION ELECTRONICS CO., LTD.		
CTV-310 B/U/I/L			億 聲 電 子 股 份 有 限 公 司		
CTV-416 L			TITLE: CTV-310 SWITCH POWER SCHEMATIC DIAGRAM		
CTV-417 B			DRAWN	DESIGN	APPROVED
			曾 美 華		
					REV
					7
					SH3
					DRAWING NO
					05-G1-1321

REMOTE CONTROL SCHEMATIC DIAGRAM



5	8	10	9
14	13	12	11
18	17	16	15
22	21	20	19
7	27	26	25
31	30	29	32
4	3	2	1



SUBFIX	MOD RECORD	SUBFIX	MOD RECORD	ACTION ELECTRONIC CO., LTD.		
AF	1996/1/12	AA	1994/8/23	億豐電子股份有限公司		
AG	1996/2/15	AB	1994/12/15	TITLE: CTV-3101/B SCHEMATIC DIAGRAM		
AH	1996/5/21	AC	1994/12/23	DRAWN	CHECK	APPROVED
AI		AD	1995/2/8	DRAWING NO		
AJ		AE	1995/4/18	REV		
				05-G1-1322		
				SH2		

(IRRADIO) (LENCO) (OKAND) (AWA)
(MARK)