


15 - 51 m.

F 3038 - 5 Ω

185 - 580 m.

110 - 150 V



185 - 580 m. A	15 - 51 m. B
C3, C4 min.	C3, C4 min.
432 Kc/s 32000 pFy/V	4,1 Mc/s —
S8, S7, S5, S4, S7	S4, S2 min.
	21,8 Mc/s —
	C8, C5 min.
	185 - 580 m.
	548 Kc/s —
	S14, S12 min.
	1630 Kc/s —
	C23, C22 min.

VALVULAS

TIPO	POSICION
UCH-42	V-1
UF-41	V-2
UBC-41	V-3
UL-41	V-4
UY-41	V-5
8097 D-00	L-1 (piloto)
8097 D-00	L-2 (piloto)

C1	50 pF	F 5008	R1	1800 Ω	48 553 10/185
C2	50 pF		R2	22000 Ω	48 553 10/22K
C3	12-500 pF	28 49 001 G1	R3	18000 Ω	48 557 10/18K
C4	12-500 pF		R4	2,2 MΩ	48 556 10/2M2
C5	1000 pF	48 757 20/1K	R5	0,05 MΩ	F 6009
C6	25 pF	49 005 49	R6	0,45 MΩ	
C7	47000 pF	48 750 20/47K	R7	4,7 MΩ	48 555 10/4M7
C8	30 pF	28 212 36	R8	0,22 MΩ	48 556 10/220K
C9	400 pF	48 429 01/490E	R9	0,08 MΩ	48 553 10/880K
C10	110 pF	1,7 Rob. FI	R10	150 Ω	48 557 10/150E
C11	185 pF		R13	800 Ω	48 495 10/800E
C12	82000 pF	48 751 20/82K	R14	15000 Ω	48 557 10/15K
C13	110 pF	2,7 Rob. FI	R15	120 Ω	48 555 10/120E
C14	195 pF		R16	47000 Ω	48 555 10/47K
C15	100 pF	48 203 20/100E			
C16	2700 pF	48 751 20/27K			
C17	10000 pF	48 751 20/10K			
C18	10000 pF	48 757 20/10K			
C19	22000 pF	48 757 20/22K			
C20	220 pF	48 203 20/220E			
C21	27 pF	48 203 10/27E			
C22	25 pF	49 005 49			
C23	30 pF	28 212 36			
C24	56 pF	48 203 20/56E			
C25	100 pF	48 203 20/100E			
C26	120 pF	48 203 02/120E			

	V1	V2	V3	V4	
	UCH 42				
	Hexodo	Triodo	UF 41	UBC 41	UL 41
Vf	14		12,5	14	45
Vn	105	72	105	40	125
Vg 2+4	46		46		105
-Vg	0,5		0,5	0,5	5,6
Ia	1,2	2,8	3,8	0,83	30
Ig 2+4	1		2,8		5,1

S1, S2	28 A3 125 27
S11, S12	28 A3 125 35
S3, S3a, S4	28 A3 125 56
S13, S14	F 3298
S5, S6, C10, C11	28 A3 126 84
S7, S8, C13, C14	28 A3 126 84
S9, S10	F 2583