



LOEWE OPTA "Dolly" 3921

C 1	3,4	31	27
R	6	7	2
	3	1	5
	2	8	10
	12	14	16
	18	20	22
	24	26	28
	30	32	34
	36	38	40
	42	44	46
	48	50	52
	54	56	58
	60	62	64
	66	68	70
	72	74	76
	78	80	82
	84	86	88
	90	92	94
	96	98	100

Chassis von oben gesehen

Emittor

Basis

Kontakte in Stellung MW

SP L M AUS

S L1 L2 M1 M2 A

Sp 1	Sp 14	155/74.005 S	Trabantentr. I. I.
Sp 2	Sp 15	5/74.005 S	2.1.280/02 L
Sp 3	Sp 16	155/74.005 S	2000/007 L
Sp 4	Sp 17	155/74.005 S	2000/007 L
Sp 5	Sp 18	225/81 L S	Ausgangstr. 2,2
Sp 6	Sp 19	15/015 L S	130/035 L
Sp 7	Sp 20	160/015 L S	20/07 L
Sp 8	Sp 21	15/104.005 S	20/07 L
Sp 9	Sp 22	170/104.005 S	130/035 L
Sp 10	Sp 23	155/74.005 S	
Sp 11	Sp 24	5/74.005 S	
Sp 12	Sp 25	155/74.005 S	