
G&G


MILITARY & COMMERCIAL

SURPLUS

ELECTRONIC EQUIPMENT AND **ACCESSORIES**



Serving the Electronics Industry since 1920



CATALOG No 67

ON PAGE 21

RADIO SUPPLY COMPANY

75-77 Leonard Street, New York, N.Y. 10013 • Telephone: (212) CO 7-4605



RCA GEIGER COUNTER MODEL WF-16A

USES 10 EXTRA-SENSITIVE BISMUTH-TYPE GEIGER-COUNTER TUBES . . . USEFUL FOR AERIAL AND CAR SURVEYS \$750-

OUR PRICE

BRAND NEW!

The WF-16A is the most sensitive portable instrumen in RCA's line of Geiger counters. It uses a bank of ten bismuth-type Geiger-counter tubes, and measures up to 200,000 counts per minute (CPM) in three ranges: 0-2,000; 0-20,000; and 0-200,000 CPM. Its high sensitivity makes the unit an indispensable tool for the professional prospector. The WF-16A has many features, such as a control to compensate for background radiation, a rapid-zero-reset button, and a built-in battery-voltage checker which shows condition of "A" and "B" batteries directly on the meter. A two-step switch permits choice of "fast" or "slow" meter indication. The WF-16A measures
11" x 4%" x 7½" and weighs approximately 8 pounds with batteries. It is supplied complete with all tubes, RCA batteries, headphone, and top-grain leather case.

SCR-625 ARMY MINE DETECTOR



A Boon To All Prospectors —Oil Companies—Plumbers -Miners-Etc.

OUR PRICE

A novice can readily learn how to operate this device, which locates any metal buried approximately two feet in the ground or even in water! A fully explanatory 64 Page "Technical Manual" is included—it describes the Operation-Maintenance-Application-Servicing, Etc. Contains many Photographs, Circuit Diagrams and a wealth of helpful data. Removed from its sturdy Wood Chest, all the equipment weighs only 15 pounds, thus can be carried on the user's back in the Special Bag included, except the hand held Exploring Rod with its associated Controls, Etc. Truly Portable! The user is alerted to the presence of a buried

metal mass Audibly — by listening to the varying inten-COMPLETE sity of volume of a 1,000 Cycle Tone produced by the Resonator As Pictured Apparatus, thus useage at night or in dark areas is always possible. (Suggestion: makes an ideal Rental Money Maker!) Batteries not included. Required: 2 BA-30 Flashlight Cells & 1 BA-38.

CAN BE ADAPTED FOR UNDERWATER EXPLORATION!

RA-62 AC POWER SUPPLY



Used with SCR-522, this power supply furnishes all the necessary Transmitter-Receiver Volt-

input: 115/230 Volts 60 cycles OUTPUT: 300 VDC at 230 Ma. -150 VDC at 8 Ma. 13 VDC at 3.9 Amps

Completely fuesed and filtered. Size: 16x11 1/4x11". Wt 75 lbs. NEW..... \$59⁵⁰

RA-43 POWER SUPPLY



RECTIFIER Excellent \$4475

INPUT: 80 to 125 or 200 to 250 volts 50/60 cycles. OUTPUT: 115 V.D.C. regulated

at 6 Amps. Features full-wave grid-controlled rectifier. Output voltage is regulated to 1%. Ripple 0.5%. Input circuit breaker. Output fused. AC/DC voltmeter to measure intout and output voltages. RF input and output noise filters, Size: 29x16x16", Weight 175 lbs.

TRANSMITTER



NAVY MODEL

NEW, complete with tubes 60 to 80 Megacycles. 50 Watts

Carrier Power, Designed for reliable ship-to-ship communications, Crystal controlled, will operate on any single frequency in 60 to 80 Mc range. Input pow-er 220 V 60 cycles 1000 Watts.

Provides Voice or Modulated CW signals, 100% modulation, Tubes; 2/708, 3/808, 1/6A6, 1/6D6, 1/2A3, 1/84. Size: 23½ x10½ x 173". Weight 75 lbs.

SIGNAL CORPS EE-8 FIELD PHONE

PROVIDES 5 MILE RANGE CLEAR RECEPTION USING ITS TWO SELF-CONTAINED FLASH-LIGHT BATTERIES!

GUARANTEED: Perfect Working Condition! GOVERNMENT COST-\$90.00 **Excellent Used**



Serves countless applications where Telephone calls are desired between two or several more locations. Signal Corps endorsement vouches for its Utility & Efficiency! Portable-Completely Self Contained! Uses low cost Two Cond. Cable. Two Way Ringing Telephone System—Side Crank actuates a Generator to ring one or more remote stations. Incoming calls sound the Ringer Unit. Modern Handset is equipped with switch that disconnects batteries from Mouth-Piece Unit during listening useage. Canvas Carrying Case has a Shoulder Holster. Handset Connector Cable included. Extremely simple to use-by even any youngster!

RADIO SET AN/APR-21

FREQUENCY MODULATED 152 to 174 Megacycle



Operates on any preset frequency within VHF range of 152-174 Mc FM. Provides reliable voice communications over moderate distances, Tubes: 1/1AG4, 1/5672, 1/6397, 3/6611, 2/6612, and 1 transistor 2N65 and 1/2N101. Consists of Radio Receiver-Transmitter, Handset H-33, Antenna AT-486/G and two carrying straps, Battery BA-358/U not included, Overall size: 12" x 81" x53", Weight 15 lbs.

TG-5B TELEGRAPH SET for CODE COMMUNICATIONS

CODE PRACTICE NEW



Portable, with hinged lid. Two or more units can be operated up to 25 miles apart, over land lines. Has bell call system, 1000 cycle howler, key, headpiece, canvas case, book. Wt. 10 lbs. Batteries not included: two $1\frac{1}{2}$ volt and one $22\frac{1}{2}$ V. Overall size $5\frac{1}{2} \times 5\frac{1}{2} \times 10^{\circ}$.

ARR-1 OSCILLATOR



SPECIAL! UHF Cavity Resonator, 234-258 Megacycles. Special Buy! \$425

GOLD-PLATED

Fully wired, includes two 955 acorn tubes. Navy portable test oscillator. Can be used as modulated signal generator! Tuning wrench, tubes, whip antenna, included, Size: $9\frac{1}{2} \times 6\frac{1}{2} \times 6\frac{3}{4}$ ".

All merchandise shown herein is subject to prior sale and price change without notice

TG-34A KEYER

BRAND NEW in ORIGINAL \$2450



Excellent Used...... \$18.95

Operates on 115 or 230 Volts 50-60 cycles AC. This is an automatic unit for reproducing audible code practice signals reviously recorded in ink on paper tape. By use of self contained speaker, the unit will provide code practice signals to one or more persons, or will provide a keying oscillator for use with a hand key. Compact in portable case. Complete with tubes, photocell. Size 10-9/16" x 101 " x 15-13/16". Shpg wt 45 lbs.

TG-10 CODE PRACTICE SET



Especially fine for schools or groups. This completely automatic unit operates from 110 V 60 cy current, using inked paper tapes to produce audible Morse code. Keyer may be set from 5 to 25 words per minute. 10-watt amplifier. Permits use of key instead of tapes for classroom work. Used......\$1750

MCELROY AUTOMATIC KEYER



Suitable for keying transmitter, or for code practice. Has photo-electric cell and sensitive relay. Variable speed motor operates on 110 Volts 60 cycles AC. Complete

BC-617 RECEIVER



FM RECEIVER

BC-617 FM Receiver & Selector Frequency Coverage 30 to 40 Mc. 10-channel tone selector that

actuates relay circuits. Coaxial Antenna input, squelch circuit, audio control output jack, etc. Complete with tubes: 7/12SN7, 1/12H6,1/12S A7, 2/12SJ7, 3/12SK7, and 1/VR105 and 24 volt dynamow.
Size 11x8x20". Wt. 35 lbs. \$1495 and 24 volt dynamotor.

BC-733 RECEIVER



Receive radio signals being trans-mitted by US Satellite on approx. 108 Mc. This receiver is AM and crystal controlled on six preset frequencies in the 108.3 to 110.3 Mc range. Provides audio and band pass filter output of 90 and 150 cycles for aircraft instrument landing for which originally used. Complete with ten tubes: 1/12AH7, 2/12SG7, 2/12SR7, 1/12SQ7, 3/717 1/12A6, Crystals and Schematic. Voltage required: 12 or 24 V DC and 220 VDC 80 Ma. Size: 13-3/8" x 5" x 7". Also can be converted to FM receiver 80 to 108 Mc. BC-733 Receiver, Exc. Used.....

BC-732A Control Box for above, NEW..... \$1.75

BC-654 TRANSMITTER/RECEIVER



superhet receiver and 6-tube transmitter. covers from 3800

to 5800 Kc. Furnished with all 13 tubes (low drain battery type). Modulation: AM or CW. Freq. Control: Master Oscillator. Power Output 17 Watts.

Complete with Tubes, \$2950 Excellent Used PE-104 Vibrator Power Supply for above, NEW......\$12.50

TRANSCEIVER **BC-611**

HANDIE-TALKIE Crystal controlled battery-operated hand held transceiver. Range is about 3 miles and more, depending on terrain. Freq. 3.7 to 5 Mc. Transmitter is 4-tube A M crystalcontrolled. Receiver is 5-tube superhet. Batteries needed: Burgess #37(A) and XX-69 (B). Complete with tubes, less batteries. LIKE NEW CONDITION

NEW BC-645 TRANSCEIVER





FIXED MOBILE

This equipment originally cost over \$1000. You get all in original factory carton, BRAND NEW, Complete with 15 tube, less dynamotor and accessories, OUR PRICE...

DEPENDABLE TWO WAY 695 COMMUNICATION MORE THAN

has taps for 600 or 4000 ohms.

FREQUENCY RANGE: About 435 to 500 Megacycles TRANSMITTER has 4 tubes: WE-316A, 2-6F6, 7F7

RECEIVER has 11 tubes: 2-955, 4-7H7, 2-7E6, 3-7F7 RECEIVER I.F.: 40 Megacycles SIZE: 10-1/2" x 13-1/2" x 4-1/2". Shpg Wt 25 lbs.

Makes wonderful mobile or fixed rig for 420 to 500 Mc. Easily converted for phone or CW operation. Provides reliable communication for more than 15 miles!

Superb quality components and circuitry in this unit make it ideal for the technician experimenter. Many fabulous experiments can be performed. For example, you can construct a Yagi antenna for the 420 Mc band that will produce a gain of 10 db and yet fit on your operating desk!

ACCESSORIES FOR BC-645 MOUNTING for BC-645 Transceiver..... \$1.50 PE-101C DYNAMOTOR, 12-24 Volts,

(easily converted to 6 volts)...... 7.95 MOUNTING FOR PE-101C Dynamotor......1.00 UHF ANTENNA ASSEMBLIES (set of 2)....per set 2.95 COMPLETE SET OF 11 CONNECTORS...... 5.95

SPECIAL "PACKAGE" OFFER:

BC-645 Transceiver, Dynamotor and all accessories above, COMPLETE, \$2695 BRAND NEW, While Stocks Last......

F.O.B. New York City or Ogden, Utah FOR SAVINGS ON FREIGHT CHARGES

BC-659 TRANSMITTER/RECEIVER



FM TRANSMITTER & RECEIVER, 27 to 38.9 Mc Crystal control on any two pre-selected channels, 80 channels, Uses FT-243 crystal; 13 tubes: 1LH4, 1LC6, 4/1LN5, 2/1291, 4/1299, 1/1291.

Complete with tubes, speaker and meter. VIBRATOR POWER SUPPLY for above, available for 6V, 12V or 24V (please specify voltage desired when ordering.) LIKE NEW..... \$8,95



BC-966-AZ TRANSMITTER/RECEIVER

Receiver-Transmitter IFF set, used in aircraft for "Friend-or-foe" identification in the freq. range of 160 to 211 Mc. Pulse operation. Contains 13 tubes: 3/6H6, 3/7193, 7/6SH7, Also 18 volt dynamotor with blower and gear train, voltage regulator relays, condensers, resistors USED CONDITION.....



24V ABC POWER SUPPLY

Model 24, made by Setchell-Carlson, Supplies A, B and C voltages. INPUT: 24 Volts DC at . 8 Amps. OUTPUT: 1,5 V DC at ,3 Amps; 65 V DC at ,010 Amps, and -6 V DC. Black wrinkle case 7"x4"x4", Wt 4 lbs, Like New.... \$6,95 BRAND NEW..... \$8,95

BC-1206-C RECEIVER



Aircraft Beacon Receiver 200 to 400 Kc. Operates from 24V DC 1.5A. 135 Kc IF. Comp=

lete with tubes: 2/14H7, 1/14J7, 1/14R7 and 1/28D7. Continuous tuning, volume control, on-off switch and phone jack. Very sensitive, 3 microvolts drives it to 10 mw output. Very compact. only 4"x4" (front panel) x 62" deep. No power supply required, works on 24 V DC for both plates and heaters. Output transformer in the unit

Weight 5 lbs.
NEW, With Tubes....
Exc. Used, with Tubes \$9.95 \$12 95 Exc. Used, less Tubes \$5.95

BC-652 RECEIVER



8-tube, single conversion 2-band 2-6 Mc sensitive receiver, made by GE. Has builtin crystal calibrator which gives markers every

Excellent for Amateur or Marine installation. Can be powered from either 12V or 24V DC Power Source. Has all controls on front panel and requires no conversion. Tubes; 12SG7 RF, 12K8 Conv., 12SK7 IF. 12C8 IF, 12SK7 IF, 12SR7 Det., Avc. & Audio, 6Y6 output, 12K8 BFO. Freq. Range: 2 to 6 Mc (2 bands). Output Imp.; 4000 & 600 chms. Size: 13" x 8" x 15" Deep. Wt 47 lb. Complete with all tubes, NEW.....

DM-40 12V DC Dynamotor for above, NEW..... \$2.95 DM-41 24V DC Dynamotor for above, NEW..... \$3.25

BC-1033 RECEIVER



75 Mc. Three tube tuned RF reflex type receiver with a rectified output operates extremely sensitive relays in audio control work. Relay closes at 0.4 Ma, reopens when current falls to 0.2 Ma. Excellent basis for door opener, robot audio control of model planes, boats, etc. Converts to tone keyer for xmtr monitors. Excellent Used, CLEAN.....

R-58/ARQ-8 RECEIVER



Used with T-51 transmitter as a search and jamming set in 25 to 105 Mc range.

Receiver freq. controled by trans, oscillator and feedthru the coaxial connector on front of receiver which has a 20 Mc IF. Unit requires 115 V 400 cycle and 24 V for power, Complete with tubes; 1/9001, 3/68G7, 1/68G7, 1/6AG7, and 1/5y3GT, Size: 5\frac{1}{2}x7x22" Weight 25 lbs.

SCR-522 TRANSMITTER/RECEIVER

Designed to operate from 100 to 156 Mc. this unit makes fine 2-meter rig for 2-way mobile radio! Complete xmtg, rcvg remote control.

Power requirements: 28V DC at 12 Amps (PE-94 Dyn.) 12V DC at 24 Amps (PE-98 Dyn. 110 V AC 60 cps (RA-62 Rectif.)

Both units can be removed from case separately. Overall size: $16\frac{1}{2}$ "x1 $2\frac{1}{2}$ "x10 $\frac{3}{4}$ ". Weight 49 lbs. SCR-522 Transmitter-Receiver, complete with 18 \$3950 tubes, LIKE NEW.....\$

BC-624 Receiver with tubes Excellent Used......\$23.50 BC-625 Transmitter with tubes. Excellent Used......\$23.50 BC-602 Pushbutton Control Box NEW..... \$ 2.50 AN-104 Antenna, NEW.. \$ 1.75 PE-94 28VDC Power Supply Used.... \$4.75 NEW..\$ 7.95 PE-98 14 VDC Power Supply RA-62 AC Power Supply.. PUR. Miscellaneous Control Boxes & Connecting Plugs, Spare Parts & Accessories

TRANSMITTER/RECEIVER

SCR-510/BC-620

BC-620 Low Power VHF FM Pack Sets are designed for short range use. These sets are ideal for installation in vehicals for Amateur, Citizens Band or Commercial Applications.

SCR-510 consists of BC-620 Transceiver, Vibrator Power Supply, all accessories including handset, mast sections, manual etc, in 3 cases, BRAND NEW....

BC-620 Transceiver only, with all tubes, exc.used.....\$2250

Vibrator Power Supply for Trans ceiver, like new..... \$ 6.95

THE FAMOUS No. 19 MARK II

TANK TRANSMITTER-RECEIVER



One of the best buys on the surplus market today! 2 to 8 Mcs in 2 bands . (A Set) 15 to 25 Watts output depending on frequency and type of emission. CW and Radio Telephone. Also short range (B Set) band 230 to 240 Mcs. No.19 MARK III is VFO tuning, easy to convert to crystal operation. Sender/Receiver alone complete with tubes. Power requirements: 12V at 3A., 265V DC at 120 Ma and 540V DC at 50 Ma.

APN-1

TRANSMITTER/RECEIVER

RT-7/APN. FM Transceiver. Receiver frequency: 400-450 Mc. Transmitter frequency: 418 to

462 Mc. Frequency modulated by

moving coil transducer - heart of the W.W. Wobulator, Easily con-

cms. Complete with 14 tubes, 4-

12SH7, 3-12SJ7, 2-12H6, 2-955, 2-9004 and 1-VR150.

Exc. Used, as above.... 8.95

Indicator.....NEW \$ 4.75 SA-1A/ARN-1

Altitude Switch... NEW \$ 2.50

APN-1..... \$ 1.75

BC-AR-430

TRANSMITTER

Aircraft Transmitter for 24V DC

and two type 45 tubes, 0-1,5 amp

R.F. Ammeter and power output

approx. 25 watts. Voice modula-

NEW, with tubes..... \$495

Plug-in Coils for Above

Available from Stock

ted, less plug-in coils. Size: 6" H, x 6-3/8" W, x 11" D. Wt.

approx. 13 lbs.

operation. Contains two type 10

APN-1, NEW, with

tubes, dynamotor,

Mounting Rack for

ID-14/ARN-1

verted for Radio control or 70

New, With Tubes

L.F.O. Coils, Exc. Used: 0-16, 200-1500 Kc..... \$7.95 0-17, 200-600 Kc \$7.95 Shunt Capacitor, NEW .. \$2,50

Makes a very satisfactory "Ham"

Transmitter for 80, 40, 20 and

10 meters. With the Autotune

feature, you can preset the fre-

quency desired on any 10 pre-

100 watts on AM, CW or MCW.

Ten preset channels from 2 to

18;1 Mc. One: 200 to 1500 Kc.

Microphone: Carbon T-17 or Dyr

amic. Circuit: Two 811 Mod. 813

Power Amplifier. Power input 24

V DC at 25 Amp. Size: 12" High,

16" Deep, 24" Wide. Wt 70 lbs.

ART-13 Transmitter,

above, exc. used..... \$11.50 C-87 Pilot Control Box

NEW..... \$ 6.95

Frequency control: Master Osc.

selected channels. Power output

ART-13 Audio Speech Amplifier contains two 6V6GT and one 12SJ7 tubes, can be used for carbon or dynamic mike. Size 7x4x34". Wt. 4 lbs. Used...... \$5.25

ART-13 CF I Calibration Frequency Indicator & MCW Oscillator Assembly. Used to provide a constant crystal controlled standard of 200 Kc in order that frequency can be checked; also 1000 cycle tone. Supplied with 200 Kc crystal and two tubes. Size: 6x5x3". Wt. 3 lbs. \$5.95 Used.......\$5.95

Mount, Connecting Plugs, Handbook of Operating Instructions, Antenna Loading Coils, Spare Parts and Additional Accessor-

AVAILABLE FROM STOCK

ARC-1 TRANSMITTER-RECEIVER



2-METER TRANSCEIVER RT-18/ARC-1

Covers 100 to 156 Mc AM or CW with 832A final and push-pull plate modulation. Receiver has separate guard channel which can be preset for a net or club rag-chew frequency.

50 auto-tuned preset crystal con-trolled channels can be replaced with VFO for 2 meters. Power requirement: 350 V DC at 350 Ma and 24 V DC at 3 Amps.

Size: 21" x 11" x 7½" High. Shpg Weight 57 lbs. Supplied complete Excellent Used...... \$7950

with 29 tubes, 50 crystals

BC-223AX TRANSMITTER

25-Watt, CW, MCW, Voice, Crystal Control on 4 pre-selected channels in the frequency range of 2000 to 5200 Kc by use of three plug in tuning units (uses FT-171 Crystal) and var

Tubes used: 801 Oscillator, 801 Power Amplifier, two type 46 modulators and one type 46 audio modulators and one type 45 address maplifier. Voltages required: 12/24 V DC and 500 V DC at 150 to 200 Ma. O-3 RF meter and 0-300 V DC Milliammeter $2\frac{1}{2}$ ".

Black wrinkle case, size: 18"x 13"x7". Weight 40 lbs.

BC-223AX Transmitter, Brand New in original case with three Tuning Units..... \$26.50 As above, with two

PE-125AX Vibrator Power Supply for above, 12/24 VDC. New..... \$12.95 PE-135AX Dynamotor Power Supply for above, New., \$14.95 Connecting Cable with

two plugs...... \$3.50 FT-173 Mounts \$2.50 CS-56 Case...... \$1.50

APT-5 TRANSMITTER



AN/APT-5 consists of a lighthouse tube 3C22 oscillator in a precision tunable cavity modulated by 2 type 829B tubes driven by a 931 noise generating photo cell. Output approx. 30 watts CW. Power requirements: 115 V 400 cyc. Frequency Range 300 to 1400 Mc. Excellent Used con-

PP-104/APT-5 Power Supply for above. Two power supplies in one case. Two each type 1616 tubes for high

dition......

AN/ART-13 TRANSMITTER **TRANSMITTERS**



BC-191/BC-375

Famous GE 150 Watt Transmitter originally cost US Govt \$1800.00 Just the thing for beginner or old timer; has five tubes, five tuning units. Transmitter is designed to operate from 200 Kc to 12 Mc (minus the Broadcast Band). Equipped with antenna tuning unit BC-306-A - variometer and tap switch. Dynamotor (PE-73-C) complete with relay.
Will operate on 10 and 20 meter bands with slight modification. BC-191 Transmitter (for 12 V DC). With Tubes, NEW. \$4950 Excellent Used \$32.50

BC-375 Transmitter (for 24 V DC). With Tubes. Excellent Used \$41 50 Components Available, prices

on request: PE-73 24 VDC Dynamotor BD-77 14 VDC Dynamotor TU-5 Tuning Unit 1500-3000 Kc. TU-6 Tuning Unit 3000-4500 Kc.

TU-7 Tuning Unit 4500-6200 Kc. TU-8 Tuning Unit 6200-7700 Kc. TU-9 Tuning Unit 7700-10000 Kc. TU-10 Tuning Unit 10 Mc 12.5 Mc. TU-26 Tuning Unit 200-500 Kc. BC-306 Antenna Tuning Unit

Connecting Plugs RA-34 AC Power Supply

T-28 / APT TRANSMITTER



Mount

Radar-Jamming Transmitter covering the frequency of 140 to 210 Mc. Uses Tubes: 931 (Noise Tube) 2/832, 2/6C4

2/5R4, 3/6AC7, & 1/6V6, 1/6X5, Complete with tubes, 2/24 Volt Blowers, Power Supply 115 volt 400 to 2600 cycle. Osc., Amp., Plate, Grid Plate & Mixer Plate control on front panel, Size: 7½ x10x20", Wt 40 \$3250 NEW.....

BC-357 RECEIVER



75 Mc marker beacon signals. Power req.: 24 VDC . 158 Amps and 220 VDC at 4.5 Ma. Builtin 11,000 ohm plate relay, makes fine capacity relay or remote receiver for garage door opener, etc Exc. Used, Clean....

LIKE NEW.....\$14.50

AVAILABLE FROM STOCK

Frequency Range 20-27.9 Mc. (80 channels). Power Output: 2 Watts. Preset Freq.: 2. Freq. Control: Crystal Power Source: 6-12 or 24 V DC. Size: 7"x14"x15". Wt. 30 lbs.

ACCESSORIES: PE-120, 6, 12, 24 VDC Power Supply. TS-13 Handset. Tech Manual. Mast Base & Sections, etc. Brand new, packed in 3 original cases. Price Upon Request.

BC-603 FM

RECEIVER

GP-7 TRANSMITTER



\$4250

Navy's Plug-in Tuning Unit Transmitter tunes 300 Kc to 10 Mc. continuous with 6 tuning units. 125 Watt Xmtr., self-contained AC 400 cycle power supply. Uses suppressor grid modulation for phone, VFO controlled, 803 in final.

NEW, less tuning units. \$42,50 PLUG-IN TUNING UNITS: Range "A" 350-800 Kc. Range "B" 350-800 Kc. Range "D" 800-3000 Kc. Range "F" 3000-9050 Kc. Tuning Units, Each.... \$7.95

TRANSMITTER/RECEIVER



TRANSPONDER

RT82/APX-6 Radar Identification Set. Receiver-Transmitter covering range of 950-1150 Mc. (Car be converted to 1215, 1296 Mc). With 30 tubes: 6/6J6, 1/6AS6, 1/3E29, 3/6AL5, 1/5Y3, 2/3B24, 3/6AL5, 2/12AU7, 7/6AK5, 1/2C42, 1/2C46, 1/1B40, 1/1N43, 1/1N25. Digit counter on tuners for trans-rec-lo freq, controls. Voltage required: 24 and 115 V., 400/800 cycle. Size: 13"x13"x10" Weight 45 lbs. Excellent Used..... P.U.R.

BC-1335 TRANSMITTER/RECEIVER



PAGE 4

FM- 27 to 38.9 Mc. Crystal-controlled Transmitter-Receiver for 2-way Radiophone up to 10 miles. Can be powered from either 6V or 12 V DC. Size: 13"x13"x8". LIKE NEW COND..... \$1425

RT-34/APS-13 TRANSMITTER/RECEIVER



Designed to

Receive &

control at

a distance

5 separate


circuits or

devices by

means of

Easy to convert to 420 Megacycle Ham Band. Exceptional Buy - only a few left! \$795 Excellent Used, less tubes......

R-116/ARW-26 RECEIVER



650, 955, 1390, and 3000 cycles. Contains 1 stage RF-Det., 2 stage Audio, 5 tuned AF circuits. Has five 10,000 ohm relays, 7 3Q4 tubes, 1/9003 and 1/9002 tube. Compact 7x5x7". \$1295



Used in Aircraft to receive a modulated signal 90

& 150 cyc. on 332.6, 333.8 Mc. Operates from 24 VDC. Complete with tubes: 6/6AJ5, 2/12SN7, & 1/28D7. Size: $5\frac{1}{2} \times 6\frac{1}{4} \times 11$ ". Wt 12 lbs. Complete with tubes and

RECEIVER

LIKE NEW..... \$950 R-122/ARN-12



Airborne equipment, designed to receive radio signals to deliver aural and visual indication to aircraft pilot.

Received signal is fixed frequency 75 Mc AM modulated at 400, 1300 or 3000 cps. Operates from 24VDC Complete with tubes: 5/6AJ5, 2/6AL5W, 2/28D7. Has crystalcontrolled oscillator with 6,9 Mc IF freq. Size 10x5x6". Wt 8 lbs. In LIKE NEW

| T-26/APT-2 TRANSMITTER



This unit operates on 80/115 V 400 cycle AC. Contains 400-700 Megacycle oscillator circuit using two WE368A5 tubes. Other tubes included are: 2/5R4GY, 1/807, 1/931A photo multiplier, 1/6AG7, 1/2X2, 2/6AC7. Size: 8x10½ x20". Shpg wt 60 lb. Complete with all Tubes, NEW...... \$2850

DIVERSITY RECEIVER

Provides means for combining output of three receivers to pro-duce a single keyed audio output signal free from noise, interference. Suitable for use only in CW and MCW signals, not voice. Band-pass filter is for 600 to 1200 cycles. Output of each receiver indicated on 500 microamp meters. 600-ohm input and output impedance. Operates from 115/230 Volt 50/60 cycles, Can be rack-mounted, With tubes: 1/VR-150, 1/6F8, 3/6A6, 2/6SJ7 1/77, 1/1V, 1/80. Size 21x19x14" Weight 125 lbs.

BC-684 Transmitter BC-683 Receiver (27-39 Mc). Checked out, Supply for Transmitter

ADDITIONAL ACCESSORIES FOR ABOVE UNITS AVAILABLE FROM STOCK

BC-603 FM Receiver: Freq. Range 20-27 Mc. 10 preset push button channels or manual tuning. Has sensitivity and volume con-



BC-603 RECEIVER.....\$5.95

BC-604 FM TRANS MITTER



27.9 Mc. Output approx. 30 Watts. 10 crystal controlled channels. Tubes: 1619 1st Audio Amp., 1619 2nd Audio Amp., 1619 Osc., 1619 Doubler, 1619 Tripler, 1619 1st RF Amp., 1619 RF Rect., 1624 Power Amp. Size: 18" x $11\frac{1}{2}$ " x 10-3/8" Deep. Weight 60 lbs less dynamotor. BC-604 Transmitter New with Tubes......\$12 50 Exc. Used with Tubes, \$10.50 excellent used..... \$44.50 FT-237 Mounting Base for BC-603 and BC-604 units above, NEW...... \$ 6.95 DM-37 28 VDC Dynamotor Above, NEW \$4.75

AM & FM RADIO RECEIVER AN/APR-4Y



This is the only receiver we know of with such a tremendous frequency range! Ideal for amateurs, schools, experimental laboratories. Originally designed for AM reception, this receiver can easily be modified for

The equipment comprises one main unit, the receiver proper, and five tuning units. The receiver consists of Amplifier AM-27/APR-4 which is the IF, Detector and video channels, together with a complete self-contained power supply operating from 80 to 115 V AC at any frequency from 60 to 2600 cps. The power supply also furnishes power requirements of the tuning units.

The receiver measures $21 \times 10\frac{1}{2} \times 7\frac{3}{4}$ high, weight $31\frac{1}{4}$ lbs. Tuning units measure 15x9x62 wide and weigh about 193 lbs each.

In operating one of the tuning units is removed from its shock-mounted case and plugged into the receiver. Tuning units may be used separately as converters for use with any stanA 115 VOLT 60 CYCLE RECEIVER FOR FREQUENCIES FROM 38 TO 4000 MEGACYCLES!

LIKE NEW CHECKED OUT.......\$8850

dard receiver having 30 Mc IF; or may be used as RF unit around which a receiver may be built. RECEIVER CHARACTERISTICS: Freq. Range: 38-4000 Mc. Calib. Accuracy: 1% approx. Video Output: 1.5 V at 70 ohms. Audio Output: 100 Mw into 600 ohms. Sensitivity: 35 to 50 Mv average. Selectivity: 4 Mc wide position and

LIKE NEW, Checked Out ... \$8850 APR-4 AM Receiver

600 Kc Narrow position.

TN-1 or TN-16 38-95 Mc	\$35.00	
TN-2 or TN-17 74-320 Mc	59.50	
TN-3 or TN-18 300-1000 Mc	39.50	
TN-19 975 to 2200 Mc	59.50	
TN-54 2200 to 4000 Mc	119.00	

Note: Tuning Units TN-1, 2 and 3 are interchangeable with Tuning Units TN-16, 17 and 18 respectively. We will ship units in stock at time order is received.



The RDO was designed and built for use as a Microwave Search Receiver aboard Navy vessels. This set is very similar to the AN/APR-4. The RDO has complete metering of both RF and Audio circuits. The RDO utilizes the same plug-in RF Tuning Units as the AN/APR-1. This receiv-

er is ideally suited for monitoring and

measuring signals in the 38-4000 Mc

range. It is designed for operation on

RDO RADIO RECEIVER

An Improved Microwave Receiver Covering 38 to 4000 Megacycles. LIKE NEW CHECKED OUT.....

TECHNICAL CHARACTERISTICS: Freq. Range: 38-4000 Mc covered by 4 plug-in units. Calibrated Accuracy: 1% approx. Video Response: 60 cps to 2 Mc. Audio Output: 45 mw into 600 ohms. IF Freq.: 30 Mcs. IF Sensitivity: 4 Mcs wide position, 600 Kc Narrow position

Power input: 115 V A C 60 cps. Dimensions: 11x25x18" Deep. Weight: 100 lbs.



PAGE 6

115 volts 60 cycles AC.

R-105/ARR-15 COLLINS 51H-3 RADIO RECEIVER SET

This is a general purpose aircraft receiver designed by Collins Radio to replace the BC-348. This receiver has a built-in 10 channel auto tune system or may be manually controlled, It is extremely stable due to modern circuitry and use of Collins 70E-1 permeability tuned oscillators. Also has built-in crystal calibrator.

EXCELLENT USED......\$8850

TECHNICAL CHARACTERISTICS: Freq. Range: 1.5 to 18 Mc tunable in six bands.

AM and CW Power Input: 24 VDC at 2 Amps. Circuit: 14-tube. Dimensions: 23x10x10"

ASB-5 RECEIVER FOR 420 Mc. BAND

This handsome unit is supplied complete with ten tubes and shock mount. Tubes used are: 5/6AC7, 1/6H6, 1/6AG7, 1/6V6, 2/955. Overall size: BRAND NEW..... \$1275

Tuning Knob for ASB-5 Receiver.....



AN/APR-1 BROADBAND RECEIVER

40 to 1000 Megacycles

This is airborne receiving equipment, designed on a unit construction basis allowing IF units power supply and tuning units to be freely interchanged to give the receiver the facility of receiving all types of pulse and other signals, designed principally for radar search.

Frequency range 40 to 1000 Mc is covered by three interchangeable plug-in type tuning units. Information is presented by either aural means, thru headset, or by visual means thru cathode ray indicator.



PLUG-IN TUNING UNITS FOR AN/APR-1:

TN-1 38 to 95 Mc...... \$35,00 TN-2 74 to 320 Mc..... 59.50 TN-3 300 to 1000 Mc..... 39,50

TUNING UNITS FOR APR-4, APR-1, RDO

These tuning units are designed for use in the APR-4, APR-1 and RDO Receivers shown on this page. The tuning units are directly calibrated in frequency. Note that tuning units TN-1, 2 and 3 are interchangeable with tuning units TN-16, 17 and 18 respectively. ock at time order is received. All Tuning

We will ship uni	its in sto ed out in
TN-1 38-95 Mc. Like New	\$35.00
TN-2 74-320 Mc. Like New	\$59.50
TN-3 300-1000 Mc. Like New	\$39.50
TN-16 38-95 Mc. Like New	\$35.00
	-

or	king order.	
	TN-17 74-320 Mc. BRAND NEW	\$59.50
	TN-18 300-1000 Mc. Like New	\$39.50
	TN-19 975-2200 Mc. Like New	\$59.50
	TN-54 2200-4000 Mc. Like New	\$119.00

AN/ARC-3 RECEIVER & TRANSMITTER

100 to 156 Megacycles. Airhorne receiving and transmitting equipment designed to provide communications from plane to plane or from plane to ground. Remote op-eration on eight frequency channels. EASILY ADAPTED FOR HAM 2-METER BAND!

THE RECEIVER

8-channel crystal control, electric 12A6, 12H6, 12SH7, 12SL7, 2/12SN7, band change with tubes: 2/832, 3/12SG7 & 6/6AK5. Voltage required 2/6L6, 1/6J5, 3/6V6 & 1/12SH7, 24 VDC and 210 VDC 125 Ma. Size 11x7x15". Weight 21 lbs. ARC-3 RECEIVER Exc. Used with tubes.....\$2150

JUNCTION BOX for ARC-3 set, used to mount dynamotors DY-22 for receiver and DY-21 for trans. Also has connector plugs to hook up receiver, transmitter, control box and power, relays. Size: $10\frac{1}{2}x3\frac{1}{2}x8\frac{1}{2}$ ". Wt 7 lb.



THE TRANSMITTER

Voltage required 24 VDC and 410 VDC 325 Ma. Size: 154x124x72". Weight 21 lbs. Transmitter power output 8 watts AM. Exc. Used with tubes..... \$2150 PUSHBUTTON CONTROL BOX for receiver and transmitter. Has eight pushbuttons for channel selection and one for off. Size: 6x3x ". Weight 2 lbs. Used...... \$295

RADIO RECEIVER NAVY TYPE RAY-3

Navy Model RAY-3 is a high frequency amplitude modulated radio receiver, not for voice communication. It consists of a crystalcontrolled superhet receiver with dynamotor power supply in one cabinet. The receiver is designed to operate on any one pre-determined frequency in the range for which made. The audio system is designed for modulation frequencies from 20,000 to 120,000 cps. Tubes: 1/6AC7, 1/6A8, 1/6SJ7, 1/12SR7. Size: 10"x81 x124" deep. Weight 18 lbs. Weston output meter on front panel, also coaxial antenna and output connection, phono jack, on-off switch.



Model PR6N - 14 VDC. With tubes, dyn.....\$1250 Like New, Model PR7-NA - 28 VDC Like New, With tubes, dyn. \$1125

Circuit Diagram Included.

For your convenience, an ORDER BLANK will be found on page 21

SCR 274-N ARC-5 COMMAND RECEIVERS & TRANSMITTERS

The COMMAND SET Series of Receivers and transmitters are the most popular surplus items on the market today! This series consists of several units covering the frequency range of 190 Kc to 9.1 Mc for the Receivers and 2.1 Kc to 9.1 Mc for the Transmitters.

RECEIVERS



The Receivers are 6-tube super-hets using: 1/12A6, 1/12K8Y, 3/12SK7 and 1/12SR7. Designed to operate from 24 VDC Dynamotor which mounts on the rear of the set, supplying 250 VDC 60 Ma.

Size of	set: 5x5x11"	. Wt 6 1	bs.
		Exc. Use	
BC-453	190-550 Kc	\$18.95	\$23.50
BC-454		\$16.50	
BC-455	6-9.1 Mc		
BC-946	550-1500 Kc	\$ -	\$48.50
ADC-E	Donoissono		

ARC-	5 Receivers		
	1.5-3 Mc	s -	\$21.5
R-26	3-6 Mc	\$16.50	-
R-27	6-9.1 Mc	\$14.95	-
R-23	190-550 Kc	\$18,95	-
		CONTRACTOR N	

COMMAND SET COMPONENTS

BC-946 Double Receiver
Control Box, NEW \$1.49
BC-450 Triple Receiver
Control Box, NEW \$1.49
BC-451 Transmitter
Control Box, NEW \$1.15
Double Receiver Rack \$2.95
Single Transmitter Rack \$2.25

Double Transmitter Rack. \$2.45 4-Place Xmitter Rack.... \$3.49 DM-33 28 VDC Dynamotor for

DM-32 28 VDC Dynamotor
or Receiver, NEW\$3.95
DM-32AZ 12 VDC Dynamotor
or Receiver, NEW\$4.45

110 Volt AC Power Supply for all 274-N and ARC-5 Receivers, factory wired.....\$12.50 110 Volt AC Power Supply for Command Transmitters. wired.....\$25.50

COIL SETS USED IN COMMAND

CEIVERS		ĬĬ
Mc.	22	11 11
1 Mc	Each	\$1.5

85 Kc IF Transformers Also 2830 Ke, 239,Ke, 1415 Ke, 15 Me....Each \$1.50

TRANSMITTERS



The transmitters work well on CW and on phone at inputs of about 50 to 60 watts with any modulator capable of delivering 25 watts of audio power. Dynamotor used with the equipment is DM-33 24 V DC input with output of 575 VDC at 175 Ma. It mounts on the BC-456 Modulator. Transmitter tubes are 2/1625, 1/1626, and 1/1629 magic eye tube for crystal calibration.

Size: 5x7x12". Wt 9	lbs.	
	Exc. Used	NEW
BC-457 4-5.3 Mc	\$ 6.95	\$11.95
BC-458 5.3-7 Mc	\$ 6.95	\$12.95
BC-459 7-9.1 Mc	\$14.95	\$17.95
ARC-5 Transmitter	rs	Accepted
T-18 2.1-3 Mc	-	\$10.95
T-19 3-4 Mc	\$10.50	\$14.95
T-20 4-5.3 Mc.	\$ 6.95	\$11.95
T-22 7-9.1 Mc.	\$14 95	\$17 95



BC-456 MODULATOR For voice operation of Command Transmitters. Complete with Dynamotor Mounting, Tubes: 1/1625, 1/12J5, VR-150, Size: 7x8x10". Weight 10 lbs. Excellent Used..... \$2.75

Brand New..... \$4.95



BC-442A SWITCHING RELAY. Antenna Current Indicator with 19.5 millivolt movement, current transformer and thermocouple, 50 mmfd vacuum condenser, fixed 5000 V rating, CAN BE USED WITH ANY RIG......\$3.25 Flexible mechanical tuning cable or receiver & control box \$2.49 Connecting Plugs Available P.U.F. Tuning Knob for Receiver... 49¢

T-39/APQ-9 RADAR JAMMER



R-4/ARR-2 RECEIVER

11-tube aircraft unit for recention of double amplitude modulated carrier. Operates from 24 VDC & 250 VDC 60 Ma. Tubes: 3/6AK5 7/9001 & 1/12A6, Size: 5x5x11". Weight 6 lbs. Mounting is same a Command Sets. Complete with all tubes. Circuit diagram included. Dynamotor for ARR-2..... \$2.45



Consists of an RF Oscillator delivering 10 to 20 watts of RF power at any frequency between 500 and 585 megacycles, a noise source, a video amplifier and video driver stage, Tubes: 1/931A Multiplier photo tube; 2/6AC7, 1/6AG7, 2/8012, 1/1N21B, 2/807, Operates from 80 or 115 volts, 400 to 2600 cycles AC. Used......\$3950

The AN/ARC-5 VHF Radio Set consists of the following major units: Receiver, Transmitter, Modulator and Control

Receiver

fied for 12 VDC.

R-28/ARC-5 VHF RECEIVER Tunes 100 to 156 Mc AM. Easy to Convert for 2-Meter Operation! Ideal for installation in vehicles,

Excellent Used With Tubes......\$24.50



Transmitter

MODULATOR MD-7/ARC-5

For the ARC-5 transmitter series. With tubes, 1625 for push-pull 24V motor. Coils can be easily reoperation, plugs and outputs for both plate and screen modulation. Less Dyn, Shpg Wt 13 lbs. tubes and crystals, \$2350 Less Dyn, Shpg Wt 13 lbs. S1250 NEW. Start Sta Used, less tubes, xtals.... \$ 5.95 Set of Plugs for MD-7..... \$8.50



MODEL R-11A Long Wave Receiver, tunes 190

Boxes, Covers frequency range of 100 to 156 Mc in four preset Crystal controlled frequencies, Intended for

T-23/ARC-5 TRANSMITTER

24 VDC operation but can be modi-

Companion to the R-28, this VHF

Transmitter tunes 100 to 156 Mc.

has turret switching coils for all

channels are provided, using 4

wound for 6 and 10 meters!

Shpg wt 18 lbs. Complete with

stages. Uses 1625 Osc., 1625 Trip ler, 832A Tripler, 832A final. 4

separate coils in automatic turret

manually operated or with 12V or

to 550 Kc. Operates on 28 V DC. Late commercial type model. Excellent Condition..... \$1995

BC-749-A RADAR



This is a UHF Receiver in the 2-meter range.

Excellent Used, With Tubes..... Uses 12 tubes: 8/6AC7, 1/6H6,

2/955, 1/5T4. Tunable over entire range. Contains 24 V motor driven lobe switch which connects the various antennas to receiver and synchronize display on the indicator.

BROADCAST RECEIVER





This ARC model Broadcast Receiver tunes 550 to 1500 Kc. It operates on 28 V DC. Complete with tubes, Control Box for Remote Tuning,

\$4.95 Flexible Mechanical Tuning Cable..... \$2.49

ARC Model R-19 VHF RECEIVER



Tunable VHF Receiver, tunes 118 to 148 Mc in one band. Excellent Used......\$4995

This is a 9-tube superheterodyne with 3 tuned circuits of RF, 8 tuned circuits of IF at 15 Mc. Plus noise limiter, AVC & s2 AF stages, Operates from 24 VDC but can be modified for 12 VDC. Designed for remote control operation.

R-162 (SRR-1) RECEIVER

This is a unit of Navy Radio Set AN SRR-1. It operates on 110 V 60 cycles AC. Tubes: 14/6AK5, 1/6AL5, 1/6AG7, 3/6V6G, 1/5U4G, 1/6SJ7, 1/VR-75, Front panel contains DeJur 3½" 10 Ma Meter. Shock mounts included. Size: 10¾" 181" x 13". Complete, NEW..... \$2950



R-56 RECEIVER CODER UNIT



Made by Galvin Mfg Corp., this unit is designed to operated from 115 Volts 60 cycles AC, Tubes included: 6/6SL7, 8/6AC7, 4/ 6SN7, 5R4, 6AG7, 6SJ7, 2/6B4, VR-105. Overall size: 10" x 22" x 17" deep. LIKE NEW..... \$4250

RADIO SET SCR-583 TRANSMITTER and RECEIVER

TRANSMITTER & RECEIVER Frequency Range: 2.2 to 4.6 Mc.

Complete with all components and

RELIABLE VOICE & CW OPERATION IN TWO-WAY FIELD COMMUNICATIONS!

This equipment is designed to provide communication between motor vehicles and armored cars. CW and Voice signals are employed, with Amplitude Modulation. Provides reliable communication for distances up to 65 miles on CW and 35 miles on Voice. Suppressor Grid modulation is used.

The TRANSMITTER is a Master Oscillator-Power Amplifier type (MOPA), using 14 tubes: 7 each for voice and CW. Power output is about 8 watts on phone, 20 Watts CW. Calibration is provided by 200 Kc fixed crystal oscillator.

The RECEIVER is a 9-tube Superheterodyne with a 455 Kc IF. Zero-beating Transmitter to Receiver is possible. Modulator zero-beating Transmitter to Receiver is possible. Modulator acts as audio oscillator to produce sidetone on CW. POWER SUPPLY: 1.5 V supplied by dry cell battery, or storage battery, or hand generator. 6.3 Volt supplied by storage battery, hand generator or auxiliary power supply. 90 V Plate Voltage, supplied by dry cell battery or hand generator or vibrator. Ginal transmitter RF power amplifier: 500 V supplied by dynamotor, hand generator or auxiliary power supply. Grid bies for transmitter. -20 volts supply. Grid bias for transmitter: -20 volts.



SCR-284 (BC-654A) TRANSMITTER-RECEIVER

Frequency Range 3800 to 5800 Kc.

Complete with All Accessories

\$47500

This equipment is designed to operate either in a vehicle or on the ground. It provides CW or Voice transmission, Amplitude Modulated, 17 watts. It has a 455 Kc IF, and uses a dynamotor PE-103A and vibrator supply for 6 or 12 V DC.

THE RECEIVER: Continuous frequency range 3800 to 5800 Kc in one band. Beat Frequency oscillator on fixed frequency of 455 Kc. Output: 100 mw into two 8000 ohm headsets in parallel. Tubes: 3/VT-146, 1/VT-147, 1/VT-223, 2/VT-221,

THE TRANSMITTER: Continuous frequency range 3800 to 5800 Kc in one band. Calibration frequencies every 200 Kc throughout the band. Power output 20 watts into specified vehicle antenna. Tubes: 4/VT-221, 1/VT-225.

When this equipment is carried in the field away from a vehicle the components are grouped for a three-man load: Load #1: Radio Receiver & Transmitter BC-654A including

Key J-48-A. Size 18x14x9\frac{3}{4}. Weight 44\frac{3}{4} lbs.

Load #2: Generator GN-45, Cranks, Legs, Mast Sections, Insulator, wire, Bag Size: 9x6\frac{1}{4}x6\frac{3}{4}. Weight 22\frac{1}{2} lbs.

Load #3 Headsets, Counterpoises, microphone, guys, stakes, wrenches, screwdriver, accessories. Weight 25 lbs.




R-64/ARW-17 RADIO RECEIVER

Frequency Modulated, 30 to 42 Megacycles Operates from 24-28 V DC power source. New, complete with Tubes & Dynamotor.......\$1650

Small size, light weight radio re-ceiver designed to receive radio control channels carrying five FM control channels. Audio signals actuate corresponding control relays. Control action can be obtained on each control channel singly or on as many as three channels simultaneously. Tubes: 5/6AK5, 1/6AS6, 1/6AL5, 3/6J6. Size: 94x43x9" high, approx. Weight 19 lbs.

RT-7/APS-2 RECEIVER-INDICATOR



Exc. Used. With Tubes

.--

\$2995

RT-45/ARQ-1 TRANSMITTER-RECEIVER

milliammeters and all controls on front panel. Also requires 24 V DC for blower. Size 20x24x14". Wt 90 lbs.

Complete with All Tubes, Excellent Used

\$4950

This is a transmitting and receiving unit used for Inis is a transmitting and receiving unit used for radar and radio jamming in the frequency range from 14 to 50 Mc., tunable, Power input requirements are 80 or 115 volts, 400 to 2600 cycles AC. Tubes used are: 1/JAN-931A, 3/JAN-65G7, 1/JAN-6AG7, 1/JAN-6SJ7, 1/JAN-807, 1/JAN96J5, 1/JAN-2X2, 1/JAN-5R4GY, 1/JAN-5Y3GT/G,

CP-103/APA-44A RANGE COMPUTER



This beautiful piece of equipment is part of an aircraft computer landing system. It has a fine gear train and dial assembly, 2 motors, 2 autosyns, 2 micropots, slip rings, relays, rectifier, precision resistors, 12 "grain of wheat" lights 4 fold back spin type knobs, about 25 switches of all types. Will make a fine cabinet for a transmitter or receiver. Size 72x12½x8". Wt 22 lbs.

SCR-283 TRANSMITTER & RECEIVER

Frequency Range: 201 to 398 Kc and 2500 to 7850 Kc Complete, \$3950

Designed for aircraft having 24-28.5 V DC power supply systems. The receiver may be used to receive modulated or damped-wave signals. The transmitter provides unmodulated, tone-modulated or voice modulated signals. Included are: Receiver, Transmitter, Dynamotor unit, xmtg and revg Radio Control Boxes, Antenna Switching



Relay and Xmtg Coil Sets. (Some Revg Coil units available, P.U.R). Total weight approx, 50 lbs

T-41/APS-18 TRANSMITTER

Designed for 115 Volts 800 to 1400 cps. Tubes included are 2/15E and 1/15R. Complete with shock mounts and blower motor. Overall size: 7" x 8" x 18". BRAND NEW...... \$1295



ARB RADIO RECEIVER

Excellent Used, with Tubes & Dynamotor... \$3950

Broadcast, Marine, Mobile, Foreign, Amateur: 40,75,80 & 160 Meters, Operates on 24 V DC. Navy Model ARB is a general pur-

pose 4-band 6-tube communications receiver. Has provision for either local or remote control or both. Suitable for Boat, Car or Home. Illuminated dial, sharp & broad tuning, AVC, CW. Tubes: 1/12SA7, 1/12A6, 4/12SF7, Size: 8x7x16".

190 to 9050 Kc. Aircraft, Weather,

AC Power Supply for AR	
Wired	
Pilot Control Box, New	\$3.95
Remote Tuning Control	1000000
Box, New	\$2.95
Mount for Receiver	\$1.95
Connecting Plugs	
Tuning Knob	\$1.35
Flexible Mechanical	11.4
Tuning Cable	\$3,49

CRV 52233 TRANSMITTER FOR ARB



Weight 26 lbs.

CRV 52233 AT TRANSMITTER FOR ARB With Tubes...... \$2950 Tuning Units Tuning Units Dynamotor Supply NEW, Each...\$7.95 New(CRV 21724).. \$8.95

This unit covers 3000 to 9050 Kc. CW or phone. Designed for dynamotor operation. Power requirements: 380 V & 1000 V DC. Separate Ant. uning units cover 540-1500 Kc; 1500-3000 Kc; 3000-9050 Kc. Size: 7-3/16" x 10-3/8" x15½". Weight 35 lbs. Tubes used: 2/815, 2/6SN7, 1/1625, 1/VR-150.

Crystal filter, AVC & MVC Con-

18"x10" Wt. 38 lbs.

BC-348 RADIO RECEIVER

200-500 Kc & 1.5 - 18 Mc. 8-Tube 6-Band Communications Receiver Excellent Used, with tubes and Dynamotor, Checked out.... \$8250 Exc. Used, with tubes and AC Power Supply, Checked Out \$95

BC-312 Receiver similar to BC-348 but tunes 1.5 to 18 Mc in 6 bands. This is a locally controlled super-Power input 12 V DC. het receiver, designed to operate from 28 V DC source. Features: 2 RF Amplifiers, 3 IF Amplifiers, Excellent used, with tubes & dynamotor, checked out..... \$89.50 BC-314 Receiver similar to BC-348 trol and BFO control. Size: 10"x but tunes 150 to 1500 Kc in 4 bands. Power input 12 V DC.

Mount for above...... \$3.95 Connecting Plug for above.. \$2.25 Excellent used, with tubes & Dynamotor, checked out \$82,50

BC-929 US GOVT SCOPE INDICATOR

LIKE With all Tubes

BC-929 is a compact radar display unit with 3BP1, 2-6SN7GT, 6C8G, 6X5GT, 2X2, 2-6H6GT; high voltage divider

from -1600 V; intensity, focus and positioning controls, plus DPDT motor-driven switch. BC-929 is a favorite with TTY fans as foundation for a converter with cross-line scope pre-sentation. Also a Hams' favorite Modulation-Monitor foundation. Small size: only 84x9x16", weighs only 221 lbs.

TG-30 REPEATER



This is a DC Telegraph Terminal Repeater for transmitting to and receiving from another TG-30 or equivalent at a distant terminal on a half duplex basis. Includes: a VARIABLE 100-135 V. DC 400 Ma power supply, Audio Osc., 4 polarized relays, many precision parts! All in sturdy trunk $24\frac{1}{2} \times 14\frac{1}{2} \times 12$ ". Shpg wt 130 lbs. LIMITED QUANTITY

EE-99 TELEPHONE REPEATER



Voice frequency amplifier, four-wire thru or two-wire terminating for field use. Adjustable gain and equalization. Dual 2-stage amplifier with negative feedback. Freq range 300-3500 cycles. Uses 2/ 1N5 & 2/3Q5 tubes. Will operate from dry battery or PE-204 12 V vibrator pack. Size: 11½x14½x8" NEW------ \$895

DUAL SCOPE INDICATOR

LIKE NEW..... \$650



BC-1151 Radar Indicator, using 2 each 5FP7 Cathode Ray tubes and 6H6. Each tube has separate horizontal, vertical, focus, intensity controls, etc. Size $7x11\frac{1}{2}x14\frac{1}{2}$ ". Deflection Coil Demilitarized. No Power Supply.

ID-93/APG-13

INDICATOR SCOPE UNIT This indicator is used to give the

necessary information. Operating voltage is taken from the PO-43A power inveter. All controls are mounted on front panel. Uses a 3BP1 Cathode Ray Tube, and 5/ 6SN7, 2/6H6, 1/2X2, 1/5Y3, Controls: Horizontal, Vertical, Zero, Slope, Intensity, Focus, Marker Amplifier, Yards Range, Receiver Gain. For operation on 28 V DC, 115 V AC 380-1600 cps. Complete, NEW......\$1650

INDICATOR I-102-A

Displays the altitude of the aircraft in feet. It is designed for mounting on the instrument panel of the aircraft or equivalent location. The indicator is an electrostatic focus & deflection type cathode ray tube. Tubes used: 1/VT-112(6AC7), 1/1808 PL. NEW.....\$325

APA-11 TEST SCOPE

Excellent





Test Scope, Synchroscope, phlse analyzer ID-59/APA-11, Video amplifier is flat to 4 Mc. 3BP1 presentation. Test scope sawtooth 25-20,000 cycles. Has all normal test-scope controls. As synchroscope and pulse analyzer accepts positive or negative pulses. Video delay circuit permits leading edge of pulse to be seen. Calibrated dial horizontal shift measures pulse durations from 0.5 to 100 microseconds. Sine-wave oscillator calibrator measures recurrence rates from 200 to 6000 pps accurate within 0.4%. Built-in power supply requires 115 V 400 cycles, 196 watts. Shpg wt 60 lbs Complete with all tubes. Excellent Used...... \$29.50

ID-169/APN-12

RADAR RANGE OSCILLOSCOPE

NEW.....\$1695

Used with various type sets for indication of incoming signal in order that the range may be determined. Has vertical, horizon-tal, focus, sweep & intensity con-trols. Coaxial antenna changeover motor, also tubes: 3BP1, 2/6H6, 2/6SN7, 1/6G6, 1/6X5, & 1/2X2. Operates from 115 Volt 400 cycle & 24 V DC. Size 10x8x 22". Weight 40 lbs.

Excellent



APA- 17 SCOPE

ID-80A/APA-17 Radar Indicator 5". Amplifies and gives visual indication of the relative bearing of radio & radar signals in the frequency range of 250 to 1000 Mc. when used in conjunction with a receiver covering the same range. May be adapted for use on other freq. or con-verted for use as a test scope. Has all controls on front panel, also has selsyn motor attached to variable condenser that is used for scanning in synchronism with antenna motor. Complete with 1/5JP2 5" Cathode Ray Tube, 1/6SH7, 2/6AC7, 1/6SJ7, 2/6H6, 1/6V6, & 2/2X2. Has power supply for CR tube only that operates from 115 volt 400 cycle,

T-50/CPN-8 **MODULATOR &** TRANSMITTER UNIT



Operates on 115 V 60 cycles AC. Meters on panel: 0-50 DC Ma. 0-150 AC Volts. Tubes: 1/2J38 1/715B, 2/807, 1/VR-105, 3/3B24 1/5R4GY. Cramer time delay relays (3 meters): 2-sec., 20-sec., 2 minutes. Motor 115 V 60 cy. 1/40 Hp. 3 amp. 3400 rpm., 1 ph Overall size 11x22x17. Made by Galvin Mfg Corp. LIKE NEW..... \$3250

QUANTITY BUYERS - we invite your inquiries on quantity prices

FINE LORAN EQUIPMENT at TREMENDOUS SAY

For accuracy, for dependability, for all-around performance, you can't beat these superb navigational units! Now available as surplus Government Military Gear; originally made for U.S. Govt. by RCA, Philco, etc., at an acquisition cost of more than \$1500. Now you can buy them at a tiny fraction of their cost-while our stocks last!

AN/ARN-7 RECEIVER



Like New With Tubes \$1750

Designed primarily to be used as an aircraft navigational instrument. Basically equipment is a radio receiver using a superheterodyne circuit and certain additional circuits necessary for radio compass operation. Frequency range of 100 Kc to 1750 Kc covered in four bands Consists of Radio Compass Unit, Relay, Indicators, Control Boxes, Loop, Cords and Plugs. Ideal for conversion to home broadcast receiver addition to ham shack, etc. Operates from 115 volt 400 cycle and 24V DC. Complete with tubes: 4/6K7, 1/6L7, 1/6J5, 2/6B8, 2/6F6, 1/6N7, 1/5Z4, 1/6SC7, and 2/2051. Size 12x8x19". Weight 45 lbs. LIKE NEW, with tubes \$17.50 C-4/ARN-7 Control Box for above, excellent used..... \$3.95

NAVIGATION COMPASSES—INSTRUMENTS

ACCESSORIES FOR ABOVE

BK-22 Relay & Junction Box FT-213 Receiver Mtg base. LP-21-LM Loop Antenna AVAILABLE FROM STOCK

I-81 3" Azimuth Indicator



GYRO FLUX GATE COMPASS TRANSMITTER

AN5751-1. Contains gyroscopically stabilized flux gate, which is sensitive to earth's magnetic field. Transmits signal by autosyn motor to remotely located master indicator. Dia. 8½", Depth 9". Wt 7½ lb.



GYRO FLUX GATE COMPASS MASTER INDICATOR

AN5752-1. Indicates compass direction received from transmitter, re-transmits indication to repeater indicators throughout aircraft. Dial size 4". Depth 7". Wt. 61 oz. Luminescent dial face.



GYRO FLUX GATE COMPASS AMPLIFIER

AN5753-1. Components part of gyro flux gate compass, amplifies signal transmitted from master indicator to repeater indicators. Size 11x92x7". Weight 122 lbs.

SET OF THREE UNITS DESCRIBED ABOVE.....\$8850

LORAN APN-4 RECEIVER



INDICATOR Excellent Used.....\$8850 The components of this receiver are the finest money can buy! Makes excellent fixed tuner for medium freq. police calls or public address syst.

APN-4 is a four-channel long range navigation receiver and indicator (dual units) which will provide, for ships and aircraft, an exact position by the reception of known loran transmitters. Compact two-piece set with separate receiver and indicator. Indicator has large 5-inch Cathode Ray Tube. Very popular on fishing boats and commercial ves-sels. Operates from external 12V or 24V DC power supply. Has 43 tubes including CR tube.

Has four screw-driver tuned RF channels selected by switch - IF frequency 1050 Kc. IF band width 45 to 60 Kc. RF frequencies 1600 Kc to 2000 Kc. Tubes: 2/2Y2, 1/5U4 AVAILABLE FROM STOCK 3/6B4, 1/6SU7, 1/6SA7, 4/6SK7,

RECEIVER &

1/6SN7, 1/6SL7, 1/6H6, 1/VR150. R-9B & ID-6B/APN-4 Loran Receiver & Indicator, exc.used \$88,50 R-9A & ID-6A/APN-4 Loran Receiver & Indicator, reconditioned, Like New..... \$79.50

R-9/APN-4 Receiver Only, Used, less tubes.....\$3.95 ACCESSORIES FOR ABOVE PE-206 Inverter

MG-149H Inverter 12V or 24V Transistorized Power Supply Two Shock Mounts Set of 11 connecting plugs All Replacement Parts Prices Upon Request

LORAN APN-9

RECEIVER &

APN-9 is a four-channel loran receiver and indicator (one unit) designed to provide ships and aircraft an exact position by reception of known loran transmitters.

Consists of a receiver, operating in the marine band, and indicator using a 3" cathode ray tube for presentation of the received signals. Operates from 24 V DCand 115 V 400 to 800 cycles, Ideal where space is at a premium. Size: 91x121x301". Weight 36 lbs.

This system is accurate to within 1% of the distance of the ground loran transmitter.

ACCESSORIES FOR APN-9 PE-206 28V DC Inverter MG-149H Inverter Shock Mount Set of 2 Plugs 12V or 24V Transistorized Power Supply Rubber Visor

Antenna Coupler AVAILABLE FROM STOCK Prices Upon Request

WE CARRY A COMPLETE LINE OF REPLACEMENT PARTS FOR APN-4 AND APN-9 LORAN SETS

MN-26C RECEIVER



Excellent Used With Tubes & Dynamotor \$1795

Remote control commercial type navigational receiver.

Designed for Marine & Aircraft installation. Also fine for home use. Covers 150 to 1500 Ke in 3 bands. Continuous tuning from MN-28C Control box. Complete with 24 volt DC Dynamotor, tubes: 5/6K7, 2/6N7, 1/6B8, 1/6F6, 1/6L7, 2/6J5, and

MN-26C Exc. Used......\$1795 control box. MN-26Y Radio Receiver, 150-325 Ke; 325-695 Ke; 3-4.7 Mc. Comdynamotor, NEW......\$1525

MN-26 LB Compass & Communication Receiver, 200-410 Kc; 550-1200 Kc; 2.9-6.0 Mc. Works on 24 VDC. Complete with tubes and dynamotor. \$2450 Excellent Used.....

ACCESSORIES FOR ABOVE MN-28C, MN-28Y Control Boxes MN-20E Loop Antenna, Azimuth Control Box, Right-Left Indicator Flexible Mechanical Cable, RF Cable, Tech Manual, Set of Connecting Plugs, Nul Meter AVAILABLE FROM STOCK

AN/ARN-6 RECEIVER

\$2150



Although lighter and more compact than other automatic radio compass equipment, this is one of the most efficient of the airborne direction finding systems.

Frequency range: 100 to 1750 Kc covered in four bands: 100 to 200 Ke; 200 to 410 Ke; 410 to 850 Ke; 850 to 1750 Kc. Power requirement: 28 V DC. Control Box

AS-313B Antenna Connecting Cables Mount AVAILABLE FROM STOCK Prices Upon Request



BC-778 GIBSON GIRL TRANSMITTER

EMERGENCY SOS TRANSMITTER

Famous "Gibson Girl" transmits standard SOS signal on 500 Kc just by cranking generator. Also, can be keyed manually. Sea range is up to 500 miles! 2 tubes: 12SC7 and 12A6. 1000 cycle tone modulation. Size 13"x10"x9". Shpg Wt 16 lbs.

BC-433G

CHECKED OUT....\$2450 Excellent used,

COMPASS RECEIVER 200 to 1750 Ke.

3 Bands, 15 tubes Used for Aircraft Direction finding can also be used for boats. Consists of a 6-tube superhet receiver, with additional circuits for aural reception. Operating voltages required: 115 volt 400 cyc., and 24 VDC. Complete with tubes: 4/6K7, 1/6L7 1/6J5, 2/6B8, 2/6F6, 1/6N7, 1/6SC7, 2/2051 and 1/5Z4. Size: 12"x8"x19". Weight 45 lbs. LIKE NEW

CONDITION......\$1450 BC-434 Control Box for Above, Like New..... \$3.95 COMPLETE ACCESSORIES FOR ABOVE, AVAILABLE



T-69D RADIOSONDE

T-69D/AMT-2 Radiosonde Transmitter, Has 5910 and 5703 miniature tubes. Manufactured by Molded Insulation Co. Size 23" x 5"x62". Shpg wt 1 lb. NEW......98¢

RADIO-TV RECEIVING & SPEC. PURP. TUBES

ALL NEW TUBES, in Original Cartons and Government Surplus Tubes, removed from equipment. These are all FIRST QUALITY TUBES, at money-saving prices!

Type N	let Each	Type Ne		Type No	et Each		Net Each
1A6	. 35	5CP1	4.50	12A6	. 29	724B	. 30
1AB5	.48	5CP7A	5.25	12A6 12A6M	. 24	725A	14.50
1B3GT	60	5D21	3.90	12AH7	.40	726A	6.25
1B22	1.10	5FP7	1.40	12AH7 12AX7	. 55	728EY	21.50
1B26	. 65	5FP7A	4.75	12BE6	. 39	730A 800	2.25
LB32/532A	. 35	5J29	7.50	12J5GT 12SG7M	. 35	800	.30
LB40 LD7G LE7G	.70	5JP2A	10.50	12SG7M	.60	807A	1.90
D7G	.40	5MP1	3.90	12SG7Y	.70	814	3.50
E7G	.40	5T4M	. 65	12SH7M	. 40	815	
LLA6	. 85	5V4	. 50	12SQ7GT	.80	832	4.00
L4	.85	5V4GA	1.05	12SQ7GT 12SR7GT	. 55	832A	4.00
LB4 LP25A	. 75	5Y3/6106 6-11	. 50	14E6	. 25	836 837 841	1.75
P25A	7.50	6-11	. 70	15-Amp Tun	gar	837	2.50
Q22	3.95	6-11 6AC7 6AD7G 6AG5 6AJ5 6AR6/6098	. 45	Bulb	6.00	841	.30
Q23	3 25	6AD7G	1.10	15R	. 49		
S4	60	6AG5	. 40	FG-17/5557	2.75	860 861	23.50
U4	.60 .41	6AJ5	1.05	94 Δ	65	864/VT-24	. 21
Amp Tung	rar	6AR6/6098	. 50	VT95/10V	30	866A	1.45
Bulb	1.75	6AS6	. 55	251.6G	.50	872A	3.50
2A7	.40	6AS6 6AV6 6AX4GT 6B8G 6BG6G	. 45	25L6G 27 28D7 33 34	.30	874	. 40
2C40A	8 50	6AX4GT	.50	28D7	.40	902A	2, 20
2A7 2C40A 2C42 2C46	2 75	6B8G	43	33	.30	923	. 80
2012	2.15	6BG6G	70	34	.30	932A	1.45
2C46 2C51	.70	l hCh	55	35/51	.35	954 954	.14
		6D6	55	35W4	.25	055	35
2C52	2. 25	GE 5	75	DELSE	.35	955	. 22
2E36	1.65	6D6 6E5 6F5 6FSM	. 15	REL36 39/44 43 50	.15	957 1274 1611 1613 1616	1.15
2J21A	3.10	CECM	. 15	19	.90	1274	1.45
2J22	7.50	6F6G	.70	50	.65	1011	1 10
2J26	7.50	0100	. 70	50 EE50	.40	1613	1.10
2J27	5.40	6F8G 6H6M	.50	EFDU	.50	1616	. 55
2J31	11.50	6H6M	. 41	00 D0	.75	1619 1624 1625 1626	. 25
2J32	11 -0	654	. 55	V 1-52	.35	1624	1.20
2J33	11.50	69 2 M	. 75	71A	.30	1625	. 35
2134	8.50	6J4 6J5M 6J5GT 6J6	.55	77	.35	1626	. 22
2J33 2J34 2J36 2J39	8.50	090	. 20	50 EF50 50B5 VT-52 71A 72 77 78 VR78 FG81A	.35	1629	.00
	0	6J6W 6J7M	.60 1.20	10 11D79	.40	1630/VT-1	28 .70
2J41	32.50	637M	1.20	FG81A	2 25	1633 1960 1961	. 4:
2J48	9.50	6K6GT	. 60	84/6Z4	.41	1960	4 77
2J50	12.50	6K7G	. 50	00	30	1961	4. 7
2K25/723A/	B 10.50	6K7GT 6K8	. 50	HY114B	.16	2013	. 0:
2V3G	. 35	6K8	. 85	H 1114D	.95	2014	. 00
2V3G 2X2 2X2A	. 21	6L5G	. 50	117Z3		5528/C6L	5. Zi
2X2A	. 55	6L6M	1.50	VT-127A	3, 95	5557/FG17	
3-16	. 36	6L6G	. 95	211/VT4C	2.25	5657	60.00
3A8G 1	. 35	6Q6/6T7G		217C	3.25	5692	1.7
3B23/RK22		6Q7G	. 55	251A	21.50	5762/7C24	
3BP1	4.75	6SA7Y	. 70	QK284	59.50	5814/12AU	
3C22	6.50	6SC7M	1.15	313CD	1.75	5846	11.50
3C33	2.75	6SF5G	. 55	316A	.50	5932/6L6W	/GA 2.2
3CP151	2.20	6SL7	. 65	336A	1.75	5948/1754	60.00
3DP1	1.75	6SN7GT	. 60	350B	1.45	5953/C3P1	4 11.50
3FP7	. 80	6SU7GTY	. 85	371A	. 42	5965	. 70
3HP7	1.75	6U7G	. 45	GL411	14.50	6024	4.50
3J31	22.50	6V6G	. 55	417A	9.50	6072	. 6
3JP7	4.75	6V6GTY	. 60	GL471A	. 55	6080	1.8
3Q4	. 45	6W4GT	. 60	531	3.10	6097	. 45
3S4	. 55	6X5GT	. 45	559	. 40	6147	1.19
4A21	1.50	6ZY5G	. 45	CUE-583	. 49	6397	2.10
4B22/EL5E		7A5	.40	700A	55.00	6414/6829	. 20
4J26	14.50	7A6	. 45	702B	. 55	7193	. 10
4J32	24.50	7AK7	.41	705A	. 45	8011	. 7
4J39	75.00	7F8	1.10	708A	. 25	9001	. 7
4J50	39.50	7H7	. 35	709A	. 55	9002	. 4
4J53	55.00	7Y4	.75	715B	3.25	9004	. 2
VT-5	. 65	7Z4	.55	717A	. 21	9006	. 2
5AP1	2.25	9LP7	3.25	720A	10.50	0000	
EL5B	1.65	10Y	. 35	721A	1.15		
- 101	1,00				E-100 (C-100)		

any type of Receiving, Transmitting or Special Purpose Tubes at lowest current prices !





DIVISION OF BOR WHAN & SON ELECTRONICS, INC.



PRESSURE TYPE CRYSTALS

TYPE 243 EACH 3 for \$2.00

Type FT-243. A most rugged type having .093 pins and .486 pin spacing (1/2"). Designed to operate on frequency in 32 mmfd oscillator circuit. The quartz crystal in this holder is either .5" x .5" or .5" x .6" and is held between two stainless steel electrodes by spring pressure. It is by far the most popular crystal of its type in use. Some of the government sets in which the FT-243 is used are: (Maximum drive 50 milowatts) BC620, BC659, BC611, BC1335, RT111/TRC20, R415/FRC20, R19/TRC-1, RT77/GRC9, BC1306, RT30/PRC1, AN/AMT3, BC1000, AN/PRC5, T87/TRT1, R397/TRL1 and many others. The following frequencies are in stock for immediate

		guaranteed	± 1 KC α	as listed in
ilocycles				7740
4045	5825	6530	7416	7745
4090	5850	6538	7425	7750
4095	5852.5	6550	7440	7758
4215	5875	6575	7450	7760
4220	5892.5	6600	7458	7770
4229	5900	6625	7466	7775
4255	5910	6650	7475	7783
4295	5925	6675	7480	7785
4340	5950	6694	7483	7790
4395	5955	6700	7491	7791
4445	5960	6725	7500	7800
4490	5975	6750	7505	7816
4535	6000	6760	7510	7820
4620	6025	6775	7518	7825
4695	6040	6800	7525	7830
4735	6042.5	6825	7538	7833
4785	6050	6850	7550	7850
4795	6075	6875	7558	7855
4852.5		6890	7570	7860
4950	6125	6900	7575	7866
4995	6150	6910	7580	7870
5165	6175	6925	7591	7875
5235	6185	6950	7600	7880
5295	6200	6975	7610	7886
5385	6225	7000	7616	7891
5582.5		7230	7620	7900
5660	6250	7270	7625	7910
5675	6275	7300	7641	7916
5690	6300	7308	7650	7925
5700	6325	7316	7660	7930
5720	6350	7325	7670	7933
5725	6375	7340	7675	7940
5730	6400	7341	7680	7950
5740	6425	7350	7690	7958
5750	6440	7358	7700	7960
	6450	7370	7705	7966
5775		7375	7710	
5780	6470 6475	7373	7710	7970 7975
5782.5				
5800	6500	7400	7730	7983
5820	6525	7405	7733	8000

FT-243 AMATEUR BAND CRYSTALS **UNCONDITIONALLY GUARANTEED**



40-meter general	7000 to 7300	fundamental	7000-7300
40-meter novice	7151 to 7199	fundamental	7151-7199
20-meter general	14,000 to 14,350	double	7000-7175
20-meter general	14,000 to 14,350	triple	4667-4780
15-meter general	21,000 to 21,450	triple	7000-7150
15-meter novice	21,100 to 21,250	triple	7034-7082
10-meter general	28,000 to 29,700	X4	7000-7425
6-meter gen. & tech.	50 MC to 54 MC	X6	8334-8900
2-meter general	144 MC to 148 MC	X18	8001-8221
2-meter novice	145 MC to 147 MC	X18	8056-8166
2-meter tech.	145 MC to 147 MC	X18	8056-8166

CRYSTALS IN STOCK FOR IMMEDIATE DELIVERY LISTING IN KILOCYCLES

	LISTING	IN KILOCI	CLES	
680	8082	8225	8361	8494
3800	8086	8227	8367	8497
8825	8100	8233	8375	8500
8840	8103	8236	8380	8525
3980	8110	8240	8385	8530
3995	8125	8250	8387	8541
025	8126	8256	8390	8550
7030	8138	8260	8391	8560
7050	8143	8264	8400	8566
7070	8148	8266	8405	8570
136	8150	8270	8412	8575
7152 to	8154	8272	8425	8580
198 ± 1KC	8160	8273	8430	8583
3008	8164	8275	8431	8592
3020	8166	8280	8438	8600
8025	8170	8283	8440	8620
3030	8171	8295	8450	8625
3035	8175	8300	8463	8630
3040	8177	8301	8464	8650
3045	8188	8317	8465	8675
3050	8191	8318	8475	8700
3058	8198	8330	8480	8710
3065	8200	8333	8481	8797
3070	8210	8340	8483	8820
3075	8212	8341	8486	
3077	8220	8450	8490	
8080	8224	8357	8491	

We guarantee to supply crystals within \pm 3 KC from those ordered.

> ADD 5¢ PER CRYSTAL FOR POSTAGE OR 10¢ PER CRYSTAL FOR AIRMAIL

FUNDAMENTAL FREQUENCY

in HC6/U HOLDERS

ORDER BY TYPE AND FREQUENCY

HERMETICALLY SEALED CRYSTALS


The CR18/U is a hermetically sealed plated crystal fundamental frequency to be used in parallel oscillator circuit of 32 mmfd. Tolerance is .005% from -55° to +90° Centigrade. It may be used to double, triple, or quadruple, to any desired frequency. Maximum drive is 10 milowatts.

		VERSEN VERS	CONTROL OF THE		6153.70	6905	7465	8216.25	8637.5	1
833.0	2198.75	2628.25	2998.75	4229	6159.25	6907.5	7473	8221.42	8650.0	- 1
1300.0	2202.50	2636.0	2998.91	4252	6164.81	6916	7515	8228.5	8661.11	- 1
1325.	2207.06	2639.0	3000.0	4300.0	6173.70	6922.22	7516.66	8223	8666.66	1
1400.0	2207.583	2640.0	3005	4310	6175.92	6925.0	7548:75	8227.5	8683.3	1
1500.0	2208.31	2646.0	3008	4485		6927	7561.11	8228.57	8705.55	1
1569.	2209	2647.0	3020	4495	6181.48		7575.0	8233	8750.0	- 1
1665.0	2212.06	2650.75	3035.5	4750.0	6183.33	6933		8236.3	8775.0	
1718.0	2214.56	2654.25	3052.5	4765.62	6187.03	6938	7585			
1725.0	2217.93	2658	3105.0	4843	6192.59	6944.44	7591.66	8240	8786	
1735.0	2219	2660.0	3143.5	4854	6198.14	6950.0	7600.0	8240.00	8783.3	
	2219.75	2662.0	3154	4859.5	6200.0	6955	7637.5	8248.0	8790	
1765.		2665.75	3156.5	4900.5	6203.70	6961	7638	8250.0	8791	
1771.75	2223.25		3158.5	4993.75	6216	6966	7650.0	8253.3	8808	
1773.12	2226	2669.5	3161.5		6258.30	6972.22	7665	8258.33	8842	
1781.	2230.25	2677.0		5000.0	6261.11	6977	7683	8261.11	8850.0	
1786.62	2237	2680.75	3166.0	5093.75	6316	6983	7715	8268.75	8887.5	
1786.87	2240	2681.0	3181	5109.37	6330	6986	7750.0	8273.33	8910.0	
1843.75	2243.50	2684	3192	5111.71	6366	6988.88	7758.33	8275.0	8950.0	
1845	2246.0	2688.25	3203.5	5131	6400.0	6994	7775.0	8285	8977.5	
1849	2247.75	2689.30	3207.25	5139	6425.0	7000.0	7822.22	8287.77	9019.44	
1900	2250.0	2694	3217.5	5147.90	6450.0	7005.5	7838.88	8292.31	9026	
1911.95	2253.5	2695.0	3231.5	5156	6455	7010	7850.0	8294	9027.5	
1915.40	2264.0	2695.75	3233	5158.59	6500.0	7022	7867	8296	9045	
1916	2265.25	2702	3239	5164	6516	7027.7	7886	8300.0	- 9061.11	
1918.85	2281.25	2703.5	3240	5172	6528	7030.55	7887.5	8302	9067.5	
1922.30	2293.75	2710.5	3248.87	5195	6554.44	7038.88	7894 .	8307	9108.33	
1925.75	2294	2710.75	3253.62	5261	6555.98	7061.11	7925.0	8317.5	9125.0	
1927	2298	2711.25	3255	5275.0	6591.66	7083.3	7960	8338.46	9135.0	
1931.0	2320	2715.0	3265	5277	6605	7091.66	8000.0	8342	9141.6	
1937.50	2362	2716	3285.0	5285.0	6618.75	7100.0	8006.66	8340	9150.0	
1939.55	2365	2723	3375	5295.5	6627	7105.55	8040.0	8346.15	9300.0	
1985	2368	2726.5	3400	5325.0	6638		8043	8347.5	9322.5	
1987	2375.0	2730.0	3566,66	5335.93	6650	7111.11		8350.0	9327.77	
2001	2381	2732.62	3650.0	5337.90	6661.11	7137.5	8064.28	8352.7	9337.5	
2007.50	2388.25	2737.75	3683.33-	5355	6694	7150.0	8071.4	8358	9350.0	
2028	2388.75	2751.0	3691.66	5421.87	6705	7172	8078	8362	9375.0	
2055	2394	2762.37	3693	5437.5		7185.5	8085	8372.2		
2064.65	2395	2773.5	3716.66	5555	6708.75	7247.5	8090.76		9412.5	
2072	2415.0	2782.0	3726.66	5580	6716.66	7250.0	8091.66	8376.92	9427.5	
2086.25	2418.0	2794	3733.33	5610	6727	7258.33	8107	8385	9472.5	
2135.75	2437.5	2805	3742.66	5626	6738	7260	8126.2	8387.5	9500.0	
2146.75	2442.75	2807	3759	5730	6750.0	7270	8137.5	8407	9537.5	
	2445			6005.28	6758.3	7278	8140.0	8415	9547.5	
2151	2449.5	2812.5	3768	6038.62	6761	7305.55	8142.8	8435.7	9552.77	
2157.37		2820.75	3777		6765.55	7338	8148	8450.0	9562.5	
2158	2453.95	2855.25	3783.33	6061	6772.22	7345.0	8152	8452	9572.22	
2159.5	2475.0	2870.0	3805	6091.66	6783	7365	8157.14	8469.2	9577.5	
2168.75	2494.0	2877.0	3812.5	6098.14	6788.88	7375	8160	8471.4	9579.16	
2170	2500.0	2877.5	3814	6103.70	6800.0	7383.75	8164.28	8500.0	9637.5	
2172	2502.66	2887.0	3842	6109.25	6805	7387.5	8167.05	8516.6	9662.5	
2172.25	2506.0	2894.0	3851	6116.93	6840	7395.0	8169.23	8527.7	9683.33	
2174	2594	2910	3870	61.20.37	6850	7400.0	8171.2	8547.2	9697.5	
2176.50	2604	2914	4000.0	6125.92	6872.23	7415.0	8176.92	8550.0	9705.0	
2178	2612.0	2931	4020	6131.48	6877	7518.33	8183.3	8552.7	9750	
2184	2618.0	2971.16	4055.55	6137.03	6883.33	7425.0	8185.71	8572.2	9777,77	
2185.62	2622.5	2987.75	4203.70	6142.59	6887.5	7428	8192.85	8584.6	9787.5	
2194.12	2624.5	2990.0	4210	6148.14	6888.75	7435	8199.09	8598	9794.44	
					****	21.00 0	2222	0611	0000	

CRYSTALS LISTED ARE FUNDAMENTAL FREQUENCIES. WE WILL MAKE TO ORDER ANY FREQU-ENCY FROM 2000KC TO 12000KC IN HC6/U HOLDER .Qgg TOLERANCE AT

BE SURE TO SPECIFY EXACT FREQUENCY AND CIRCUIT IT IS TO BE USED IN TO INSURE COPRECT CORRELATION.

DELIVERY ON SPE-CIAL FREQUENCIES CAN BE MADE IN 48 HOURS AFTER RECEIPT OF ORDER.





Excellent Used.... \$11.50

INPUT: 27 VDC 32 Amps. OUTPUT: 400 VDC 750 Ma. 750 VDC 350 Ma Size: 6½ x 8 x 12". Wt. 30 lb.

BD-77 DYNAMOTOR



Excellent Used.... \$19.50

INPUT: 28 VDC 39 Amps. OUTPUT: 1000 VDC 350 Ma. Size: 62x10x11". Wt 38 lbs. With fuses and starting relay.

PE-73 DYNAMOTOR

NEW..... \$21.50 INPUT: 28 VDC 19 Amps. OUTPUT: 1000 VDC 350 Ma.

CARTER GENEMOTOR



NEW.... \$4.95

INPUT: 5.9 VDC 32 Amps. OUTPUT 405 VDC .270 Amps. Fine for mobile ham gear. Built-in hash filter

CARTER MAGMOTOR



NEW.... \$2.65

INPUT: 6 VDC 3.6 Amps OUTPUT: 250 VDC .030 Amp #MA2503S.

CARTER ROTARY CONVERTER

NEW......\$9.95 ..

INPUT: 115 VDC 3.5 Amps. OUTPUT: 115 VAC 250 Watts 60 cycle, Fine for TV, Tape recorders, phonographs, etc. Size: 101x5x41". Wt 23 lbs.



CRV-21724 NEW....

\$8.95

Black & Decker. Input: 27.5 V DC at 7.4 Amps. Output: 425 VDC at 320 Ma. Filtered, Con tinuous duty, 72 x52 x7".



Bendix 651. Input 28 VDC at 4 Amp. Output 425 VDC at 163 Ma, with filter, 92 x6x6".

D-401 EICOR



LIKE NEW.... \$2.95

INPUT: 27 VDC 6.05 Amps. OUTPUT: 300 VDC 200 Ma. 18 VAC 2.2 Amps

D-101

LIKE NEW......\$2.95 INPUT: 27 VDC 1.25 Amps. OUTPUT: 255 VDC .06 Amps.

D-300

NEW..... \$9.95 INPUT: 12 VDC 11.3 Amps. OUTPUT: 425 VDC .2 Amps.

DA-161A

NEW...... \$9.95 INPUT: 26 VDC 5.0 Amps. OUTPUT: 265 VDC . 220 Amps 50 VDC .05 Amps. With filter base.

DAG-33A



NEW.... \$3.95

INPUT: 18 VDC 3.5 Amps. OUTPUT: 450 VDC 80 Ma. Size: 4x4x6". Weight 6 lb. Shaft size: 1x1. Supplied with one end bell.

DM-18-A

NEW......\$3.95 INPUT: 13 VDC 3.3 Amps. OUTPUT: 220 VDC .100 Amp.

DM-21 DYNAMOTOR



Excellent Used.... \$8.95

INPUT: 14 VDC 3.3 Amp. OUTPUT: 235 VDC 90 Ma. Size: 6x5x3". Wt 81 lbs.

DM-28 DYNAMOTOR



Excellent Used.... \$5.95

· INPUT: 27.9 VDC 1.25 Amp. OUTPUT: 220 VDC 70 Ma. Size: $3\frac{1}{2}x5x6\frac{1}{4}$ ". Wt $5\frac{1}{2}$ lbs.

DM-32 DYNAMOTOR



Used......\$2,45 New....\$3,95

INPUT: 28 VDC 1.1 Amps. OUTPUT: 250 VDC 60 Ma. Size: 3x34x42". Wt 3 lbs.

TYPE 35-X-032 (similar to DM-32 but 12 V.) INPUT: 14 VDC 2.4 Amps. OUTPUT: 250 VDC 60 Ma. NEW..... \$4.45

DM-53A DYNAMOTOR

INPUT: 28 VDC 1.4 Amps. OUTPUT: 220 VDC 80 Ma. NEW, with Base.... \$5.95 NEW, less Base ... \$3.25 USED, less Base.... \$1.49

DM-33 DYNAMOTOR



PRICE UPON REQUEST INPUT: 28 VDC 5 Amps. OUTPUT: 575 VDC 160 Ma. Size: $3\frac{1}{4}x4x7\frac{1}{2}$ ". Wt $8\frac{1}{2}$ lbs. Available NEW and LIKE NEW.

DM-34 DYNAMOTOR



\$4.45

NEW

INPUT: 14 VDC 2.8 Amps. OUTPUT: 220 VDC 80 Ma. Size: 3x4½ x6¼". Wt 5 lbs.

DM-36 DYNAMOTOR

INPUT: 28 VDC 1.4 Amps. OUTPUT: 220 VDC 80 Ma. USED..... \$2.25 NEW.....\$3.95

DM-35 DYNAMOTOR



\$19.50

INPUT: 12.5 VDC 18.7 Amp. OUTPUT: 625 VDC 225 Ma. Size: $4\frac{1}{2} \times 4\frac{1}{2} \times 8\frac{1}{2}$ ". Wt 13 lb.

DM-37 DYNAMOTOR

INPUT: 25.5 VDC 9.2 Amp. OUTPUT: 625 VDC 225 Ma. NEW.....\$4.75 Excellent Used......\$3.75

DM-40 DYNAMOTOR



NEW.... \$3,25

Used.....\$1.95 INPUT: 14 VDC 3.4 Amps. OUTPUT: 172 VDC 138 Ma. Size: 54x32x7". Wt 7 lb.

DM-41 DYNAMOTOR

INPUT: 28 VDC 6 Amp. OUTPUT: 172 VDC 138 Ma. NEW \$3.95

DM-42 DYNAMOTOR



NEW.... \$8.95

INPUT: 12 VDC 39 Amps. OUTPUT: 515 VDC 215 Ma. 1030 VDC 260 Ma. Size: 7x7x11", Wt 38 lbs.

DM-43 DYNAMOTOR

INPUT: 28 VDC 23 Amps. OUTPUT: 515 VDC 215 Ma. 1030 VDC 260 Ma. NEW..... \$29.50

DM-45 DYNAMOTOR



NEW.... \$4.25

INPUT: 24 VDC 1.1 Amps. OUTPUT: 250 VDC 50 Ma. Size: 3x3x4½". Wt 3 lbs.

DM-25 DYNAMOTOR

INPUT: 12 VDC 2.2 Amps. OUTPUT: 250 VDC 50 Ma. NEW..... \$4.45

DM-65 DYNAMOTOR



NEW.... \$11.95

INPUT: 12.5 VDC 28 Amp. OUTPUT: 440 VDC 400 Ma. Size: 41 x41 x8". Wt 15 lbs.

DM-310A DYNAMOTOR

#11523. INPUT: 28 VDC 2 Amps. OUTPUT 350 v 80 Ma. NEW..... \$1.95 DM-310A - #11522 INPUT: 28 VDC .5 Amps. OUTPUT: 100 VDC 10 Ma.

DM-414 (BD-BL-69)

NEW..... \$1.95



NEW.... \$3.95

BD-69, Eclipse or Eicor. INPUT: 14 VDC 2.8 Amp. OUTPUT: 220 VDC 80 Ma. 4200 RPM, cont. duty. Filtered. Size: $6\frac{1}{2}$ x6 $\frac{1}{2}$ 42".

DMFX

NEW..... \$5,95. INPUT: 28 VDC 5 Amps. OUTPUT: 330 VDC .250 Amp.

DY-5A/ARR-3 DYNAMOTOR

INPUT: 24 VDC. OUTPUT: 220 VDC .080 Amp. With filter base assembly. SPECIAL..... \$8.95

DMF-519H

NEW......\$3.95 INPUT: 28 VDC 17.5 Amps. OUTPUT: 600 VDC 500 Ma.

DY-25/AXT-2

NEW..... \$6,95 USED......\$4.95 INPUT: 26.5 VDC 25 Amps. OUTPUTS: 775 VDC . 225 A. 405 VDC . 345 A. -53 VDC .050 A. 18.3 VAC 3.7 A. (95 cycles)

DYNAMOTORS - INVERTERS

Used.... \$2,49

INPUT: 28 VDC 1.25 Amp. OUTPUT: 250 VDC 60 Ma. Size: $3\frac{1}{4}x5x5\frac{1}{4}$ ". Wt $3\frac{1}{2}$ lb.

PE-94C DYNAMOTOR



New... \$6.95

Excellent Used..... \$3.95 INPUT: 28 VDC 10.5 Amps. OUTPUT: 300 VDC 260 Ma. 150 VDC 10 Ma. 14.5 VDC 5 Amp. Size: 5x8x12". Wt 35 lbs.

PE-98 DYNAMOTOR

INPUT: 14 VDC 21 Amps. OUTPUT: 300 VDC 260 Ma. 150 VDC 10 Ma. NEW..... \$9.95 Used..... \$4.45

PE-101-C DYNAMOTOR

INPUT: 13/26 VDC 12.6/6.3

Amps.
OUTPUT: 400 VDC 135 Ma.
800 VDC 20 Ma.

and 9 V 80 cyc. 1.12 Amp. Size: 14x4½ x7". Wt 15 lbs.

Connector Plug..... \$1.50

PE-103 DYNAMOTOR

Ballentine. Size: 6x12x18". INPUT: 6/12 VDC 21/11 Amp.

OUTPUT: 500 VDC 160 Ma.

Continuous duty. With filters, starting relays. Wt 53 lbs.

PE-119A INVERTER

Excellent Used.....\$11.95

FRA105-KVA575. INPUT: 25/28 VDC 36 amp.

OUTPUT: 80 VAC 800 cps.

90% PF., 1 phase.

NEW....

\$6.95

NEW....

\$29.50



EICOR DYNAMOTOR

DY-42A/APW-11

NEW...... \$6.95

INPUT: 26.5 VDC 2.2 Amps.

OUTPUT: 350 VDC .080 Amp.

DY-44A/U

NEW..... \$6.95

OUTPUT: 12.9 VDC 3.5 Amp.

DYA-4115F

NEW.....\$5.95

INPUT: 25.4 VDC 5.2 Amp.

Output: 550 VDC .130 Amp.

MOTOR GENERATOR

NEW.......... \$9.95 #5AM31RJ37

GE AMPLIDYNE

INPUT: 27 VDC 75 Amps.

1000 Watts. 7500 rpm.

Shunt wound.

OUTPUT: 60 VDC 16.7 Amp.

With filter - carrying case

INPUT: 28 VDC 3 Amps.

With filter base.

and cables.

-80 V .010 Amp.

NEW.... \$4.25

INPUT: 28 VDC 2.5 Amp. OUTPUT: 19 VAC, 105 cps, at 2.1 Amp. 40 W. 100 % PF., 6300 RPM, cont. duty, ball-bearing, basemounted, filtered. Originally for C-1 Autopilot, 72 x32 x54" Wt. 10 lbs.

MG-149F INVERTER



Wt. 201 lbs.

Used..... \$12.95

made by Holtzer-Cabot. INPUT: 24-28 VDC 36 Amp. TWO OUTPUTS: 26 VAC 400 cps., 1 phase, 250 VA., 40% PF. 115 VAC 400 cps., 1 phase, 500 VA., 90% PF, 6000 rpm. Has governor for frequency control with "hi-lo" switch to change output voltages. Radio noise filtered, 12x8x7".

MG-149H INVERTER



Excellent Used.....\$14.95 Like New.....\$21.50 Holtzer-Cabot.

INPUT: 28 VDC 44 Amp. OUTPUT: 26 VAC 400 cps. 250 VA., 1 phase - and -115 VAC 400 cps. 500 VA., 1 phase.

PE-135-AX DYNAMOTOR PE-86 DYNAMOTOR

NEW..... \$14.95 INPUT: 12/24 VDC 16/8 Amp. OUTPUT: 500 VDC 0.2 Amp. With filter base.

PE-186 DYNAMOTOR

NEW..... \$9.95 INPUT: 28 VDC 11 Amp. OUTPUT: 400 VDC .4 Amp. With filter Base.

PE-206 INVERTER



NEW.....\$89.50 Like New...... \$79.50 Excellent Used..... 69.50 For use with APN-9 and APN -4 Loran. Made by Leland. INPUT: 28 VDC 38 Amp. OUTPUT: 500 VAC 800 cyc. at 500 VA. 1 phase. and 80 VAC 800 cyc. at 500 VA. 1 phase.

PE-218 INVERTER



NEW......\$29.50 Like New.....\$19.50 INPUT: 24/28 VDC 80/90 A. OUTPUT: 115 VAC 13 Amp. 400 cyc. 1 phase, 90% PF. Carbon pile voltage regulator with freq. adjustment. Radio noise filtered. 8000 RPM. Shpg wt 75 lbs.

PIONEER GENEMOTOR

NEW......\$5.95 INPUT: 5.6 VDC 17 Amp. OUTPUT: 525 VDC .1 Amp.

PE-125 MOBILE PIONEER GENEMOTOR VIBRATOR SUPPLY

INPUT: 9 VDC

#3534-1 Leland.

Size: 72 x112 x112"

OUTPUT: 450 VDC.

With blower fan assembly.

NEW..... \$2.95

SE-2 #3534-1

Excellent Used.. \$21.50

OUTPUT: 115 VAC 750 VA.

INPUT: 272 VDC 45 Amp.



NEW..... \$12.95 INPUT: 12/24 VDC 141/71 A. OUTPUT: 500 VDC 160 Ma. With starting relays, filters, fuses, vibrators, 10x11x72".

G & G RADIO SUPPLY COMPANY • 75-77 Leonard Street, New York, N.Y. 10013

New......\$11.95 Collins 21881 INPUT: 12 VDC 14.5 Amp. OUTPUT: 400 VDC 200 Ma. 225 VDC 100 Ma.

TCS POWER SUPPLY

WEBSTER DYNAMOTOR

Size: 72 x7x13". Wt 28 lb.

NEW..... \$2.95 INPUT: 9 VDC 7.5 Amp. OUTPUT: 405 VDC .095 Amp. Less 1 end bell.

X-3516-1 INVERTER



LIKE NEW..... \$24. 50 INPUT: 27.5 VDC 165 Amp. OUTPUT: 115 VAC 2500 Va., 400 cyc. 1 phase. Size: 15x11½x8". Wt 58 lb.

5DY82AB34

Excellent Used......\$1.59 INPUT: 12 VDC 1.2 Amp. OUTPUT: 120 VDC .02 Amp.

800-1 INVERTER



Excellent Used.... \$10.95

Input: 24 VDC 75 Amp. Output: 115 VAC 800 cyc. 1 phase, 10.5 Amp. Size: 4½ x8x12". Wt 35 lb.

TYPE 41 20

Excellent Used..... \$4.25 INPUT: 11.5 VDC 12.5 Amp. OUTPUT: 550 VDC .175 Amp.

12117-6-B



\$2.95

Used......

Made by Pioneer-Bendix. INPUT: 24/28 VDC 1 Amp. OUTPUT: 26 VAC., 400 cps. 1 phase, 6 VA., 40% PF. Will operate up to 4 autosyns or magnesyns without power factor correction and up to 18 if corrected. Radio noise filtered. Base mounted.

12123-2-A INVERTER

NEW..... \$5.95 INPUT: 24 VDC 8 Amp. OUTPUT: 115 VAC .15 Amp. 30 VA., PF.3 3-phase, 400 cycle. Made by Pioneer.

PAGE 14



This unit is a component of the AN/APS-3A Aircraft Radio Equip-ment. It is designed to supply power to the transmitter in pulsed form. Modulator tubes: 1/829, 1/ 715B, 4/72R, 1/73R, A motor in the unit is used for cooling the driver tube. Overall size: 154x154 x 173". Wt. 63 lbs. Operates on 115 V 800-2400 cps. LIKE NEW......\$4950

RADIO TRANSMITTER & RECEIVER SCR-178



Transmitting & Receiving Frequency 2.4 to 3.7 Mc. This equipment supplies field communications on CW, Tone or Voice, up to 100 miles. Power source is hand generator supplying 8 & 500 V DC, or dry batteries. Tubes used are: Receiver: 2/30, 2/34. Transmitter: 1/10, 1/865. Modulator: 2/30 . Total weight 200 lbs. \$7450

TS-102/AP TEST SET



Range Calibrator TS-102/AP is a portable pulse generator that produces a marker pulse and a synchronizing pulse used in calibra-ting range units of radar receivers. Marker output pulse: 0 to 30 V. Repetition frequency: 327, 800 pps. Synch. Output pulse: Amplitude: 30 to 50 V into 72 ohms. Duration: .8 usec. Temp. Range: -40 C. to +1200 C. Repetition Freq.: 400/800/1600 or 2000 pps. Tubes: 1/5Y3GT, 5/6AC7, 2/6AG7, 2/6SN7GT. Size: 14 x 25 x 18". Wt. 37 lbs. New......\$3950

DUMMY ANTENNA LOAD



3-inch pyrex feedthru insulator, 1000 ohm 100 watt resistor with two test leads and clips. Cabinet size 13x6x4". Cabinet can be used for a chassis. LIKE NEW..... \$395



BRAND NEW.... 3345 Excel. Used \$1.95

Easily converted to home or office intercom system!. Uses pair of 1619 tubes, delivering 10 watts of audio power. Massive construction, suitable for shops, factories, Finest parts used. Conversion diagram and instructions included.

TS-59/APN-1 TEST SET



This is a range calibrator, used in testing altimeter equipments. It is part of Radio Set AN/APN-1 Frequency range: 440 to 450 Mc. Attenuation: 75 db (max). Delay: 4 usec.

Temp. Range: -10°C, to +52°C. Accuracy: ±2% at center of range. This unit is self-contained in single instrument case. No external power source needed. Overall size $20\frac{3}{4}$ "x9"x20 $\frac{1}{2}$ " high. Complete with interconnecting cord assemblies, T adapter plugs and maintenance handbook, Wt. 60 lbs. \$6950 Like NEW.....

TS-62/AP ECHO BOX

9320 to 9430 Megacycles



Portable ringing cavity for radar testing and general microwave research. Has loaded Q of 50,000 to 80,000. Used as a target simulator in radar maintenance, for relative power measurements, spectrum analysis, frequency checks, etc. Impedance 50 ohms. Resonance and relative power indicated by meter deflections. Shpg wt 15 lbs. **\$7950** LIKE NEW......

Butterfly Condensers

AN/APR type tuners, can be used for ultra high frequency transceivers, freq. meters, oscillators.



TN-3A 300-1000 Mc. 21" dia. 21" deep. Each.... \$395 TN-2A



106-330 Mc. 41" dia. 3" deep. Acorn socket for 955 tube. \$395 Each.....\$3



TN-30 135-485 Mc 4½" dia. 2½" deep. Each.....\$395



C-3553 300-1000 Mc. 23" dia, 2" deep.




Has two input circuits, each feeding a single 6SN7GT twin triode amplifier. The unit is complete with 115 volt 60 cycle power supply which uses 6X5GT rectifier. Finest components. All transformers hermetically sealed. Vibrationproof chassis on 4 rubber shock-mounts. Size: 53"x24"x43". Weight 11 lbs.

PACKARD-BELL PRE-AMP.

NEW

\$795



SERVO AMPLIFIER

Less Tubes, 95¢ With Tubes \$1.95.

Made by Sperry. Contains 2/1632, 1/1633, 1/1634. Many excellent parts: mica condensers, dozens of color coded 1 -watt resistors, two dual and 4-section bathtub condensers, 3 transformers, two wafer switches, one volume control, 4 octal sockets. In ventilat-

ed aluminum drawer cabinet 83"x

4½"x3¾". Works on 115 V 400 cy.

AM-300/A1C PUSHPULL AMPLIFIER



4-tube PP power amplifier with dynamotor, works on 28 V DC. Automatic gain control. Includes barometric device for operation from 10,000 to 30,000 ft. Will operate 6 or more station jack boxes. Shpg wt 15 lbs.

AM-142/A1C AMPLIFIER



Single tube pushpull amplifier, used as audio line booster and mixer. Input 500 ohms, output 600 ohms. Operates from 24 V DC. Complete with one 26A7 tube and schematic. Size 5x5x2". Wt 21 lb. Excellent Used......\$145

TS-51/APG-4 TEST SET

NEW \$6950



Designed for adjusting and calibrating Radio Set AN/APG-4 bomb release equipt. It is connected to permit signal from transmitter section to pass thru the test set before it is applied to the receiver section. Operates from 26 or 13 V DC. Variable motor speed controls frequency increase. Equipment includes Phase Modulator and Case, size 15½ x8¼x15¼", 8' Transmitter ant. cable with connectors, 8' Receiver antenna cable with connectors, and Battery Input and Relay Output Cables with connectors, each 8'. Total wt. 40 lbs. Manual included

TRANSMITTER



Operates on 465 to 515 Mc


Designed for airborne use as part of an AEW system. It relays the radar video, together with synchronizing signals, to surface control station for presentation on indicator. Tubes used: 2/7F7, 1/6AB7, 1/6V6GT, 1/6H6, 1/829B, 2/6SN7, 2/6AR6, 1/5V4, 1/3C22. Size: 21¹/₄ x10 x10 x8". Weight. 57 lbs. \$5950 TRANSMITTER, NEW....\$5950



POWER SUPPLY PP-104/APT-5 Separate assembly consisting of two power supplies: High voltage power supply delivers 1000 V at 150 Ma.

Low voltage supply delivers 400 V at 500 Ma. Power input 115 Volts 400-2600 cycles. Size: 214x5x8". Weight 37 lbs. POWER SUPPLY. NEW.....\$2950

SCR-298
TRANSMITTER & RECEIVER



FM FREQUENCY RANGE 30 to 40 Megacycles Designed for mobile two-way communication. Consists of 25-watt mobile FM transmitter, mobile FM teceiver, synchronous vibrator type power supply, designed to work on 6 V DC. Tubes used. Transmitter: 3/7C7, 2/7A8, 1/7C5, 1/807. Receiver: 2/6AC7, 1/6K8, 1/6V6, 6SH7, 1/6K8, 1/6SJ7, 2/6H6 1/6SL7GT, 1/6K6GT. Wt 55 lbs. Manual included. LIKE NEW......\$7925

AM-26/A1C PHASE INVERTER AMPLIFIER



4-tube pushpull power amplifier with phase inverter circuit. Used in aircraft intercommunication. Carbon mike input, hi and low impedance output, with volume control. Normally operates from 24 VDC. Makes excellent conversion to dandy 9-watt amplifier. Size: $9\frac{1}{2}x5\frac{1}{4}x5\frac{1}{4}$ ". Wt. $6\frac{1}{2}$ lbs. Complete with tubes and dynamotor. Excellent used...... \$995

BC-347 AIRCRAFT AMPLIFIER



Used in small planes for speech. Has two ouncer transformers, carbon mike input, standard headset output. Requires 12 or 24 v and 250 V DC. Uses 6F8G tube. Size: 3x2x5"/ Wt 3 lbs. NEW...... \$195

PANEL METERS



WESTINGHOUSE 0-50 DC MILLIAMMETER 3½" Round

Each..... \$450

G.E.

0-15 D.C. AMPS.

3½" Round, Rear

Each..... \$295

G.E.

0-25 D.C.

MILLIAMMETER

21 Round, orig-

inal boxed. \$225

WESTINGHOUSE

2" Decibel Meter.

Each.... \$245

GEN'L ELECTRIC

0-300 D.C. MILLIAMMETER

21" Round. Black-

face, silver mark-

ings, original box-

Each..... \$275

GEN'L ELECTRIC

DECIBEL METER

\$195

-16 to +3 Db.

Round.

TRIPLETT

0-1.5 R.F. AMMETER

2" Round, Flush

mounting, less

Thermocouple.

FS - 5 Ma. at

TUNING METER

resistance.

2" tune for maximum

Each..... \$1.95

WESTINGHOUSE

0-150 Volts AC

2" Panel Mount-

ing. **\$245**

VOLTMETER

B & K MFG CO.

3" Square Meter

DeJUR-AMSCO

Flush mtg.

3" Square Meter

0-800 Milliamps.

0-1 Ma. movement,

Dial reads: 0-1, +0

-10, +0-100, +0-1000.

Each.......\$345 Flush mtg.

scale. 2 Ma. right,

Flush mounting.

& WESTON

Flange. Depth: 1-7/8". 75 div.



MILLIAMMETER 0-1 Ma. Movement. Scales: 0-2 and 0-40. 3½" round. \$395 Each..... \$395



ROLLER-SMITH 0-10 D.C. MILLIAMMETER 3½" Round "Plate Current'

Each.... \$175



0-200 Microamp. DC METER 23" Round, Sealed Case. Black face. Scales: 0-5, 0-20. "Pulse Width". With mounting plate in original Each..... \$395



GEN'L ELECTRIC 0-6 R.F. Amps. 2" Round, flush mtg. SC-IS-182. Each..... \$295



240-0-240 DC AMMETER $2\frac{1}{2}$ " Round, 1-7/8" mtg. ctrs. Black face, luminous markings, zero Each..... \$265



DeJUR-AMSCO 0-50 DC MILLIAMMETER 2" Round. \$275



DeJUR-AMSCO 2" Meter 0-30 V Scale 0-1 Ma. Movement. Flush mounting. \$219



2" Milliammeter 0-1.2 Ma. Flush mounting. Scale: 0-100. 0-100. Each..... \$175

WESTON - G.E.



HOYT 0-150 Volts DC VOLTMETER Round, flush mtg. Model #17-L. \$319



WESTERN ELECTRIC 1-0-1 Milliamperes 3" Round Center read ing to each side. Flush Each..... \$395



MARION Carrier Level Meter S-1 to 9, 20-40 db. 24" Round, flush mtg. Each..... \$395

DUAL METER 0-100 Microamps. Needles at centers of both scales. Readings: Tune 2:1, Coup. 4:1. "Do not read SWR unless tuned". Weston model 827, type 31.

Each..... \$525

VISUAL

INDICATOR

Model S-47

Dual movement,

0-500 Microamps.

Mounting centers $3\frac{1}{2} \times 3\frac{1}{2}$ ". $4\frac{1}{4}$ " deep.

NEW..... \$275

SPERRY

GYROSCOPE

Electrically

operated gyro which shows

aircraft attitude

in dive-climb

and banked pos-

TWIN INDICATORS

Indicator azimuth &

sighting angle type

HEATHKIT

AC VOLTMETER

Used, but very

clean condition

Limited Supply

\$1295

itions. Operates on 115 volts 400

26 volts 400 cycles. Two 3" Indica-

Like New..... \$395

WESTON

4" Round.

Set for 2 sec. 50/70 cycles, 115 volts. SPDT switch 10 amps. 3" Square, 21" deep. Each......\$650





GEN'L ELECTRIC 4" Meter, center reading to each side: 1-0-1 Ma. Illuminated face, flush mtg. \$395




LEFT-RIGHT RADIO COMPASS INDICATOR Used with MN-26 Series Radio Receivers.


NEW, each. \$495



I-81A 3" INDICATOR

0-36 degree scale contains a matching autosyn that was used with the LP-21 LM \$245 LIKE NEW.....





TEST INDICATOR BE-67



Ranges: RMS Volts: .01, .03, .1, .3, 1.0, 3.0, 10, 30, 100, 300. Output: Db., -40, -30, -20, -10, 0, +10, +20, +30, +40, +50. In oak case 8" x 5\frac{1}{4}" x 5", with leather handle, hinged cover. Contains 0-200 Microamp. full scale. Overall size: 82" high with handle, 4-5/8" wide, 44" deep. Meter face 3" Round 0-1 DC Milliammeter made by Hickok, relay, phone jack, and 50,000 ohm potentiometer. Designed 4x2". 50" power cord and plug. for testing military equipment,



AMMETER 0-15 Amps.

3½" easy reading scale, 75 divisions, Black plastic case, $4\frac{1}{2} \times 5\frac{1}{4} \times 2\frac{1}{4}$ ". Rubber covered test clip leads plus black metal carrying case with hinged cover. \$365 BRAND NEW.....



BRAND NEW \$995

TEST SET

This is a current flow type relay adjusting set. It measures and con trols current flow thru winding of relay, drop, or similar unit being tested. DC Milliammeter has three ranges: 0-15, 0-75, 0-150 Ma.
3" Panel Meter. Overall size: 83" x54x54". Weight 9 lbs. This handsome unit is housed in massive metal cabinet with latching cover.



and teletype voltage measurements. With adaptor plug, schematic, metal carrying case. Batteries not needed for operation. \$495

BIAS METER



In heavy leather

carrying case, with 6-ft 2-cond, rubber covered test lead cable. Overall 7"x 32" x 22"

QUANTITY BUYERS - we invite your inquiries on quantity prices

HS-23 HEADSET

The standard high impedance magnetic headset. Uses R14 units (4000 ohms

each). HB-7 leather-covered adjustable headband, and quick-disconnect black PL-54 bail-out plug. This is the resonant magnetic (undamped clamped diaphragm) type, extra desirable for MCW, but also very clear on speech. \$475 NEW. less cushions.....

Used.....\$2.75 HS-33 HEADSET similar to above, but low impedance, 600 ohms, flat response 200 to 4000 cps. Comp-

lete with 18" side mounted cord with PL-354 plug: less cushions. NEW..... \$5.45 Used..... \$3,25

RUBBER EAR CUSHIONS

MC-162A Flat type for HS-23, HS-33, and similar units. NEW...... Pair 50¢ CHAMOIS EAR PADS Fit most earphones. NEW....Pair \$1.50

LARGE SPONGE RUBBER Earphone cushions for 24" elements. NEW Pair 29¢



CORD

Extension for cords with PL-54 plug as used on headsets. 65" long with JK-26 jack and PL-55 plug. NEW.....\$1.35

CD-604 CORD

with impedance mat ching transformer 500 ohm to 4000 used with HS-30 Headset. 6' cord with PL-54 plug.

CD-605 CORD similar to CD-604 Cord but with PL-55 plug instead of PL-54, and this cord is 30"950 long. NEW......950



CD-318 CORD Has press-to-talk switch and 41 branch

ending in standard 3-circuit mike plug PL-68. NEW.....\$125



MC-385 High to Low Impedance HEADSET ADAPTER

For use with headsets HS-33, HS-38 or other high impedance phones Jack for PL-55 on one side of case (input), PL-55 plug on other side, NEW..... 59¢


HS-30 HEADSET 256 ohms. Soft rubber hangs in your ear lobes below (not in) your ear canals.

Lightweight headband and cord 9" long. Used......\$1.45



HS-17 HEAD & CHEST SET ASSEMBLY Headset phones 30

with rubber cushion Microphone 50 ohms with 8-ft cord & PL-58 plug fits EE-8 field fone. Weight 5 lbs. Excellent used...........\$395



Press-to-talk switch on side makes mike circuit before control circuit. Latest model.

NEW......\$850 Exc. Used, Weight 2 lbs. Checked out.... \$4.95



most uses. 2 microphones mounted in rubber neckpiece with

elastic neckband. Operates between 100 & 300 ohms.

Carbon type 100 ohm, 50 db below millivolt, flat response, with PL-291 2-cont male plug, 11" \$125 NAVY-TYPE LIP MIKE, similar to T-45; made by Western Electric NEW..... \$1.25

W.E.BREAST MIKE Single button carbon mike with breastplate. Very sensitive, complete with 6-ft cord and W.E. plug. NEW.....\$1.29



DESK MICROPHONE Signal Corps Carbon Type. Used by "Hams' and professional recording studios, broadcasting, public address, etc. Telephone type with sensitive clear tone. Complete with cord and plug. With and without switch.

LIKE NEW...... \$395

R-14 SPEAKER 1000-ohm earphone element with PL-54 plug and cord. Called "Mine Detector Resonator"



TS-9 HANDSET

Has butterfly type press-to-talk switch. Standard Signal Corps handset. 50/75 ohm carbon button. 135/600 ohm (1 kc) magnetic rcvr capsule, 3-cond.cord. \$375 Excellent Used......\$375

TS-13 HANDSET



Battery powered. Receiver: 3500 ohms impedance, Transmitter: 50 ohms. Both in single phenolic housing with switch, 68" 4-cond. rubber covered cable. Excellent Used...... \$425



CARBON BOOM MICROPHONE With 16" cord and PL-291 plug. \$165

RS-38 MICROPHONE

This is a compact press-to-talk 100 hm carbon hand microphone. Can be used in place of the T17D mike.

Complete with 5-ft cord and PL-68 plug. NEW.

T-26 CHEST MIKE

Carbon microphone with oress-to-talk switch, on hest plate with adjustable boom. 60-ohm impedance. Like new....\$1.69



SWITCHBOARD

Provides a means of locating practically all faults common to magneto and common battery telephone exchanges. Test can be made in a simple manner for grounds, shorts, opens, crosses and bad joints. Unit contains a Weston model 24, 7-inch 100,000 ohm voltmeter, 0-40 DC scale, hand crank generator switches, etc. NEW \$1895



ELECTRIC No. 1407C TESTING CABINET This is a condensed wire chief's desk that affords means for accurately testing for practically all troubles com-

mon to both magneto and central battery exchanges. Quickly and easily tests for grounds crosses, short circuits, opens, bad joints, etc. Equipped with high quality Weston Voltmeter. Substantial Oak Cabinet. Complete with instruction manual, NEW, in original carton, \$1295 F.O.B. NYC or Calif.

SELSYN ZEROING ANALYZER



Roller-Smith Model B. Functions: zeroing of Selsyn Generators, Selsyn Control Transformers and Differential Selsyns; Voltage Read ingsj 0-50, 0-500 V DC; 0-300, 0-600 V AC.; Resistance Measure ments 0-1000, 0-10,000, 0-1 Meg. ONLY \$2950

TELEPHONE HANDSET Western Electric type. Carbon button mike and 200 ohm standard telephone receiver. OK for replacement or experimental use. Will operate with as little as 12

Available in GREEN or BLACK LIKE NEW..... \$295



volt power supply. Size $8\frac{3}{4}x2\frac{1}{4}x3-3/8$ ". Weight 2 lbs. With 4-conductor coiled-cord.

NEW



aluminum case that nandset, magneto type ringer and a three-tube battery operated amplifier which permits use of the telephone system over wires for more than 20 miles Can also be used with other magneto type telephones without using the amplifier. Batteries required:

RM-29 REMOTE CONTROL

 $\frac{1}{2}$, $4\frac{1}{2}$ and 65 volt. Complete with

Wt 18 lbs. With Manual. \$1950

tubes and handset. Size 19x11x121".



This is a portable

in a waterproof

contains a TS-9


NEW \$795

RM-29 is similar to EE8 plus facilities for remotely controlling any receiver-transmitter. Use as a telephone with any carbon mike and any low-impedance headset. As a PHONE PATCH, use it with no modifications! Just put phone line in parallel with your headset and mike. Uses 3 standard flashlight cells. Handcrank generator does ringing. Good up to 25 miles. Patch cords with PL-68 and PL-55 Plugs. Size 9x6x5". Weight 14 lbs. Less Batteries.

RM-52 REMOTE CONTROL

Multi-purpose unit RM-53; as a separate telephone system; direct control for radio equipment: or converted to a PHONE PATCH. Provides bias for mike, sidetone to headset. High/lo impedance mike and phone jacks.

FL-8 FILTER



FL-30 FILTER with PL-55 Plug and JK-26 Jack, complete \$185.

BEAM FILTER

1020 cycles low impedance, Similar to the FL8 but more elaborate. with cord and PL55 and switching control on slant panel for easy viewing. NEW.....\$225

H-22/U HANDSET

Has retractable "Y" cord, PL-68 and PL-55 Phone Plugs. Butteryfly switch.

each..... \$525






ART-13 KEYING RELAY & VACUUM SWITCH

2 SPDT & 1 SPD

each 27 ohms, series. Size 4x3x5" Wt 2 lbs. \$1025 NEW. \$8.95 Wt 2 lbs. SPERTI VACUUM SWITCH As used in ART-13 Transmitter Keying Relay described above. Each......95¢

TELEPHONE TYPE RELAY

Operating voltage 28 V DC. 2 coils



Made by J. H. Bunnell, this telephon type relay has adjustable sensitivity 150 ohm coil. Size $3\frac{1}{2}$ x4x $7\frac{3}{4}$ ". Shpg NEW, each.....\$345

> MERCURY WETTED CONTACT RELAYS



Made by Western Electric, these mercury wetted contact relays provide high speed (up to 60 operations per second) long life, uniformity and chatter-free operation.

Mounted in medium octal base sealed metal tube. WE type D171584. SPDT unit with single 4500 ohm coi Operates at 8 Ma. Releases at 5.2 Ma. Has enclosed 24-volt heater coil for positive subzero operation. Each...... \$275



DUAL RELAY Struthers Dunn 68AXX101 Dual 40-amp. con-

tact relays with dual 24 V DC coils Mounted on a bakelite base 4" x 34" x 5". Shpg wt 3 lbs.



1000 KC. CRYSTAL

For BC-221 Frequency Meters. Adaptable for use with LM-13 and LM-14 Frequency Meters, Fits octal sockets, Late type in can approximately 1-5/8" high, 14" dia. Hermetically sealed can. NEW, each.....\$550

100 KC, CRYSTAL For Loran Sets. G.E. #32C401G53 mounted in standard 3-pin holder. Size: 2-1/8" high (with pins $2\frac{3}{4}$ " high) x $1\frac{1}{4}$ " W x 1-5/8" D. Weight 2 oz. \$365

AIRCRAFT RADIO COMPRESSOR

Pressurization package equipment, includes Motor, Switch Assemblies. Desiccant char ber, Absolute Press.Indicato

and associated valves and controls. Overall 13½ x8½ x8" high. NEW...... \$1650



With voltage regulator tube VR-105 two ballast tubes and relay instal-led in rear compartment which is 2" deep. Front compartment is 9\frac{3}{4}" x7\frac{1}{2}" x7-3/8". Hinged cover with inner compartment for holding calibration chart. Can also be used for BC-221, TS-174, TS-175, etc. Weight 15 lbs. NEW, Each....\$395



used with BC-603, 683 BC-604, 684 This is a very useful spare parts chest.

SPARE

PARTS

CHEST

fine for storing tubes and parts. It is same size and shape as receiver: two compartments. Size 7x114x11" Each..... 95¢



WESTINGHOUSE RECTIFIER 95 V. 1/2 amp. 11 x 3³/₄ x 4" . \$250



257 Geared 3-digit counter, reversible. Overall size: 3-3/8" x 13" square.

COUNTER



COUNTER 5 place counter oneway. Overall 1½" high. Mtg ctrs 1" x Each......44¢


VEEDER-ROOT

COUNTER



3-digit counter Brand new, 77¢ FTR MINIATURE CHOKE Hermetically sealed, rated

2 henrys at 130 Ma. Size 23" high x 1½" wide x 1" deep. SPECIAL BUY! NEW.



TRANSFORMER

SPECIAL BUY Excellent Used...... \$195



Used with Azimuth Indicator Units MN-22 and MN-40 to control loop antennas MN-20 and MN-24. Shpg NEW.....\$345



MN-52 DIRECTION FINDER LOOP CONTROL For manual turning

of loop with crank an by use of flexible shaft, Has 0-360 dial, grain-o -wheat lamp,

switch and crank. NEW, each...... \$175

CONVERTS TO A

SA-1/ARN-1. Sig.

Corps. 2-gang wafer

switch with 11 posit-

DECADE BOX!

RESISTANCE

ions and fourteen 2500-ohm 2-watt

ance box from 0 to 20,000 ohms or

excellent audio attenuator for low-

impedance circuits. Large black

from 50 to 300 in 11 steps of 25

units each. Complete with alumin-

on rear. Overall size is 5x34x34"

um cover and Cannon plug mounted

Shpg wt 4 lbs. \$250 EACH, NEW.....

BRAND NEW...... \$185

FEED THRU INSULATOR

Ceramic feed thru insula-

tor. Each half is 13" dia.,

 $\times 1-1/8$ " high. Flanged to fit $1\frac{1}{4}$ " hole, 2-3/8" over-

all length. 4-20 threaded

FULL WAVE SELENIUM

Rated 110 volts at 150 Ma.

G.E. MAZDA LAMP

Rated 5 Amps at 5.9 V.

Pre-focussed base with

slotted collar, Individu-

packed ten to the origin-

ally G.E. sleeved and

6 Volt Auto Light

Style #1045

al carton.

5 for\$1.00

RECTIFIER

100 for.....\$12.50

rod 5" long. 3 nuts on each

VICTOREEN RADIATION

Model 506

DETECTOR (DOSIMETER)

pointer knob, clear dial calibrated

resistors. Convertible to resist-

ALTITUDE LIMIT SWITCH

2-METER ASSEMBLY

For Novice or Technician

Complete front end from BC-624 receiver. Set to cover frequencies from 100 to 156 Mc. Includes: 1 3-gang variable condenser; 1 2gang variable

condenser, 5 slug-tuned condensers 4 coil sets, 4 tube sockets (7-pin) numerous mica condensers, resistors, Size: 5x5x5", Ideal for building custom 2-meter receivers, transmitters, test equipment - eliminates all the hard work, such as coil winding, etc. Shpg wt 6 lbs. NEW. Each..... \$795

MOTOR DRIVEN COAXIAL SWITCH

Designed for use in RF circuits

where constant impedance charac=

rapid change of circuits by remote

control is desired. Specifications: 50 ohms impedance. Usable up to

Low VSWR. High isolation between

channels, Type "N" connectors. High reliability. 28 V DC. Max. diameter 3". Overall length 7½".

11,000 Mc. Low insertion loss.

teristics must be maintained and

HEAVY DUTY KNIFE SWITCHES



Excellent switches for anten switching or in circuits where high voltage or high currents are encou

S.P.D.T. Each	69¢
D.P.D.T. Each	99¢
3 P.D.T. Each	\$125



WOBBULATOR (Electro-Mechanical Frequency Shifter) Radio Altimeter FM Generator Frequency

Shifter, High quality alnico magnet cylinder 2½" OD x 1-1/16" long, 1¾ I.D. weighing 10 oz., with removable soft iron poles which close the magnetic circuit of a standard loudspeaker type voice coil. As voice coil is energized with AC the diaphragm alters capacity coupling. Wonderful for experiments with a powerful magnetic field in a cylinder magnet. You can make a sweep-signal generator with this voice-coil driven variable capacitor! Shpg wt NEW, each......\$295



REGULATOR INPUT: 21 to 30 volts DC at 5 A.

VOLTAGE

Regulation 18 to 30 volts DC. Overall size 4" x 3" Wt. 3 lbs. NEW, 99¢ NEW, 4 for \$3.50

PAGE 19

SERVO MOTORS =



SERVO MOTOR CK1001-4-C Bendix, Size 15

26/50 volts, 2 phase, 400 cps, 8 poles, 135 500 ohms impedance. 7 watts max. power,

2 GM, CM. 2 rotor inertia, 0.28 oz in, stall torque, 5500 rpm no load speed. Totally enclosed, ball-bear ing. Pressed steel housing 1-29/64' O.D. x 1" long. With spline shaft $\frac{1}{2}$ " long x 1/8" Dia. Excellent Used...........\$245



PM MOTOR With Governor Part C-3A-633, Type MM, Globe.

1/200 Hp, 10,000 rpm + 10%, 18 to 29 V DC., 0.35 A. Rev. rot., ballbearing, totally enclosed body 2-5/ inches long x 14" dia. Shaft 1/8" D. x 5/8" L, threaded on end for nut. Face mounting by 2 holes tapped 4-40 thd 3/16" deep on 0.676" mtg NEW..... \$450

JOHN OSTER SHUNT MOTOR



27 V DC at .7 Amps. 5600 rom. Aluminum cased motor and gear as sembly, Motor

is flange mounted to Gear Case. 2 gear reductions: 22 and 51 rpm on $\frac{1}{4} \times 1\frac{1}{4}$ shafts. Size $2\frac{3}{4} \times 3 \times 7$. Wt lb. 14 oz. REWIRED FOR A.C. OPERATION. Each......\$225



DELCO PM MOTOR #5072750, 10,000 rpm 27½ V DC tapered shaft 1/2". Will operate at lower voltage, Excellent used...... 95¢



LOW INERTIA SERVO MOTOR CK-5 Drag Cup

Designed for 2-phase 26 V 400 cycle oper-0.5 oz/in. Speed

3460 rpm, 0.4 sec. rev. time. W approx. 8 oz. Body $2\frac{1}{4}$ D x $1\frac{3}{4}$ L. With shaft 1/8 D x $\frac{3}{4}$ L.



SYNCHRO CONTROL TRANSFORMER AY-201 Mfg by Bendix, Rotor 1 ph. 26 volt 400 cycle, stator 3-phase 11, 8 volts, Size 12

 $x 1\frac{1}{2} \text{ shaft } \frac{1}{2} \times 1/16$ ". Wt 3 oz.

SYNCHRONOUS SELSYNS For 115 Volt 60 cycle AC.



Made by Diehl and Bendix. Brasscased, 6" long x 4" dia.

Type I-4 Trans, Selsyn. Type FJ-84-8 Trans, Selsyn Type IX-2 Repeater Selsyn Type M Autosyn BRAND NEW, EACH..... \$495

GRAB-BAG OF ONE DOZEN

TRANSMITTING CRYSTALS

PAGE 20

12 Assorted frequencies as used

in SCR-522, ARC-3, etc. \$159

Sprague, #16E1-2-600-50-P3T. 16 Kv, Single Circuit, 2 micro-seconds pulse width, 600 pulses paper dielectric, 3 terminals,

REDUCERS

EACH \$395



DELCO PM REDUCER Model 5069600 250 rpm at 10 oz

per inch torque. Continuous duty. 27 V DC, rev.rot ball-bearing, totally enclosed. Body 1-3/8" D x 34" L. Parallel spline shaft 14T30P, 4" OD x 3/8" long. Each.....\$3.95



DELCO SHUNT WOUND Model 5068750

160 rpm at 15 oz./inch torque, con tinuous duty; 55 oz/inch torque int. duty 50 hours. 27 VDC rev. rot. Magnetic brake for instantaneous braking action when power shut off. Body $1\frac{1}{2}$ "D x $4\frac{3}{4}$ "L, With spline shaft 14T30P $\frac{1}{4}$ "D x 3/8" long. Each......\$3.95



SHUNT WOUND REDUCER

Model 5BA10AJ37. 250 rpm at 8 oz /inch torque, cont. duty; 40 oz/in. torque int.duty 50 hours. 27 V DC 0.8 Amps. Ball-bearing, rev. rot. totally encl. body 1-3/8" D x $3\frac{1}{2}$ " L. Pinion shaft 14T30P. Each..... \$3.95



G.E. SHUNT WOUND REDUCER Model 5BA10AJ52 27 V at . 65 A.

Gear reduction 145 rpm output on a ½ x 3/8 splined shaft. 14 oz/in. torque. Motor size $1-3/8 \times 3\frac{1}{2}$ ". Weight 8 oz. Each.....\$3.95

G.E. SHUNT REDUCER With Magnetic Clutch



Model 5BA10FJ226. 575 rpm at 50 in.oz. torque, cont.duty. 14:1 gear ratio, 27 V DC 1.1 Amp. rev rot. Totally encl. Ball-bearing. Body 1-3/8" D x $3\frac{3}{4}$ " long. Shaft 3/16" D x $\frac{3}{4}$ " long. Magnetic clutch brake assembly attached. 1:1 ratio operative on 24 V DC. 1-9/16" D x 2" L with parallel pinion shaft " OD x 1 " L. Clutch assembly is Each.....\$3.95



2J1H1 SELSYN GENERATOR Normally operates

400 cycle. Size 24x44". Wt 8 oz. Only......\$225

YNCHRONOUS REPEATER JE22-2 400 cycles 115 Volts Cach.

16 KV NETWORK NEW



per second, t50 ohms impedance

ANTENNAS



AN-69A AIRCRAFT ANTENNA For APN-1 and SCR-718 Radio alti-NEW..... \$149

AN-130 GOOSNECK WHIP ANTENNA 30-inch Screw Base. Originally used with BC-1335, BC-1000. Each..... \$115



DIPOLE ANTENNA AN-148 150 to 180 Mc Each Only.... \$395

STUB ANTENNA AN-104A For SCR-522 100 to 156 Mc. Each. M Only..... \$175



LOOP ANTENNA Type L-10A (part of ARC) " Direction finding loop. Suitable for top or bottom mtg. Inductance 19 micro henrys, distributed "Q" of 46 at 400 Kc.

Excellent Used...... \$275

TEST

Manual rotatable loop antenna used with RA-10DB and MN-26 receivers'as a direction-finding antenna in the 150 to 1500 Kc range. Wt 7 lbs. Each......\$425

0000

Made by Rex-Cole. Used for com-

regulator systems. Has amplifier test gage, manifold pressure gage, RPM gage. Meter tests AC & DC Volts, Ohms. In aluminum suit-

case that opens to 2-section panel.

containers plus operating \$14950 instructions......

IP-69A/ALA-2

3" Scope, Front

Vertical Pos.;

Horiz. Pos.: In-

tensity, Focus,

Gain, Width,

Center freg.

INDICATOR

All cable connections included.

Pan. Operates on 115 Volts 380

Tubes: 1/6AL5, 2/6BA6, 1/6BE6,

1/6AC7, 1/6J6, 1/884, 2/6SL7, 1/1B3, 1/6X5, 1/OD3, 1/6SN7, 3/28D7, 1/12AU7, 1/3BP1.

to 1000 cps. AC.

NEW, in original metal

plete operational check of turbo

MN-20E ANTENNA

GRC-32B POWER SHPPLY 105-250 VDC



PHANTOM ANTENNA

This is a portable

equipment that pre-

vents signals from

being radiated when

adjusting, tuning or

checking the perfor-

mance of radio sets.

Used with BC-604 for

loading transmitter.

Can be used with any transmitter in

21 to 28 Mc band. Has variable cap-

acitor 55 mmf., two resistors, coil

slug-tuned, binding posts and indic-

ator lamp that lights when transmit-

ter is loaded. Size 3x6". Wt 4 lbs.

AT-96A ANTENNA

Modern stream-lined

broad-band quarter-wave

antenna. 3½" x 5/8" tear-

drop cross-section. 12"

long. Has matching stub

inside hermetically seal-

ed base. 160 to 240 Mc.

No standing waves in 52 ohm coax

(RG-8/U) throughout its band. UG-191/U (1. P. C. #325) in the base.

Each......\$345

Portable equipment used in tuning

and testing low-frequency and low-powered transmitters, in field and

depot maintenance. Frequency range: 500 Kc. Resistance 31 ohms

10%. Capacitance 700 uuf + 10%.

6" long. Shpg wt .6 lb.

Size: 2-9/16" x 2" x 1-9/16". Lead

hog wt 5 lbs.

4-98 ANTENNA

INPUT: Power transformer primary, 50/60 cps., 8 Amps: 105/ 115/125 VAC. 4 Amps: 210, 230/ 250 VAC. 1750 RMS working volt-age to ground. Choke 8.6 Mh at 22 Amps DC 10 V RMS 60 cycle excitation. Max DC resistance 0.97 ohms. Size 9x16x22". LIKE NEW.....





Made by Raytronic. Can be used for testing picture tubes as well as ageing. This is a quality instrucomplete with 4 harnesses. in original carton..... \$895

AUTO RADIO REMOTE CONTROL TUNING HEADS



Suitable for use with any auto radio. Universal type. With two 18" cab-

NEW......\$2750 "Serving the Electronics Industry since 1920"

CHECK THESE BATTERY VALUES!

WILLARD 2-VOLT STORAGE BATTERY

Convenient non-spill construction.

Lightweight polystyrene container.

extremely sturdy. Size: 3x4x51".

Shipped dry, uses standard elec-

trolyte (listing here). Shpg wt 3 lb

Lots of 100 or more, each \$2.30

Rated at 3 ampere hours. Exten-

sively used for model boats, etc. Size: 3-5/8 x 1-13/16 x 2-3/8"

high. Uses standard electrolyte,

see listing here. Shipped dry. Weight 2 lbs.

NEW, each.....

BATTERY ACID

Quart bottle of Willard

Battery Acid, 1280

specific gravity, for

use with any storage

All mixed, ready for

battery listed here.


WILLARD

STORAGE

BATTERY

Model NT-6

6-VOLT MIDGET



WILLARD ER-40-4 4-VOLT

STORAGE BATTERY

Rated at 40 ampere-hours. Side terminals. Six indicating balls; with metal case and cover. Size: 4-3/8" high x 6-3/8" wide x 534 deep. Shipped dry. Weight 12½ lb NAVY Type, NEW, each..... \$395

WILLARD BB-210/U 2-VOLT STORAGE BATTERY

24 Ampere-Hours

Top terminals. Size! 61" high, $2\frac{1}{2}$ " wide, $2\frac{1}{2}$ Shipped dry. ' wide, 2½" deep. Weight 3 lb. NEW, each..... \$275

BB-208/AMT BATTERY PACK



Contains three BB52 - 36 V miniature lead acid type storage batteries and one BB51 - 6 V lead acid storage battery. Shipped dry charge. Uses 1280 acid for cycling service and 1350 for one shot . BB52 supplies 3 hrs thru 1200 ohms. BB51 supplies 23 hrs thru 30 ohms. Made by Willard. Pack size: 41 x 1x1-3/8". Shpg 12 or more, each...... \$.80 | NEW.....

TYPE BB-41 STORAGE BATTERY

4 Volts 16 Amp Hrs. In metal carrying case 4½ x3-7/8 x 8¼" Each.....\$595

PE-219 BATTERY Designed to

charge one or two 6 V batteries at 7 amps, from a 6, 12 or 24 volt source. Charger uses one plug-in vibrator which serves as a rectifier and circuit breaker. Complete with a 10" pov er cord, in metal case 11x10x512 deep. Wt 40 lbs. Signal Corps Equipment, NEW.... \$750

AUTOMATIC BATTERY

NEW..... 69¢

Operates on principle of thermoexpansion - doubles battery life! Needs filling only twice a year. Fits all cars. Use one for 6 volt systems, two for 12 V. Instantly installed. Complete with mountin bracket and instructions.

12-VOLT VIBRATOR

Signal Corps type VB -13-A. 12 V - 115 cps. vibrator 9 pins. Diam: 1½"x2-7/8" long. For PE-120. NEW, each.... \$195 PE-104A VIBRATOR POWER SUPPLY

Vibrator power supply for BC-654. Works on 6 or 12 Volt Battery, supplies 84 volts and 51 volts DC also 1.4 volts "C" bias. Size. 7"
x4" x 3\frac{3}{2}". Limited quantity. \$1150 BRAND NEW.....

PE-204 VIBRAPACK

NEW..... \$249

12-volt Power Supply: 12 V DC input. Output: 2/4.3 V DC taps at 50 Ma., 2/45 V DC at .5 Ma and 2/85 V DC at 5 Ma. Voltage divider network can be revised to supply 135 V DC with enough current for small set. Schematic

VB-16 VIBRATOR

For PE-237. Operates on 6, 12 or 24 volts DC. NEW, each.... \$795



12-VOLT VIBRAPACK

Mallory Vibrator Power Supply. Efficient, dependable. 12 V DC input. Output: 220-250 V DC at 60 Ma. Size: $5\frac{1}{2} \times 2\frac{3}{4} \times$ 6". Special Buy! NEW.....

2-VOLT SYNCHRONOUS PLUG-IN VIBRATOR

7-prong synchronous Vibrator, replacement for 2volt auto radios. NEW, each..... 69¢



ORDER BLANK

Quart Bottle, each...... \$125

Lots of 6, each..... \$1.05

G&G RADIO SUPPLY COMPANY

75-77 Leonard Street, New York, N.Y. 10013 Telephone: (212) 267-4605

lame	Please Print Clearly	DATE	ie	repriorie: (212) 2	207 -4003	L V
Street Address		R.F.D. P.	O. Box REMARKS			
Post Office		State				
Page	Stock No. or	THE REAL PROPERTY.		Drieg Feeb	Total Drice	Do

ost O	fice			State						
Page	Quan.	Stock No. or Type No.		DESCRIP	TION	Price	Each	Total I	Price	Do U
	- 5									
										-
	0									-
			HOW ANALL	Include sufficient	Please Do Not Use	TOTAL				-
ull.	C.O.D.	Deposit with order, , or Remittance in ling Charge on all	HOW SHALL WE SHIP?	money for postage. We refund unused		FOR G				
rders	under \$5	6.00. All Shipments behouse N.Y.C. All bject to Prior Sale	PARCEL	amounts. Please send cash by reg- istered mail only.	ON FREIGHT OR	NY STA				
nd Pr	ice Chang	ge.	EXRESS	FILL IN AMOUNT ENCLOSED	EXPRESS ORDERS:	For Po				

REFERENCES:

Marine Midland Trust Co. 128 Chambers St. Branch.

Dun & Bradstreet,

Order

Cash

FREIGHT AIR EXP. Check ☐ BEST WAY Credit If your station has an agent do

not send money for shipping charges. If no agent, send money to pay the charges in advance. Charges are the same either way.

THANK YOU FOR YOUR ORDER!

Insurance Due from

TOTAL

PAGE 21

Original Ford-Majestic vibrator pack, consisting of power transformer, vibrator, and associated condensers, mounted in can 41" x " x 3½" with 6-prong plug. For 4½" x 3½" with 6-prong proge 6 V DC. Also useful for transceiver, experimental, etc. DC.output 180 volts at 40 Ma.

ed al

PE-120 POWER SUPPLY

Vibrator type, voltage-regu-lated, complete with tubes: OB -3/VR-105, 1005 and ballast. INPUT:

6/12/24 V DC at $4\frac{1}{2}/2\frac{1}{2}/1\frac{1}{2}$ amps respectively. OUTPUT: 145 V DC at 75 Ma., 90 V DC at 40 Ma., & $1\frac{1}{2}$ V DC at $\frac{3}{4}$ amp. Size: $4\frac{1}{2}$ x $13\frac{1}{4}$ x15½". Weight 29 lbs. LIKE NEW.....

WESTINGHOUSE BLOWER

NEW..... \$450

Westinghouse Style 1171145B. Type FL motor with sirocco single outlet metal housing. 50 CFM. Motor is self-vent, Capacitor induc. type, 115 V 400 cps. single phase, 6700 RPM, cont.duty. Inlet 1½" dia. Outlet 1-1/8" x 7/8" CW rotation viewed from motor end. Motor capacitor mounted on end bell of motor. Overall 4" L x 3-5/8" W x 4-1/8" not including mtg plate on bottom. Mtg plate $3\frac{1}{2}x1\frac{1}{2}$ ".

GN-45 GENERATOR

Excellent Used \$1125

Converts 24-28.6 V DC aircraft

cover (half ATR size) and is sup

Front panel contains output connec

spares. Uses 3/VT-119 (2X2) type

Excellent Used...... \$475

With sirocco metal housing, 100 CFM at free air; 0.6" S.P. at no

delivery. Motor is 208V, 400 cps 3 ph., 1/15 Hp, 0.45 A. 10,800

RPM, ball-bearing, self-ventila-ted, cont.duty. Inlet 13" dia. Im-

peller 2" dia. Outlet 14" x 12".

end. Triangular base mounting

plate with 3 holes 3/16" dia, on

90° angle on 2½ "x24" mtg ctrs.

Weight 2 lbs. EACH..... \$245

B

-1

CCW rotation viewed from motor

G.E. MOTOR

LIKE NEW. \$525

ART-13 MOTOR

12V. Size 3x3x31

28 V DC 3900 rpm, ball-

bearing, reversible, 1/20 Hp. Will work on

5K25DJ21

tion, two operating fuses, set of

ported by mounting FT-322-A.



Crosley or equivalent Sig. Corps type GN-45A. Output 6.3 volts DC at 3.0 Amps & 500 Volts DC at 7200 RPM, 115 V 400 cps 1 ph. 0.4A, 9W, ball-bearing, rev.rot. self-vent. Cont.duty. Requires 0.14 Amps. Driving speed 50 to ext. capacitor. Flange mtd on shaft end by 3 tapped holes on $1\frac{1}{2}$ circle on 1-5/16" mtg ctrs. Body 70 RPM. Can also be cranked by use of bicycle, motor or hand. is 2-5/16" dia. x 2-7/8" long, with 90° double-flatted shaft 4" PE-112 POWER SUPPLY

LIKE NEW...... \$275 power into suitable potentials for aperation of equipment. It is housed in a black wrinkle-finish dust

MX-215/APG MOTOR

D x 5/8" L.

New... \$3²⁵

Blower works on 12 to 115 volts AC or DC. Uses a series wound 28 v motor and a No. 2 blower. Includes a radio noise filter. It moves approx. 20 cubic ft per minute at 28 V but it REALLY blows on 115 V 60 cy.! Very useful around shop, for blowing out heavy dirt. 7500 RPM at 28 V. Dynamically balanced, vibration free. Shpg wt 5 lbs.

LOW VOLTAGE AC MOTOR

Small 6-8 volt AC Heavy Duty Shaded Pole Induction Motor, NEW...89¢



DELCO MOTOR

Operates on 6-8 volts DC. For model boats, trains, experimental work. 95¢ NEW....



MAGNETS

4500 GAUSS for use with tubes like 725-A, 730-A, 2J22, etc. Pole pieces are 1" in diameter. Gap 5/8"

Height from pole centers to base is 3-7/8" clear. Wt 15 lbs. \$1495

5200 GAUSS

Magnetron magnet. Air-gap ½". Poles tapered: ". Height 7". Base 2¾ x 6½" Weight 93 lb. EACH..... \$995

1800 GAUSS



Magnetron Magnet. Air gap 1=5/8". Pole dia. $1\frac{1}{2}$ ". $7\frac{1}{2}$ " long x $4\frac{1}{2}$ " high. Mounted on iron base 8-3/8! long x 21' wide x 11/16" thick.

Made by Cinaudagraph. Net wt. 111 lbs. \$975

5190 GAUSS Pole pieces 3" dia. 5/8" gap. SPECIAL EACH..... \$975

5270 GAUSS Pole pieces 3" dia. 5/8" gap. SPECIAL EACH..... 5235 GAUSS

13" dia. 1.48" gap. Pole center to ase: 4-1/8". EACH...... \$975



HEAVY DUTY MAGNET Weighs 13 lbs. Overall size: 3" x 13" x 2" high. SPECIAL, EACH...........\$144

ORDER BLANK (Continued from Reverse Side)

Page No.	Quan.	Stock No. or Type No.	DESCRIPTION	Price Each	Total Price	Do No Use
			A DESCRIPTION OF THE PERSON OF			050
-						
						1000
						210-6
-						
	. 19					
10		4 (20) 11 5 (500)				
	1271					
	-					
	e la c					
	N H N			TOTAL FOR GOODS		

TEST SETS

PORTABLE TEST SCOPE



A small portable instrument for both field and lab use in testing and maintaining radar and associated electrical equipment. Used to display wave-forms of positive or negative pulses and sine waves. Measures peak voltage pulses, signal voltages amd power by comparison of unknown to known reference images on screen and pulse duration. Oscilloscope is suitable for high and low impedance cir-

cuits. Input Power: 115 V 50-1200 cy. AC. Vertical Amp: Flat 30 cps to 1 mc. CR tube 2AP1(2") with integral lens providing 2x magnifications. Sweeps: Recurrent 10-50,000 cps driven 5/50/250 Usec. Size: 6x8x15". Wt 26 lbs.

TS-239/UP OSCILLOSCOPE

Excellent used.....



Power required: 105-125 V 50 to 1600 cycles single phase AC. Frequency Range: 1 cycle to 3 Mc. Calibrating Voltages: 0.1 to 1 V(P to P). Sweep speeds: .05 to 50,000 microsec/in. Vert. Sensitivity: 0.1V to 456 V (Peak). Less instruction manual, Shpg wt. \$14950



TEST OSCILLO-SCOPE TS-100AP

Small portable instrument used to test and calibrate range measuring circuits of radar systems. Also used as general synchroscope. It is used for viewing short video pulses and 3" screen and measuring time intervals between pulses. Power Supply: 115 or 230 Volts 50-1200 cps. Trigger input: Pulse repetition rate 100 to 3000 pulses per sec. for 1/30 and 350 mile undelayed sweeps. Size: 7.8"x12" x16" deep. Weight 39 lbs. Complete with plugs, cables, NEW..... \$7950



TEST SET 159 TPX

Measures frequency between 150-200 Mc by heterodyne method. Out put of transmitter can be measured directly. Measures DC voltages up to 500 V. Operates on 110 V 400 cycles AC. Complete with tubes, crystal, calibration chart. \$2850

FLIGHT INSTRUMENTS



INDICATOR Type A-3 WHEEL & FLAP POSITION

AN-5780-1

indicates whether flaps are up, 1/4 , 3 or fully on, and whether the wheels are up or down and locked or unlocked. Indications are shown on dial representing the plane, produced thru electrical impulses received from four transmitters at landing wheels, tail wheel and flaps. Dial size \$390



F-9 INDICATOR

Ratio meter type electric thermometer, used for registering carburator air or mixture temperatures. Markings: fluorescent; Range: -45 to 45° C. Dial 1-7/8" diameter; Voltage: 12 V DC; Size 2-3/8" dia.x $3\frac{1}{2}$ " deep. Wt 1 lb. Excellent



BANK & CLIMB GYRO A-3A


Vertical gyro control, part of the Army type A-3a automatic pilots. Contains gyroscope which provides a reference for manual or automatic control of plane attitude, a suction gage, gyro caging device and mechanism to operate the air pick-off assembly. Size $7\frac{1}{2}x7\frac{1}{4}x$ 12" approx. Weight 131 lbs. Power: 4" of mercury vacuum. Fluorescent markings. \$5950 Exc. Used.....



FLIGHT COMMAND INDICATOR

ID-524/ARR-39A Model HD-649

Multimeter for Data Link or Analog applications. This is a 31" AN type meter with up to 4 simultaneous readouts, Hermetically sealed, gas-filled, in shielded steel case. Max. sensitivity 200



TESTER ASSEMBLY T-101001

pilot. Contains a 24" AC meter with center scale 50-0-50 and 15-0-15, 5-position metering switch for range and 11-position switch for measuring voltage from the external pin-jacks on conn. plug. Also has 7 toggle switches, 4 lights. Tubes: 2/6AL5, 1/2C51 In aluminum carrying case 131 x11 x11". Weight 22 lbs. Excellent Used......

TEST INDICATOR BE-67

Portable milliammeter, used as a source of DC in relay adjustment, or as output meter with test oscillator. Complete with 0-1 Ma Meter and Caryying Case. Excellent used condition.. \$695



RANGE CALIBRATOR TEST SCOPE TS-126/AP

Top quality 2" oscilloscope with all positioning, focus, gain and intensity controls. Sawtooth sweep triggered by external negative pip or can be switched to self-triggering. For 115 V AC 400-1600 cycle AC operation. Complete with tubes and

BRAND NEW..... \$2450 As above, with all tubes, demilitarized, like new cond..... \$13.75



Measures peak power levels of pulsed transmitters. Comprises terminal diode, integrating network, hi-impedance VTVM, cal-ibration circuits, power supply. Operates on 115 V 50 to 2460 cycles AC. Frequency range 405 to 425 Megacycles. Complete with 3 tubes, cables, manual. NEW...... \$2195



FREQUENCY METER MODEL LM

Fine general purpose Navy Freq. Meter. Range 125 to 20,000 Kc. Operates on 12 or 24 V DC and 200 V 10 Ma DC. Complete with tubes, crystal, calib. book. \$7950 Checked out. Excellent used..... As above, less book..... \$34.50

AC Power Supply......\$22.50



ECHO BOX TS-545/UP

Used for checking radar sets in the frequency range of 1150 to 1350 Mc. Tuned cavity manual type meter 3½" 0-100 DC micro-amps. Essentially this test set consists of a hand-ringing resonator of high Q, excited by means of loop connected by flexible cable toRF test point of radar. Size: 16x9x9". Weight 23 lbs. Excellent \$3950 Used.....

SIGNAL GENERATOR



I-198A

Frequency range 7 to 15 Mega-cycles, which multiplies into 20 and 10 meter bands. Modulated, 110 AC. Can be used as a frequency meter. LIKE NEW\$1450

FREQUENCY METER BC-638A

VHF, covers 100 to 156 Mc. Preset channels are crystal-controlled with built-in modulation. Varjable tuning and magic eye. Makes a fine 2-Meter exciter! Works on 115 - 230 volts 60 cycles AC. Mounts in 19" Rack. With Power Supply. Excellent Used......\$2425



EQUIPMENT

WAVEMETER OSCILLATOR used for checking radar equipment in the 140 to 240 Mc band, has

magic eve tuning indicator, large dial and tuning assembly similar to BC-221 freq.meter. Coaxial input and output circuits. Operates from 115 volt 50-70 cycles AC. Size: 9x16x10". Wt 35 lb. \$1495

TEST SET I-96A



VHF Signal Generator. Frequency range 100 to 156 Mc. Master oscillator tunable or may be crystal controlled. IF frequency 12 Mc. 110 V 60 cy. AC power supply or battery operated. This is a complete test set for SCR-522, BC-639



USN Frequency Meter type CWS 60028, Diode type tuned cavity wavemeter, covering frequency range 236 to 256 Mc. Utilizes a micrometer type tuning arrange ment to give 3-figure readings. Indicator is a 0-500 microammeter. Crystal diode rectifier, Furnished with cable and calibration chart. Unit is 3" diameter x 143" long. In metal case 64x18x5 high, with carrying handle. Shpg wt 25 lbs. TIKE NEW......

G&G RADIO SUPPLY COMPANY

75-77 Leonard Street, New York, N.Y. 10013

RETURN REQUESTED

B. H. Scheidt 5163 Brown Rd. R.F.D. #1 Take Odessa, Michigan

Bulk Rate U.S. POSTAGE PAID

NEW YORK, N.Y. Permit No. 8803

TEST SETS

RANGE CALIBRATOR TS-10/APN



for servicing air-borne altimeters. Checks sensitivity tuning, antenna systems, calibra-tion and limit calibration. Freq.

Range: 410-470 Mc. Includes plugs & cables. NEW. \$1695

AMPLIFIER ALIGNMENT UNIT TS-92 /AP



Portable test equipment, used in readjusting response curve of broadband amplifiers.

Frequency Range: 15 to 500 Mc. Operates on 115 V AC. Complete with 7 tubes. \$2150 Excellent Used.....

PICK-UP ASSEMBLY



Test unit, indicates relative output of airborne transmitting antenna, Range 20 to 1000 Mc. Complete, \$495 Brand New....

SIGNAL GENERATOR TS-251



Portable, for pre-flight and shipboard checking of Loran receivers. Opera-

tes on 80, 115 or 230 V, 50 to 1600 cy. AC. Range 1700 to 2010 Kc., pulse emission. Exc. Used... \$9950

RANGE CALIBRATOR TS-293/CPA-5



Portable, used in calibrating and adjusting range measuring cir-

cuits of radar apparatus. Operates on 115 V 60 cy. AC.
Crystal freq. 186.3 Kc. Complete with 10 tubes,
NEW. \$4250

TEST UNIT TS-16



Portable, selfcontained, for checking altimeter counter & indicator circuits.

Freq. read direct-ly in Mc from rotary dial. Power input 27 to 28 V DC. Includes meter for line voltage.

WAVEMETER LAVOIE



TYPE 105

VHF 2-tube battery operated. Measures 375 to 725 Mc. tunable. Complete with

0-200 microamp meter in wood carrying case, with calibration Excellent Used..... \$4450

FREQUENCY METER BC-221



Exc. Used Checked Out

Unmodulated ···· \$7950

Modulated ... \$129.50

Accurate, reliable crystal-calibrated frequency-indicating instrument for 125 to 20,000 Kc. range. Also useful as signal generator or VFO. Complete with tubes, calibration book, Checked Out.

1000 Kc Crystal for above \$5.50

TS-173/UR FREQUENCY METER

For calibration of transmitters, oscillators, signal generators, etc. Range 90 to 450 Mc. Checked out, complete. Excellent Used......\$14950

TS-175/U FREQUENCY METER

Portable, crystal-controlled, heterodyne type, for field testing of CW, MCW RF transmitters and signal generators. Range 85 to 1000 Mc. Complete with tubes, crystal, calibration book. Checked out, Excellent Used......\$14950

TEST SET IE-36



For bench test of SCR-522 etc. Checks starting and stopping mechanisms, channel selection, switching, etc. Includes

instruction manual. Sturdy Carrying Case.

TEST SET

TS-110 /AP

Portable ringing cavity resonator, measures power output of radar xmitters, spectrum analyses, power level & freq. of radar-receiver local oscillators, frequency of CW MCW. pulsed RF Xmitters, detects multiple moding of magnetrons, recovery speed of radar TR boxes and revrs, receiver sig. to noise ratio. Range 2400 to 2700 Mc. Exc. Used ... \$2450

TEST OSCILLATOR O TS-170/ARN-5



Portable, battery-operated, crystal-controlled. Checks receiver sensitivity and audio channels.

3 pre-selected frequencies: 332.6 Mc., 338.8 Mc., 335 Mc. \$1495 Excellent Used....

SIGNAL GENERATOR



I-222-B

Excellent Used. \$2950

Portable unit for checking freq. output of transmitters, aligning receivers. Range: 8 to 15 Mc., 45 to 76 Mc., 135 to 230 Mc. CW. 115 V 60 cy. operation. Complete with 6 tubes.

COMPUTER TEST SET



TS-667 /AP

Portable, for testing and adjusting ground position indicators. Operates on 26,5 V. 5 A DC.
Range 0-,35 V RMS, 400 cy. AC
to 400 V DC. Complete, \$2150 Brand New.....

TEST SET TS-41 /CRN-1



For operating test and maintenance of radio transmitters.

Measures frequency, battery volts & amps, antenna current. Range 1400 to 1750 Mc. CW, MCW. Like New......\$1295

WAVEMETER



TS-111 /CP Brand New

\$8950 Portable, adsorption type, for measuring freq. of CW, MCW or pulsed S-band ground radar bea-cons. Range 2500 to 3750 Mc.

I-223 RANGE CALIBRATOR



Brand New \$2450

Calibrates, checks and adjusts range measuring circuits of pulse operated radar apparatus. Signal outputs: Sine wave 163,94 Kc; Sinc Pulse 240 pps. Pos. pulse 163, 940 pps, 1 usec wide. Complete with 8 tubes.

FREQUENCY METER



BC-906

NEW \$1295

Portable absorption type meter for determining frequency of CW MCW or pulsed radar transmitthe wor pulsed radar transmitters and local osc. Also for calibrating, aligning and checking sensitivity of receivers. Battery operated: 1.5V, 45 V DC. Range 150 to 234 Mc.

SIGNAL GENERATOR



TS-155C /UP Brand New \$6950

Portable, general purpose, checks overall system perform-ance, receiver sensitivity, pow-er output of xmitters. Supplies sync trigger pulses. Complete. RF wattmeter included.