

4JC6, 4JC6A

Sharp-Cutoff Pentodes

The 4JC6 and 4JC6A are the same as the 6JC6 and 6JC6A, respectively, except for the following items:

Heater Characteristics and Ratings

Current	I_h	0.450 ± 0.030	A
Voltage (AC or DC) at 0.450 A	E_h	4.5	V
Warm-up time (Average).		11	s

4JD6

Sharp-Cutoff Pentode

The 4JD6 is the same as the 6JD6 except for the following items:

Heater Characteristics and Ratings

Current	I_h	0.450 ± 0.030	A
Voltage (AC or DC) at 0.450 A	E_h	4.5	V
Warm-up time (Average).		11	s

4KE8

Medium-Mu Triode— Sharp-Cutoff Pentode

The 4KE8 is the same as the 6KE8 except for the following items:

Heater Characteristics and Ratings

Current	I_h	0.600 ± 0.040	A
Voltage (AC or DC) at 0.600 A	E_h	4.5	V
Warm-up time (Average).		11	s

4KT6

Semiremote-Cutoff Pentode

The 4KT6 is the same as the 6KT6 except for the following items:

Heater Characteristics and Ratings

Current	I_h	0.450 ± 0.030	A
Voltage (AC or DC) at 0.450 A	E_h	4.5	V
Warm-up time (Average).		11	s



5AM8

Diode—Sharp-Cutoff Pentode

CONTROLLED HEATER WARM-UP TIME

The 5AM8 is the same as the 6AM8A except for the following items:

Heater Characteristics and Ratings

Current	I_h	0.600 ± 0.040	A
Voltage (AC or DC) at 0.600 A	E_h	4.7	V

5AN8

Medium-Mu Triode— Sharp-Cutoff Pentode

CONTROLLED HEATER WARM-UP TIME

The 5AN8 is the same as the 6AN8A except for the following items:

Heater Characteristics and Ratings

Current	I_h	0.600 ± 0.040	A
Voltage (AC or DC) at 0.600 A	E_h	4.7	V

5AQ5

Beam Power Tube

CONTROLLED HEATER WARM-UP TIME

The 5AQ5 is the same as the 6AQ5A except for the following items:

Heater Characteristics and Ratings

Current	I_h	0.600 ± 0.040	A
Voltage (AC or DC) at 0.600 A	E_h	4.7	V

