
DESCRIPTION AND RATING

3AF4-A

3AF4-A Triode. Except for heater characteristics and ratings, the 3AF4-A is identical to the 6AF4-A.

GENERAL**ELECTRICAL**

Cathode—Coated Unipotential

Heater Characteristics and Ratings

Heater Voltage, AC or DC¶	3.2	Volts
Heater Current†	0.45 ± 0.03	Amperes
Heater Warm-up Time‡	11	Seconds

3AF4-B

3AF4-B Triode. Except for heater ratings and heater-cathode voltage ratings, the 3AF4-B is identical to the 6AF4-A. The 3AF4-B differs from the 3AF4-A in heater-cathode voltage ratings only.

GENERAL**ELECTRICAL**

Cathode—Coated Unipotential

Heater Characteristics and Ratings

Heater Voltage, AC or DC¶	3.2	Volts
Heater Current†	0.45 ± 0.03	Amperes
Heater Warm-up Time‡	11	Seconds

MAXIMUM RATINGS**DESIGN-MAXIMUM VALUES**

Heater-Cathode Voltage

Heater Positive with Respect to Cathode

DC Component.....100 Volts

Total DC and Peak.....180 Volts

Heater Negative with Respect to Cathode

Total DC and Peak.....180 Volts

Design-Maximum ratings are limiting values of operating and environmental conditions applicable to a bogey electron tube of a specified type as defined by its published data and should not be exceeded under the worst probable conditions.

The tube manufacturer chooses these values to provide acceptable serviceability of the tube, making allowance for the effects of changes in operating conditions due to variations in the characteristics of the tube under consideration.

The equipment manufacturer should design so that initially and throughout life no design-maximum value for the intended service is exceeded with a bogey tube under the worst probable operating conditions with respect to supply-voltage variation, equipment component variation, equipment control adjustment, load variation, signal variation, environmental conditions, and variations in the characteristics of all other electron devices in the equipment.

3AL5

3AL5 Double Diode. Except for heater ratings and heater-cathode voltage ratings, the 3AL5 is identical to the 6AL5.

GENERAL**ELECTRICAL**

Cathode—Coated Unipotential

Heater Characteristics and Ratings

Heater Voltage, AC or DC.....	3.15	Volts
Heater Current.....	0.6	Amperes
Heater Warm-up Time‡.....	11	Seconds

3AF4-A

3AF4-B

3AL5

3AU6

3AV6

Page 2

4-63

MAXIMUM RATINGS

DESIGN-CENTER VALUES

Heater-Cathode Voltage

Heater Positive with Respect to Cathode

DC Component.....100 Volts

Total DC and Peak.....200 Volts

Heater Negative with Respect to Cathode

Total DC and Peak.....200 Volts

Design-Center ratings are limiting values of operating conditions applicable to a bogey tube of a specified type as defined by its published data, and should not be exceeded under normal conditions.

The tube manufacturer chooses these values to provide acceptable serviceability of the tube in average applications, making allowance for normal changes in operating conditions due to rated supply voltage variation (For an AC

power source, 117 volts plus or minus 10% is accepted USA practice.), equipment component variation, equipment control adjustment, load variation, signal variation, environmental conditions, and variations in tube characteristics.

The equipment manufacturer should design so that initially no design-center value for the intended service is exceeded with a bogey tube in equipment operating at the stated normal supply voltage.

3AU6

3AU6 Pentode. Except for heater characteristics and ratings, the 3AU6 is identical to the 6AU6 and 6AU6-A.

GENERAL

ELECTRICAL

Cathode—Coated Unipotential

Heater Characteristics and Ratings

Heater Voltage, AC or DC*.....3.15 Volts

Heater Current†.....0.6 ± 0.04 Amperes

Heater Warm-up Time‡.....11 Seconds

3AV6

3AV6 Duplex-Diode Triode. Except for heater characteristics and ratings, the 3AV6 is identical to the 6AV6.

GENERAL

ELECTRICAL

Cathode—Coated Unipotential

Heater Characteristics and Ratings

Heater Voltage, AC or DC*.....3.15 Volts

Heater Current†.....0.6 ± 0.04 Amperes

Heater Warm-up Time‡.....11 Seconds

FOOTNOTES

φ Heater voltage for a bogey tube at $I_f = 0.3$ amperes.

¶ Heater voltage for a bogey tube at $I_f = 0.45$ amperes.

* Heater voltage for a bogey tube at $I_f = 0.6$ amperes.

† For series heater operation, the equipment designer should design the equipment so that heater current is centered at the specified bogey value, with heater supply variations restricted to maintain heater current within the specified tolerance.

‡ The time required for the voltage across the heater to reach 80 percent of its rated value after applying 4 times rated heater voltage to a circuit consisting of the tube heater in series with a resistance equal to 3 times the rated heater voltage divided by the rated heater current.

The tubes and arrangements disclosed herein may be covered by patents of General Electric Company or others. Neither the disclosure of any information herein nor the sale of tubes by General Electric Company conveys any license under patent claims covering combinations of tubes with other devices or ele-

ments. In the absence of an express written agreement to the contrary, General Electric Company assumes no liability for patent infringement arising out of any use of the tubes with other devices or elements by any purchaser of tubes or others.

RECEIVING TUBE DEPARTMENT

GENERAL  **ELECTRIC**

Owensboro, Kentucky