

MECHANICAL

Mounting Position—Vertical†
 Envelope—T-12, Glass
 Base—B8-110, Short Medium-Shell Octal 8-Pin
 Top Cap—C1-1, Small

MAXIMUM RATINGS

HORIZONTAL-DEFELECTION AMPLIFIER SERVICE§
DESIGN-CENTER VALUES UNLESS OTHERWISE INDICATED


DC Plate-Supply Voltage (Boost + DC Power Supply)	700	Volts
Peak Positive Pulse Plate Voltage	7000▲	Volts
Peak Negative Pulse Plate Voltage	1500	Volts
Screen Voltage	175	Volts
Peak Negative Grid-Number 1 Voltage	200	Volts
Plate Dissipationπ	20	Watts
Screen Dissipation	3.0	Watts
DC Cathode Current	200	Milliamperes
Peak Cathode Current	700	Milliamperes
Heater-Cathode Voltage		
Heater Positive with Respect to Cathode		
DC Component	100	Volts
Total DC and Peak	200	Volts
Heater Negative with Respect to Cathode		
Total DC and Peak	200	Volts
Grid-Number 1 Circuit Resistance	0.47	Megohms
Bulb Temperature at Hottest Point	225	C

CHARACTERISTICS AND TYPICAL OPERATION

AVERAGE CHARACTERISTICS

Plate Voltage	60	175	Volts
Screen	100	175	Volts
Grid-Number 1 Voltage	0◆	—30	Volts
Plate Resistance, approximate	...	7200	Ohms
Transconductance	...	7700	Micromhos
Plate Current	230	75	Milliamperes
Screen Current	21	5.5	Milliamperes
Grid-Number 1 Voltage, approximate			
I _b = 1.0 Milliampere	...	—55	Volts
Triode Amplification Factor #	...	3.9	

* Heater warm-up time is defined as the time required in the circuit shown at the right for the voltage across the heater terminals to increase from zero to the heater test voltage (V_1). For this type, $E=100$ volts (RMS or DC), $V_1=20.0$ volts (RMS or DC), and $R=126$ ohms.



† Without external shield.

‡ Horizontal operation is permitted if pins 2 and 7 are in a vertical plane.

§ For operation in a 525-line, 30-frame television system as described in "Standards of Good Engineering Practice Concerning Television Broadcast Stations," Federal Communications Commission. The duty cycle of the voltage pulse must not exceed 15 percent of one scanning cycle.


▲ Value given is to be considered as an Absolute Maximum Rating. In this case, the combined effect of supply voltage variation, manufacturing variation including components in the equipment, and adjustment of equipment controls should not cause the rated value to be exceeded.

π In stages operating with grid-leak bias, an adequate cathode-bias resistor or other suitable means is required to protect the tube in absence of excitation.


◆ Applied for very short interval so as not to damage tube.

Triode connection (screen tied to plate) with $E_b = E_{c2} = 175$ volts and $E_{c1} = -30$ volts.


AVERAGE TRANSFER CHARACTERISTICS



AVERAGE TRANSFER CHARACTERISTICS



AVERAGE PLATE CHARACTERISTICS



AVERAGE PLATE CHARACTERISTICS

