



32ET5

32ET5

POWER PENTODE

7-PIN MINIATURE TYPE

GENERAL DATA

Electrical:

Heater, for Unipotential Cathode:

Voltage (AC or DC) $32 \pm 10\%$ volts

Current 0.1 amp

Direct Interelectrode Capacitances (Approx.):⁰Grid No.1 to plate. 0.6 μf Grid No.1 to cathode & grid No.3,
grid No.2, and heater 12 μf Plate to cathode & grid No.3,
grid No.2, and heater 6 μf

Mechanical:

Operating Position. Any

Maximum Overall Length. 2-5/8"

Maximum Seated Length. 2-3/8"

Length, Base Seat to Bulb Top (Excluding tip). . . 2" $\pm 3/32$ "

Diameter. 0.650" to 0.750"

Dimensional Outline See General Section

Bulb. T5-1/2


Base. Small-Button Miniature 7-Pin (JEDEC No.E7-1)

Basing Designation for BOTTOM VIEW. 7CV

Pin 1 - Cathode,
Grid No.3

Pin 2 - Grid No.1

Pin 3 - Heater



Pin 4 - Heater

Pin 5 - Grid No.1

Pin 6 - Grid No.2

Pin 7 - Plate

AMPLIFIER — Class A₁

Maximum Ratings, Design-Maximum Values:

PLATE VOLTAGE. 150 max. volts

GRID-No.2 (SCREEN-GRID) VOLTAGE. 130 max. volts

GRID-No.2 INPUT. 1.2 max. watts

PLATE DISSIPATION. 5.4 max. watts

PEAK HEATER-CATHODE VOLTAGE:

Heater negative with respect to cathode. 200 max. volts

Heater positive with respect to cathode. 200[▲] max. volts

Typical Operation and Characteristics:

Plate Voltage. 110 volts

Grid-No.2 Voltage. 110 volts

Grid-No.1 Voltage. -7.5 volts

Peak AF Grid-No.1 Voltage. 7.5 volts

Zero-Signal Plate Current. 30 ma

Zero-Signal Grid-No.2 Current. 2.8 ma

Plate Resistance (Approx.) 21500 ohms

Transconductance 5500 μmhos

Load Resistance. 2800 ohms

32ET5



32ET5

POWER PENTODE

Total Harmonic Distortion.	10	%
Max.-Signal Power Output	1.2	watts

Maximum Circuit Values:

Grid-No.1-Circuit Resistance:

For fixed-bias operation	0.1	max.	megohm
For cathode-bias operation	0.5	max.	megohm

O without external shield.

▲ The dc component must not exceed 100 volts.