

## Sharp-Cutoff Twin Pentode With Common Cathode, Grid No.1, and Grid No.2

*The 3GS8 is the same as the 4GS8/4BU8 except for the following items:*

### Heater Characteristics and Ratings

|                                       |       |                   |   |
|---------------------------------------|-------|-------------------|---|
| Current . . . . .                     | $I_h$ | $0.600 \pm 0.040$ | A |
| Voltage (AC or DC) at 0.600 A . . . . | $E_h$ | 3.15              | V |

# 3HM5/3HA5

## High-Mu Triode

*The 3HM5/3HA5 is the same as the 6HM5/6HA5 except for the following items:*

### Heater Characteristics and Ratings

|                                       |       |                   |   |
|---------------------------------------|-------|-------------------|---|
| Current . . . . .                     | $I_h$ | $0.450 \pm 0.030$ | A |
| Voltage (AC or DC) at 0.450 A . . . . | $E_h$ | 2.7               | V |
| Warm-up time (Average). . . . .       |       | 11                | s |

# 3HS8

## Sharp-Cutoff Twin Pentode

*The 3HS8 is the same as the 6HS8 except for the following items:*

### Heater Characteristics and Ratings

|                                       |       |                   |   |
|---------------------------------------|-------|-------------------|---|
| Current . . . . .                     | $I_h$ | $0.600 \pm 0.040$ | A |
| Voltage (AC or DC) at 0.600 A . . . . | $E_h$ | 3.15              | V |
| Warm-up time (Average). . . . .       |       | 11                | s |



# 3JC6, 3JC6A

## Sharp-Cutoff Pentodes

*The 3JC6 and 3JC6A are the same as the 6JC6 and 6JC6A, respectively, except for the following items:*

### Heater Characteristics and Ratings

|                                       |       |                   |   |
|---------------------------------------|-------|-------------------|---|
| Current . . . . .                     | $I_h$ | $0.600 \pm 0.040$ | A |
| Voltage (AC or DC) at 0.600 A . . . . | $E_h$ | 3.5               | V |
| Warm-up time (Average). . . . .       |       | 11                | s |

# 3JD6

## Sharp-Cutoff Pentode

*The 3JD6 is the same as the 6JD6 except for the following items:*

### Heater Characteristics and Ratings

|                                       |       |                   |   |
|---------------------------------------|-------|-------------------|---|
| Current . . . . .                     | $I_h$ | $0.600 \pm 0.040$ | A |
| Voltage (AC or DC) at 0.600 A . . . . | $E_h$ | 3.5               | V |
| Warm-up time (Average). . . . .       |       | 11                | s |

# 3KT6

## Semiremote-Cutoff Pentode

*The 3KT6 is the same as the 6KT6 except for the following items:*

### Heater Characteristics and Ratings

|                                       |       |                   |   |
|---------------------------------------|-------|-------------------|---|
| Current . . . . .                     | $I_h$ | $0.600 \pm 0.040$ | A |
| Voltage (AC or DC) at 0.600 A . . . . | $E_h$ | 3.5               | V |
| Warm-up time (Average). . . . .       |       | 11                | s |

