

15AF11

Dual Triode— Sharp-Cutoff Pentode

DUODECAR TYPE

The 15AF11 is the same as the 6AF11 except for the following items:

Heater Characteristics and Ratings:

Current.	0.450 ± 0.030	amp
Voltage (AC or DC) at 0.450 amp.	14.7	volts
Warm-up time (Average)	11	sec

15BD11

Dual Triode— Sharp-Cutoff Pentode

DUODECAR TYPE

The 15BD11 is the same as the 6BD11 except for the following items:

Heater Characteristics and Ratings:

Current.	0.450 ± 0.030	amp
Voltage (AC or DC) at 0.450 amp.	14.7	volts
Warm-up time (Average)	11	sec

15CW5

Beam Power Tube

The 15CW5 is the same as the 6CW5 except for the following items:

Heater Characteristics and Ratings:

Current.	0.300 ± 0.020	amp
Voltage (AC or DC) at 0.300 amp.	15.0	volts



15FM7

Dual Triode

DUODECAR TYPE

The 15FM7 is the same as the 6FM7 except for the following items:

Heater Characteristics and Ratings:

Current.	0.450 ± 0.030	amp
Voltage (AC or DC) at 0.450 amp. . . .	14.8	volts
Warm-up time (Average)	11	sec

15FY7

Dual Triode

DUODECAR TYPE

The 15FY7 is the same as the 6FY7 except for the following items:

Heater Characteristics and Ratings:

Current.	0.450 ± 0.030	amp
Voltage (AC or DC) at 0.450 amp. . . .	14.7	volts
Warm-up time (Average)	11	sec

15HB6

Power Pentode

The 15HB6 is the same as the 6HB6 except for the following items:

Heater Characteristics and Ratings:

Current.	0.300 ± 0.020	amp
Voltage (AC or DC) at 0.300 amp. . . .	14.7	volts
Warm-up time (Average)	11	sec

