

Dual Triode—Sharp-Cutoff Pentode

Dual Triode Has High-Mu & Medium-Mu Units

DUODECAR TYPE

Electrical:

Heater Characteristics and Ratings:

Voltage (AC or DC)	6.3 ± 0.6 volts
Current at 6.3 volts	1.050 amp

Maximum Heater Cathode Voltage:

Heater negative with respect to cathode:

Peak	200 volts
----------------	-----------

Heater positive with respect to cathode:

Peak	200 volts
----------------	-----------

DC component	100 volts
------------------------	-----------

Direct Interelectrode Capacitances: (without external shield)

Triode Unit No.1

Grid to plate	1.9 pf
-------------------------	--------

Input: G_{T1} to (K_{T1} , $K_{T2} + 1S$, $K_p + G_{3p} + 1S$, H)	3.0 pf
---	--------

Output: P_{T1} to (K_{T1} , $K_{T2} + 1S$, $K_p + G_{3p} + 1S$, H)	2.2 pf
--	--------

Triode Unit No.2

Grid to plate.	3.6 pf
------------------------	--------

Input: G_{T2} to ($K_{T2} + 1S$, $K_p + G_{3p} + 1S$, H)	2.4 pf
--	--------

Output: P_{T2} to ($K_{T2} + 1S$, $K_p + G_{3p} + 1S$, H)	3.8 pf
---	--------

Pentode Unit

Grid No.1 to plate	0.13 pf
------------------------------	---------

Input: G_{1p} to ($K_{T2} + 1S$, $K_p + G_{3p} + 1S$, G_{2p} , H)	11.0 pf
---	---------

Output: P_p to ($K_{T2} + 1S$, $K_p + G_{3p} + 1S$, G_{2p} , H)	4.6 pf
---	--------

Pentode plate to plate of triode No.2.	0.045 max. pf
--	---------------

Plate of triode No.1 to plate of triode No.2.	0.075 max. pf
---	---------------

Characteristics, Class A₁ Amplifier:

	Triode Units	No.1	No.2
Plate Supply Voltage	200	200	volts
Grid Voltage	-2	-	volts
Cathode Resistor	-	220	ohms
Amplification Factor	68	41	
Plate Resistance (Approx.)	12400	9400	ohms
Transconductance	5500	4400	μ mhos
Plate Current.	7	9.2	ma
Grid Voltage for plate $\mu_a = 100$	-5.5	-6.5	volts

Pentode Unit


Plate Supply Voltage	35	135	volts
Grid-No.2 Supply Voltage	135	135	volts
Grid-No.1 Voltage.	0 ^a	-	volts
Cathode Resistor	-	100	ohms
Plate Resistance (Approx.)	-	45000	ohms
Transconductance	-	10400	μ mhos
Plate Current.	34 ^b	17	ma
Grid-No.2 Current.	13 ^b	4	ma
Grid-No.1 Voltage (Approx.) for plate $\mu_a = 100$	-	-6	volts



Mechanical:

Operating Position	Any
Types of Cathodes	Coated Unipotential
Maximum Overall Length	2.375"
Seated Length	1.750" to 2.000"
Diameter	1.062" to 1.188"
Dimensional Outline (JEDEC 9-58)	See <i>General Section</i>
Bulb	T9
Base	Small-Button Duodecar 12-Pin (JEDEC No. E12-70)
Basing Designation for BOTTOM VIEW	12DP

- Pin 1-Heater
 Pin 2-Pentode Plate
 Pin 3-Grid of Triode Unit No.2
 Pin 4-Plate of Triode Unit No.2
 Pin 5-Cathode of Triode Unit No.1
 Pin 6-Grid of Triode Unit No.1
 Pin 7-Cathode of Triode Unit No.2,
 Internal Shield
 Pin 8-Plate of Triode Unit No.1
 Pin 9-Pentode Cathode, Pentode
 Grid No.3, Internal Shield
 Pin 10-Pentode Grid No.2
 Pin 11-Pentode Grid No.1
 Pin 12-Heater



AMPLIFIER — Class A_j

Maximum Ratings, Design-Maximum Values:

	Triode Units No.1	No.2
Plate Voltage	330	330 volts
Grid (Control-Grid) Voltage:		
Positive-bias value	0	0 volts
Plate Dissipation	1.5	2 watts

Pentode Unit

Plate Voltage	330	volts
Grid-No.2 (Screen-Grid) Supply Voltage	330	volts
Grid-No.2 Voltage	See <i>Grid-No.2 Input Rating Chart</i> at front of Receiving Tube Section	
Grid-No.1 (Control-Grid) Voltage:		
Positive-bias value	0	volts
Grid-No.2 Input:		
For grid-No.2 voltages up to 165 volts	1.1	watts
For grid-No.2 voltages between 165 and 330 volts	See <i>Grid-No.2 Input Rating Chart</i> at front of Receiving Tube Section	
Plate Dissipation	4	watts

Maximum Circuit Values: (Values are for Each Unit)

	Triode Units	Pentode Unit
Grid-No.1-Circuit Resistance:		
For fixed-bias operation	0.5	1 megohm
For cathode-bias operation	1	1 megohm

^a Applied for short interval (2 sec. max.) so as not to damage tube.

^b Value measured by recurrent waveform such that maximum ratings of tube are not exceeded.