

2ER5

High-Mu Triode

The 2ER5 is the same as the 6ER5 except for the following items:

Heater Characteristics and Ratings

Current.	0.600 ± 0.040	A
Voltage (AC or DC) at 0.600 A.	2.3	V

2FH5

High-Mu Triode

The 2FH5 is the same as the 6FH5 except for the following items:

Heater Characteristics and Ratings

Current.	0.600 ± 0.040	A
Voltage (AC or DC) at 0.600 A.	2.35	V
Warm-up time (Average)	11	s

2FS5

Beam Hexode

The 2FS5 is the same as the 6FS5 except for the following items:

Heater Characteristics and Ratings

Current.	0.600 ± 0.040	A
Voltage (AC or DC) at 0.600 A.	2.4	V
Warm-up time (Average)	11	s

2GK5

High-Mu Triode

The 2GK5 is the same as the 6GK5 except for the following items:

Heater Characteristics and Ratings

Current.	0.600 ± 0.040	A
Voltage (AC or DC) at 0.600 A.	2.3	V
Warm-up time (Average)	11	s



2GU5

Beam Hexode

The 2GU5 is the same as the 6GU5 except for the following items:

Heater Characteristics and Ratings

Current.	0.600 ± 0.040	A
Voltage (AC or DC) at 0.600 A.	2.4	V
Warm-up time (Average)	11	s

