


## TUNG-SOL


## REMOTE-CUTOFF PENTODE

## MINIATURE TYPE

GLASS BULB  
MINIATURE

9 PIN BASE E9-1

## UNIPOTENTIAL CATHODE

HIGH G<sub>m</sub>, SMALL SIGNAL  
RF & IF AMPLIFIER  
WITH GAIN CONTROLBOTTOM VIEW  
BASING DIAGRAM  
JEDEC 9A0

THE 6EH7 IS A REMOTE-CUTOFF PENTODE IN THE 9 PIN MINIATURE CONSTRUCTION. IT FEATURES VERY HIGH G<sub>m</sub> WITH A REMOTE CUTOFF AND IS DESIGNED FOR FREQUENCIES INTO THE VHF RANGE. ITS CHIEF APPLICATION IS IN THE IF AMPLIFIER STAGES OF TELEVISION RECEIVERS.

## DIRECT INTERELECTRODE CAPACITANCES

WITHOUT EXTERNAL SHIELD

GRID #1 TO PLATE: (G<sub>1</sub> TO P) MAX.

0.0055 pf

INPUT: G<sub>1</sub> TO (H+G<sub>2</sub>+G<sub>3</sub>+K+IS)

9.5 pf

OUTPUT: P TO (H+G<sub>2</sub>+G<sub>3</sub>+K+IS)

2.8 pf

## HEATER CHARACTERISTICS AND RATINGS

DESIGN MAXIMUM VALUES - SEE EIA STANDARD RS-239

AVERAGE CHARACTERISTICS

6.3 VOLTS

300

MA

HEATER SUPPLY LIMITS:

VOLTAGE OPERATION

6.3±0.6

VOLTS

CURRENT OPERATION

300±20

MA.

MAXIMUM HEATER-CATHODE VOLTAGE

165

VOLTS

## MAXIMUM RATINGS

DESIGN CENTER VALUES - SEE EIA STANDARD RS-239

PLATE VOLTAGE

250

VOLTS

PLATE DISSIPATION

2.5

WATTS

GRID #2 VOLTAGE

250

VOLTS

GRID #2 DISSIPATION

0.65

WATTS

CATHODE CURRENT

20

MA

GRID #1 CIRCUIT RESISTANCE

1

MEGOHM

CONTINUED ON FOLLOWING PAGE

CONTINUED FROM PRECEDING PAGE

TYPICAL OPERATING CHARACTERISTICS

|                                                         |       |       |            |
|---------------------------------------------------------|-------|-------|------------|
| PLATE VOLTAGE                                           | 200   | 200   | VOLTS      |
| GRID #3 VOLTAGE                                         | 0     | 0     | VOLTS      |
| GRID #2 VOLTAGE (SUPPLY)                                | 90    | 200   | VOLTS      |
| GRID #2 SERIES RESISTOR                                 | 0     | 24    | KILOHMS    |
| GRID #1 VOLTAGE                                         | -2    | -2    | VOLTS      |
| PLATE CURRENT                                           | 12    | ---   | MA.        |
| GRID #2 CURRENT                                         | 4.5   | ---   | MA.        |
| TRANSCONDUCTANCE                                        | 12500 | 12500 | $\mu$ MHOS |
| PLATE RESISTANCE                                        | 0.5   | ---   | MEGOHMS    |
| GRID #1 IMPEDANCE AT 40 MC                              | 13    | ---   | KILOHMS    |
| GRID #1 CUTOFF: $E_{c1} = -6.5$                         |       | 1250  | $\mu$ MHOS |
| $E_{c1} = -9.5$                                         |       | 625   | $\mu$ MHOS |
| $E_{c1} = -19.5$                                        |       | 125   | $\mu$ MHOS |
| GRID #1 VOLTAGE FOR A CROSS-MODULATION<br>FACTOR OF 10: |       |       |            |
| $E_{c1} = -6.5$                                         |       | 100   | MV.        |
| $E_{c1} = -9.5$                                         |       | 160   | MV.        |
| $E_{c1} = -19.5$                                        |       | 450   | MV.        |

