



6BN8

6BN8

TWIN DIODE—HIGH-MU TRIODE

9-PIN MINIATURE TYPE

*With heater having controlled warm-up time***GENERAL DATA****Electrical:**

Heater, for Unipotential Cathodes:

Voltage (AC or DC)	6.3	volts
Current	0.6 ± 6%	amp ←
Warm-up time (Average).	11	sec

Direct Interelectrode Capacitances:⁰**Triode Unit:**

Grid to plate	2.5	μμf
Grid to heater and cathode.	3.6	μμf
Plate to heater and cathode	0.25	μμf

Diode Units:

Diode-No.1 plate to triode grid	0.06 max.	μμf
Diode-No.2 plate to triode grid	0.1 max.	μμf
Diode-No.1 cathode to all other electrodes.	5	μμf
Diode-No.2 cathode to all other electrodes.	5	μμf
Diode-No.1 plate to diode-No.2 plate.	0.07 max.	μμf
Diode-No.1 plate to diode-No.1 cathode and heater.	1.9	μμf
Diode-No.2 plate to diode-No.2 cathode and heater.	1.9	μμf
Diode-No.1 cathode to diode-No.1 plate and heater.	4.8	μμf
Diode-No.2 cathode to diode-No.2 plate and heater.	4.8	μμf
Diode-No.1 plate to all other electrodes.	3	μμf
Diode-No.2 plate to all other electrodes.	3	μμf

Characteristics, Class A₁ Amplifier (Triode Unit):

Plate Voltage	100	250	volts
Grid Voltage.	-1	-3	volts
Amplification Factor.	75	70	
Plate Resistance (Approx.).	21000	28000	ohms
Transconductance.	3500	2500	μmhos
Plate Current	1.5	1.6	ma
Grid Voltage (Approx.) for plate μa = 10	-2.5	-5.5	volts

Mechanical:

Operating Position.	Any
Maximum Overall Length.	2-5/8"
Maximum Seated Length	2-3/8"
Length, Base Seat to Bulb Top (Excluding tip).	2" ± 3/32"
Diameter	0.750" to 0.875"
Dimensional Outline	See General Section

← Indicates a change.

6BN8




6BN8

TWIN DIODE—HIGH-MU TRIODE

Bulb. T6-1/2
 Base. Small-Button Noval 9-Pin (JEDEC No. E9-1)
 Basing Designation for BOTTOM VIEW. 9ER

Pin 1—Diode-No.2
 Plate
 Pin 2—Diode-No.2
 Cathode
 Pin 3—Diode-No.1
 Cathode
 Pin 4—Heater



Pin 5—Heater
 Pin 6—Diode-No.1
 Plate
 Pin 7—Triode Plate
 Pin 8—Triode Grid
 Pin 9—Triode
 Cathode

TRIODE UNIT — AMPLIFIER — Class A₁

Maximum Ratings, Design-Maximum Values:

PLATE VOLTAGE	330	max.	volts
GRID VOLTAGE:			
Positive-bias value	0	max.	volts
PLATE DISSIPATION	1.7	max.	watts
PEAK HEATER-CATHODE VOLTAGE:			
Heater negative with respect to cathode	200	max.	volts
Heater positive with respect to cathode	200 [▲]	max.	volts

Maximum Circuit Values:

Grid-Circuit Resistance	1	max.	megohm
-----------------------------------	---	------	--------

DIODE UNITS — Two

Maximum Ratings, Design-Maximum Values:

Values are for Each Unit

PEAK PLATE CURRENT.	54	max.	ma
DC PLATE CURRENT.	9	max.	ma
PEAK HEATER-CATHODE VOLTAGE:			
Heater negative with respect to cathode	200	max.	volts
Heater positive with respect to cathode	200 [▲]	max.	volts

○ without external shield.

▲ The dc component must not exceed 100 volts.


→ Indicates a change.



6BN8

6BN8


TWIN DIODE—HIGH-MU TRIODE



6BN8



6BN8

AVERAGE PLATE CHARACTERISTICS
TRIODE UNIT



6BN8

AVERAGE CHARACTERISTICS TRIODE UNIT

6BN8

