

5CG8

Medium-Mu Triode— Sharp-Cutoff Pentode

9-PIN MINIATURE TYPE

With Heater Having Controlled Warm-Up Time

The 5CG8 is the same as the 6CG8A except for the following items:

Heater, for Unipotential Cathode:

Voltage (AC or DC).	4.7	volts
Current	$0.6 \pm 6\%$	amp

5CL8A

Medium-Mu Triode— Sharp-Cutoff Tetrode

9-PIN MINIATURE TYPE

With Heater Having Controlled Warm-Up Time

The 5CL8A is the same as the 6CL8A except for the following items:

Heater, for Unipotential Cathodes:

Voltage (AC or DC).	4.7	volts
Current	$0.6 \pm 6\%$	amp

5CM8

High-Mu Triode— Sharp-Cutoff Pentode

9-PIN MINIATURE TYPE

With Heater Having Controlled Warm-Up Time

The 5CM8 is the same as the 6CM8 except for the following items:

Heater, for Unipotential Cathodes:

Voltage (AC or DC).	4.7	volts
Current	$0.6 \pm 6\%$	amp



5CQ8

Medium-Mu Triode— Sharp-Cutoff Tetrode

9-PIN MINIATURE TYPE

With Heater Having Controlled Warm-Up Time

The 5CQ8 is the same as the 6CQ8 except for the following items:

Heater, for Unipotential Cathodes:

Voltage (AC or DC)	4.7	volts
Current	$0.6 \pm 6\%$	amp

5CZ5

Beam Power Tube

9-PIN MINIATURE TYPE

With Heater Having Controlled Warm-Up Time

The 5CZ5 is the same as the 6CZ5 except for the following items:

Heater, for Unipotential Cathode:

Voltage (AC or DC)	4.7	volts
Current	$0.6 \pm 6\%$	amp



**5CG8****5CG8
TO
5CM8****TRIODE-PENTODE CONVERTER**

9-PIN MINIATURE TYPE

*Intended for use in equipment having
series heater-string arrangement**The 5CG8 is the same as the 6CG8 except for the following items:*

Heater, for Unipotential Cathode:

Voltage (AC or DC)	4.7	volts
Current	0.6 ± 6%	amp
Warm-up time (Average)	11	sec

5CL8-A**MEDIUM-MU TRIODE—
SHARP-CUTOFF TETRODE**

9-PIN MINIATURE TYPE

*Intended for use as combined VHF oscillator and mixer
tube in TV receivers having series heater-string arrangement**The 5CL8-A is the same as the 6CL8-A except for the following
items:*

Heater, for Unipotential Cathodes:

Voltage (AC or DC)	4.7	volts
Current	0.6 ± 6%	amp

5CM8**HIGH-MU TRIODE—
SHARP-CUTOFF PENTODE**

9-PIN MINIATURE TYPE

*Intended for use in equipment having
series heater-string arrangement**The 5CM8 is the same as the 6CM8 except for the following items:*

Heater, for Unipotential Cathodes:

Voltage (AC or DC)	4.7	volts
Current	0.6 ± 6%	amp

5CQ8
5CZ5



5CQ8

**MEDIUM-MU TRIODE—
SHARP-CUTOFF TETRODE**

9-PIN MINIATURE TYPE

*Intended for use in equipment having
series heater-string arrangement*

The 5CQ8 is the same as the 6CQ8 except for the following items:

Heater, for Unipotential Cathodes:

Voltage (AC or DC)	4.7	volts
Current	0.6 ± 6%	amp

5CZ5

BEAM POWER TUBE

9-PIN MINIATURE TYPE

*For vertical-deflection-amplifier service in 110°
systems having series heater-string arrangement*

The 5CZ5 is the same as the 6CZ5 except for the following items:

Heater, for Unipotential Cathode:

Voltage (AC or DC)	4.7	volts
Current	0.6 ± 6%	amp

5CG8

Medium-Mu Triode— Sharp-Cutoff Pentode

9-PIN MINIATURE TYPE

For Equipment Having Series Heater-String Arrangement

The 5CG8 is the same as the 6CG8-A except for the following items:

Heater, for Unipotential Cathode:

Voltage (AC or DC)	4.7	volts
Current	$0.6 \pm 6\%$	amp

5CL8-A

Medium-Mu Triode— Sharp-Cutoff Tetrode

9-PIN MINIATURE TYPE

For Equipment Having Series Heater-String Arrangement

The 5CL8-A is the same as the 6CL8-A except for the following items:

Heater, for Unipotential Cathodes:

Voltage (AC or DC)	4.7	volts
Current	$0.6 \pm 6\%$	amp

5CM8

High-Mu Triode— Sharp-Cutoff Pentode

9-PIN MINIATURE TYPE

For Equipment Having Series Heater-String Arrangement

The 5CM8 is the same as the 6CM8 except for the following items:

Heater, for Unipotential Cathodes:

Voltage (AC or DC)	4.7	volts
Current	$0.6 \pm 6\%$	amp



RADIO CORPORATION OF AMERICA
Electron Tube Division
Harrison, N. J.

DATA
1-61

5CQ8

Medium-Mu Triode— Sharp-Cutoff Tetrode

9-PIN MINIATURE TYPE

For Equipment Having Series Heater-String Arrangement

The 5CQ8 is the same as the 6CQ8 except for the following items:

Heater, for Unipotential Cathodes:

Voltage (AC or DC)	4.7	volts
Current	0.6 ± 6%	amp

5CZ5

Beam Power Tube

9-PIN MINIATURE TYPE

For Equipment Having Series Heater-String Arrangement

The 5CZ5 is the same as the 6CZ5 except for the following items:

Heater, for Unipotential Cathode:

Voltage (AC or DC)	4.7	volts
Current	0.6 ± 6%	amp

5EW6

Sharp-Cutoff Pentode

7-PIN MINIATURE TYPE

For Equipment Having Series Heater-String Arrangement

The 5EW6 is the same as the 6EW6 except for the following items:

Heater, for Unipotential Cathode:

Voltage (AC or DC)	5.6	volts
Current	0.45 ± 6%	amp
Warm-up time (Average)	11	sec

