

**6EW6****6EW6****SHARP-CUTOFF PENTODE**

7-PIN MINIATURE TYPE

GENERAL DATA**Electrical:**

Heater, for Unipotential Cathode:

Voltage (AC or DC)	6.3 $\pm$ 10%	volts
Current	0.4	amp

Direct Interelectrode Capacitances:

	<i>Without External Shield</i>	<i>With External Shield^o</i>	
Grid No.1 to plate	0.04 max.	0.03 max.	μ f
Grid No.1 to cathode, grid No.3 & internal shield, grid No.2, and heater.	10	10	μ f
Plate to cathode, grid No.3 & internal shield, grid No.2, and heater	2.4	3.4	μ f

Characteristics, Class A₁ Amplifier:

Plate Supply Voltage.	125	volts
Grid No.3	<i>Connected to cathode at socket</i>	
Grid-No.2 Supply Voltage.	125	volts
Cathode Resistor.	56	ohms
Plate Resistance (Approx.)	0.2	megohm
Transconductance.	14000	μ hos
Plate Current	11	ma
Grid-No.2 Current	3.2	ma
Grid-No.1 Voltage (Approx.) for plate μ a = 20	-3.5	volts

Mechanical:

Operating Position.	Any
Maximum Overall Length.	2-1/8"
Maximum Seated Length	1-7/8"
Length, Base Seat to Bulb Top (Excluding tip)	1-1/2" $\pm$ 3/32"
Diameter.	0.650" to 0.750"
Dimensional Outline	<i>See General Section</i>
Bulb.	T5-1/2
Base.	Small-Button Miniature 7-Pin (JEDEC No. E7-1)
Basing Designation for BOTTOM VIEW.	7CM

Pin 1-Grid No.1
Pin 2-Cathode
Pin 3-Heater
Pin 4-Heater
Pin 5-Plate



Pin 6-Grid No.2
Pin 7-Grid No.3,
Internal
Shield



6EW6

SHARP-CUTOFF PENTODE

AMPLIFIER — Class A₁

Maximum Ratings, Design-Maximum Values:

PLATE VOLTAGE.	330 max. volts
GRID-No.3 (SUPPRESSOR-GRID) VOLTAGE.	0 max. volts
GRID-No.2 (SCREEN-GRID) SUPPLY VOLTAGE	330 max. volts
GRID-No.2 VOLTAGE.	See Grid-No.2 Input

Rating Chart at front of Receiving Tube Section

GRID-No.1 (CONTROL-GRID) VOLTAGE:

Positive-bias value.	0 max. volts
------------------------------	--------------

GRID-No.2 INPUT:

For grid-No.2 voltages up to 165 volts	0.65 max. watt
--	----------------

For grid-No.2 voltages between 165 and 330 volts.	See Grid-No.2 Input
---	---------------------

Rating Chart at front of Receiving Tube Section

PLATE DISSIPATION.	3.1 max. watts
----------------------------	----------------

PEAK HEATER-CATHODE VOLTAGE:

Heater negative with respect to cathode	200 max. volts
Heater positive with respect to cathode	200 [▲] max. volts

○ with external shield JEDEC No.316 connected to cathode.


▲ The dc component must not exceed 100 volts.



6EW6

6EW6

AVERAGE CHARACTERISTICS



6EW6



6EW6

AVERAGE CHARACTERISTICS

$E_f = 6.3$ VOLTS
PLATE VOLTS = 125
GRID-N#3 CONNECTED TO
CATHODE AT SOCKET.
GRID-N#2 VOLTS = 125

