



6ST7

DUPLEX-DIODE TRIODE
Single-Ended Metal Type
 (TENTATIVE DATA)

Ratings are to be interpreted according to RMA Standard M8-210 (Jan. 8, 1940 Rev. 11-40)

HEATER VOLTAGE (A.C. or D.C.)	6.3	Volts
HEATER CURRENT	0.15	Ampere
DIRECT INTERELECTRODE CAPACITANCES - Triode Unit (Approx.): ^o		
Grid to Plate [C_{gp}]	1.5	$\mu\mu f$
Grid to Cathode [$C_{g(h+k+shell)}$]	2.8	$\mu\mu f$
Plate to Cathode [$C_{p(h+k+shell)}$]	3.0	$\mu\mu f$
MAXIMUM OVERALL LENGTH	2-5/8"	
MAXIMUM SEATED HEIGHT	2-1/16"	
MAXIMUM DIAMETER	1-5/16"	
BULB	Metal Shell, MT-8	
BASE	Small Wafer Octal 8-Pin	
MOUNTING POSITION	Any	

^o With shell connected to cathode.

Triode Unit

PLATE VOLTAGE	250 max.	Volts
PLATE DISSIPATION	2.5 max.	Watts
CHARACTERISTICS - Class A₁ Amplifier:		
Plate Voltage	250	Volts
Grid Voltage	-9	Volts
Amplification Factor	16	
Plate Resistance	8500	Ohms
Transconductance	1900	Micromhos
Plate Current	9.5	Milliamperes

Diode Units - Two

The two diode plates are placed at one end of a cathode, the sleeve of which is common to the triode unit. Diode biasing of the triode unit of the 6ST7 is not suitable.

Bottom View of Socket Connections

Pin 1 - Shell
 Pin 2 - Triode Grid
 Pin 3 - Cathode
 Pin 4 - Diode Plate #2
 Pin 5 - Diode Plate #1
 Pin 6 - Triode Plate
 Pin 7 - Heater
 Pin 8 - Heater

