

PHILCO CATHODE RAY TUBE DATA SHEET

TENTATIVE

17DRP4 TELEVISION PICTURE TUBE

from JEDEC release #2586, Sept. 14, 1959

DESCRIPTION

The 17DRP4 is an extremely short electrostatic focus and magnetic deflection, direct view picture tube specifically intended for television applications. The tube incorporates internal magnetic shielding in the gun design so that, in spite of the very short neck length, deflecting yokes without special magnetic shields may be used. Another feature of the tube is its unusually low heater power. The heater is a 450 milliamperere, 2.68 volt design with controlled warm-up time for series string applications. Other features of the tube are a metal backed screen, a straight gun requiring no ion trap magnet and a short integral glass-button base having straight through leads and an indexing lug. The distinctive yellow base identifies the 17DRP4 as having internal magnetic shielding.

GENERAL DESCRIPTION

17" rectangular extremely short cathode ray tube intended for direct view television applications requiring low heater power.

ELECTRICAL DATA

Focusing Method	Electrostatic
Deflecting Method	Magnetic
Deflection Angle, approximate	
Horizontal	105 Degrees
Vertical	87 Degrees
Diagonal	110 Degrees
Direct Interelectrode Capacitance, approximate	
Cathode to All	3.65 $\mu\mu\text{f}$
Grid #1 to All	4.15 $\mu\mu\text{f}$
External Coating Capacitance	900 Min. $\mu\mu\text{f}$
	1400 Max. $\mu\mu\text{f}$
Heater Voltage	2.68 $\pm$ 10% Volts
Heater Current at 2.68 Volts	0.45 Amperes
Heater Warm-up Time (Note 1)	11 Seconds

OPTICAL DATA

Phosphor Number	P4
Fluorescent Color	White
Persistence	Medium
Faceplate	
Light Transmission at Center, approximate	77 Percent

MECHANICAL DATA

Overall Length	10 $\frac{13}{16}$ $\pm$ $\frac{3}{4}$ Inches
Neck Length	3 $\frac{1}{16}$ $\pm$ $\frac{1}{16}$ Inches
Greatest Dimensions of Bulb	
Diagonal	16 $\frac{9}{16}$ $\pm$ $\frac{1}{8}$ Inches
Width	15 $\frac{5}{8}$ $\pm$ $\frac{1}{8}$ Inches
Height	12 $\frac{3}{4}$ $\pm$ $\frac{1}{8}$ Inches
Minimum Useful Screen Dimensions (maximum assured dimensions)	
Diagonal	15 $\frac{3}{4}$ Inches
Width	14 $\frac{3}{4}$ Inches
Height	11 $\frac{11}{16}$ Inches
Bulb	J132 $\frac{1}{2}$ A1
Base	B7-208
Basing	8JK
Anode Contact	J1-21
Anode Contact Aligns with Center	
Line between Pin #6 and #7	$\pm$ 30°

GRID DRIVE SERVICE

Voltag es are positive with respect to cathode unless indicated otherwise.

MAXIMUM RATINGS (Absolute Maximum Values)

Anode Voltage (Note 2)	17,600 Max. Volts DC
Grid #4 Voltage	- 700 to +950 Max. Volts DC
Grid #2 Voltage	550 Max. Volts DC
Grid #1 Voltage	
Negative-Bias Value	155 Max. Volts DC
Negative-Peak Value	400 Max. Volts
Positive-Bias Value	0 Max. Volts DC
Positive-Peak Value	2 Max. Volts
Peak-Heater-Cathode Voltage	
Heater Negative with Respect to Cathode	
During Warm-up Period not to Exceed	
15 Seconds	450 Max. Volts
After Equipment Warm-up Period	200 Max. Volts
Heater Positive with Respect to Cathode	200 Max. Volts

TYPICAL OPERATING CONDITIONS

Anode Voltage	14,000 Volts DC
Grid #4 Voltage for Focus	100 to 500 Volts DC
Grid #2 Voltage	300 Volts DC
Grid #1 Voltage (Note 3)	- 35 to - 72 Volts DC

MAXIMUM CIRCUIT VALUES

Grid #1 Circuit Resistance	1.5 Max. Megs.
----------------------------	----------------

CATHODE DRIVE SERVICE

Voltag es are positive with respect to Grid #1 unless indicated otherwise.

MAXIMUM RATINGS (Absolute Maximum Values)

Anode Voltage (Note 2)	17,600 Max. Volts DC
Grid #4 Voltage	- 550 to +1100 Max. Volts DC
Grid #2 Voltage	700 Max. Volts DC
Cathode Voltage	
Positive-Bias Value	155 Max. Volts DC
Positive-Peak Value	220 Max. Volts
Negative-Bias Value	0 Max. Volts DC
Negative-Peak Value	2 Max. Volts
Peak-Heater-Cathode Voltage	
Heater Negative with Respect to Cathode	
During Warm-up Period not to Exceed	
15 Seconds	450 Max. Volts
After Equipment Warm-up Period	200 Max. Volts
Heater Positive with Respect to Cathode	200 Max. Volts

