

Picture Tube

RECTANGULAR GLASS TYPE
LOW-VOLTAGE ELECTROSTATIC FOCUS

ALUMINIZED SCREEN
70° MAGNETIC DEFLECTION

Electrical:

Direct Interelectrode Capacitances:

Cathode to all other electrodes.	5	pf
Grid No.1 to all other electrodes.	6	pf
External conductive coating to anode . . .	{ 1500 max. 750 min.	pf
Heater Current at 6.3 volts.		ma
Electron Gun	600 ± 30	Type Requiring No Ion-Trap Magnet

Optical:

Phosphor (For curves, see front of this section). P4—Sulfide Type,
Aluminized
Faceplate, CylindricalFilterglass
Light transmission (Approx.) 66%

Mechanical:

Weight (Approx.) 19 lbs
Overall Length 19-3/16" ± 3/8"
Neck Length. 7-1/2" ± 3/16"
Projected Area of Screen 149 sq. in.

External Conductive Coating:

Type Regular-Band
Contact area for grounding Near Reference Line
For Additional Information on Coatings and Dimensions:


See *Picture-Tube Dimensional-Outlines and Bulb J133 C/E* sheets
at front of this section

Cap. Recessed Small Cavity (JEDEC No.J1-21)

Base . . Small-Shell Duodecal 6-Pin (JEDEC Group 4, No.B6-63)

Basing Designation for BOTTOM VIEW 12L

Pin 1-Heater
Pin 2-Grid No.1
Pin 6-Grid No.4
Pin 10-Grid No.2
Pin 11-Cathode
Pin 12-Heater



Cap - Anode
(Grid No.3,
Grid No.5,
Screen,
Collector)
C - External
Conductive
Coating

Maximum and Minimum Ratings, Design-Maximum Values:

*Unless otherwise specified, voltage values
are positive with respect to cathode*

ANODE VOLTAGE.	17500 max.	volts
GRID-No.4 (FOCUSING) VOLTAGE:		
Positive value	1100 max.	volts
Negative value	550 max.	volts



17LP4B

GRID-No.2 VOLTAGE	550 max.	volts
GRID-No.1 VOLTAGE:		
Negative peak value	220 max.	volts
Negative bias value	155 max.	volts
Positive bias value	0 max.	volts
Positive peak value	2 max.	volts
HEATER VOLTAGE.	{ 6.9 max.	volts
	{ 5.7 min.	volts
PEAK HEATER-CATHODE VOLTAGE:		
Heater negative with		
respect to cathode:		
During equipment warm-up period		
not exceeding 15 seconds.	450 max.	volts
After equipment warm-up period. . . .	200 max.	volts
Heater positive with		
respect to cathode:		
Combined AC and DC voltage.	200 max.	volts
DC component.	100 max.	volts

Typical Operating Conditions for Grid-Drive Service:

*Unless otherwise specified, voltage values
are positive with respect to cathode*

Anode Voltage	14000	volts
Grid-No.4 Voltage	-56 to +310	volts
Grid-No.2 Voltage	300	volts
Grid-No.1 Voltage for visual extinction of focused raster.	-28 to -72	volts

Maximum Circuit Value:

Grid-No.1-Circuit Resistance.	1.5 max.	megohms
---------------------------------------	----------	---------

For X-radiation shielding considerations, see sheet
X-RADIATION PRECAUTIONS FOR CATHODE-RAY TUBES
at front of this Section

