



117L7-GT/117M7-GT



117L7-GT

RECTIFIER-BEAM POWER AMPLIFIER

Heater	Coated Unipotential Cathodes	
Voltage	117	a-c or d-c volts
Current	0.09	amp.
Maximum Overall Length		3-7/16"
Maximum Seated Height		2-7/8"
Maximum Diameter		1-5/16"
Bulb		T-9
Base	Intermediate Shell Octal 8-Pin	
Pin 1-Rectifier Cathode		Pin 5-Amplifier Screen
Pin 2-Heater		Pin 6-Rectifier Plate
Pin 3-Amplifier Plate		Pin 7-Heater
Pin 4-Amplifier Grid		Pin 8-Amplifier Cathode
Mounting Position		Any

BOTTOM VIEW (8A0)

RECTIFIER UNIT (Half-Wave)

Peak Inverse Voltage	350 max.	volts
Peak Plate Current	450 max.	volts
D-C Heater to Cathode Potential	175 max.	volts
<i>With Condenser-Input Filter:</i>		
A-C Plate Voltage (RMS)	117 max.	volts
Total Effective Plate Supply		
Impedance	15 min.	ohms
D-C Output Current	75 max.	ma.

AMPLIFIER UNIT

Plate Voltage	117 max.	volts
Screen Voltage	117 max.	volts
Plate Dissipation	6.0 max.	watts
Screen Dissipation	1.0 max.	watt
<i>Typical Operation and Characteristics - Class A₁ Amplifier:</i>		
Plate	105	volts
Screen	105	volts
Grid	-5.2	volts
Peak A-F Grid Voltage	5.2	volts
Zero-Sig. Plate Cur.	43	ma.
Max.-Sig. Plate Cur.	43	ma.
Zero-Sig. Screen Cur.	4	ma.
Max.-Sig. Screen Cur.	5.5	ma.
Plate Resistance	17000 approx.	ohms
Transconductance	5300	μmhos
Load Resistance	4000	ohms
Total Harmonic Distortion	5	%
Max.-Sig. Power Output	0.85	watt

■ It is recommended that the potential difference between heater and cathode of the amplifier unit be kept as low as possible by connecting pin #2 to the side of the line opposite that to which pins #6 & #7 are connected.

May 1, 1941

RCA RADOTRON DIVISION
RCA MANUFACTURING COMPANY, INC.

TENTATIVE DATA