


follow the leaders to

EIMAC TUBES!



TRIODES

- | | |
|-----------|-------------|
| 2C39A | 100TL |
| 3W5000A3 | 152TH |
| 3W5000F3 | 152TL |
| 3W10000A3 | 250TH |
| 3X2500A3 | 250TL |
| 3X2500F3 | 304TH |
| 3X3000A1 | 304TL |
| 3X3000F1 | 450TH |
| 6C21 | 450TL |
| 25T | 592/3-200A3 |
| 35T | 750TL |
| 35TG | 1000T |
| 75TH | 1500T |
| 75TL | 2000T |
| 100TH | |



TETRODES

- | | |
|---------|----------|
| 4-65A | 4W20000A |
| 4-125A | 4X150A |
| 4-250A | 4X150D |
| 4-400A | 4X150G |
| 4-1000A | 4X500A |
| 4PR60A | 4X500F |



PENTODE


- 4E27A/5-125B

RECTIFIERS


- | | |
|---------|-------------|
| 2-01C | RX21A |
| 2-25A | 250R |
| 2-50A | 253 |
| 2-150D | 866A |
| 2-240A | 872A |
| 2-2000A | 8020 (100R) |
| KY21A | |

AIR SYSTEM SOCKETS

- 4-400A/4000
4-400A/4006*
4-1000A/4000
4-1000A/4006*
4X150A/4000
4X150A/4006*



*Replacement Chimneys



VACUUM SWITCH

- VS-2
12V Coil
24V Coil




ACCESSORIES

- HR Heat dissipating connectors
Preformed Contact Finger Stock

VACUUM PUMP

- HV-1
OIL
DIFFUSION
PUMP

- Type A
Pump Oil
HV-1
Pump Parts



VARIABLE VACUUM CAPACITORS


- VVC60-20
VVC2-60-20
VVC4-60-20

ION GAUGE

- 100 IG ion gauge

VACUUM CAPACITORS

- | | |
|---------|---------|
| VC6-20 | VC25-20 |
| VC6-32 | VC25-32 |
| VC12-20 | VC50-20 |
| VC12-32 | VC50-32 |




4-125A

The radial-beam power tetrode that made transmitting screen-grid tubes popular. This tube will take a plate input of 500 watts for CW or 380 watts for fone. Driving power is less than two watts. A pair of these tetrodes make an ideal high power fone or CW final for the amateur.



4X150A

This small external anode radial-beam power tetrode operates efficiently at all frequencies into the UHF range with a driving power of only a few watts. Its small size and ruggedness make it ideal for compact equipment such as mobile.



450T

Often referred to as the workhorse of modern communication systems, this dependable triode has a plate dissipation rating of 450 watts. It is widely used as an amplifier, oscillator or modulator.



3K20000L (A-F-K)

These Klystrons, the latest development in UHF television transmitting, have a power output of 5000 watts. The three versions of the Klystron will cover the entire UHF range—470-890 mc. These water and air cooled Klystrons have a power gain of 20 db.



VVC60-20

This is but one type in the Eimac line of variable and fixed vacuum capacitors for plate tank circuits. It is variable over a range of 10 mmfd to 60 mmfd. Maximum rf voltage is 20 kv. at 40 amperes.



2C39A

This small, rugged triode is designed for use as a power amplifier, oscillator or frequency multiplier to frequencies above 2500 mc. It is particularly suitable for compact fixed or mobile equipment.



● Complete technical data available on request.

EITEL-McCULLOUGH, INC.
SAN BRUNO, CALIFORNIA

EXPORT AGENTS: FRAZAR & HANSEN • 301 CLAY STREET • SAN FRANCISCO 11, CALIFORNIA