

Picture Tube

RECTANGULAR GLASS TYPE
LOW-VOLTAGE ELECTROSTATIC FOCUS
LOW GRID-No.2 VOLTAGE

ALUMINIZED SCREEN
92° MAGNETIC DEFLECTION
CATHODE-DRIVE TYPE

With Heater Having Controlled Warm-Up Time

GENERAL DATA

Electrical:

Heater Current at 6.3 volts.	600 ± 30	ma
Heater Warm-Up Time (Average).	11	seconds
Direct Interelectrode Capacitances:		
Grid No.1 to all other electrodes.	6	μf
Cathode to all other electrodes.	5	μf
External conductive coating to ultor	{2500 max. 1700 min.	{μf μf
Electron Gun	Type Requiring No Ion-Trap Magnet	


Optical:

Faceplate.	Filterglass
Light transmission (Approx.)	78%
Phosphor (For curves, see front of this Section) .P4—Sulfide Type, Aluminized	

Mechanical:

Operating Position	Any
Weight (Approx.)	25 lbs
Overall Length	18-1/8" ± 3/8"
Neck Length.	5-5/8" ± 3/16"
Projected Area of Screen	282 sq. in.
External Conductive Coating:	
Type	Regular Band
Contact area for grounding	Near Reference Line
For Additional Information on Coatings and Dimensions:	
See <i>Picture-Tube Dimensional-Outlines</i> and <i>Bulb J187 C/F</i> sheets at the front of this section	
Cap.	Recessed Small Cavity (JEDEC No.J1-21)
Base	Short Small-Shell Duodecal 6-Pin (JEDEC Group 4, No.86-203)
Basing Designation for BOTTOM VIEW	.12L

Pin 1—Heater
Pin 2—Grid No.1
Pin 6—Grid No.4
Pin 10—Grid No.2
Pin 11—Cathode
Pin 12—Heater



Cap—Ultor
(Grid No.3,
Grid No.5,
Collector)
C—External
Conductive
Coating



23BJP4

Maximum and Minimum Ratings, Design-Maximum Values:

ULTOR-TO-GRID-No.1 VOLTAGE.	{ 25000 max. 11000 min.	volts volts
GRID-No.4-TO-GRID-No.1 (FOCUSING) VOLTAGE:		
Positive value.	1250 max.	volts
Negative value.	450 max.	volts
GRID-No.2 TO-GRID-No.1 VOLTAGE.	{ 225 max. 40 min.	volts volts
GRID-No.2-TO-CATHODE VOLTAGE.	70 max.	volts
CATHODE-TO-GRID-No.1 VOLTAGE:		
Positive peak value	220 max.	volts
Positive bias value	154 max.	volts
Negative bias value	0 max.	volts
Negative peak value	2 max.	volts
HEATER VOLTAGE.	{ 6.9 max. 5.7 min.	volts volts
PEAK HEATER-CATHODE VOLTAGE:		
Heater negative with respect to cathode:		
During equipment warm-up period not exceeding 15 seconds.	450 max.	volts
After equipment warm-up period.	200 max.	volts
Heater positive with respect to cathode.	200 max.	volts

Typical Operating Conditions:

With ultor-to-grid No.1 voltage of	20000	volts
and grid-No.2-to-grid-No.1 voltage of	50	volts
Grid-No.4-to-Grid-No.1 Voltage for focus.	0 to 400	volts
Cathode-to-Grid-No.1 Voltage for visual extinction of focused raster.	36 to 54	volts

Maximum Circuit Values:

Grid-No.1-Circuit Resistance.	1.5 max.	megohms
---------------------------------------	----------	---------

For X-radiation shielding considerations, see sheet
X-RADIATION PRECAUTIONS FOR CATHODE-RAY TUBES
at front of this section

