

## ADVANCE DATA CHARACTERISTICS

### GENERAL DATA

|                               |                   |
|-------------------------------|-------------------|
| Focusing Method               | Electrostatic     |
| Deflection Method             | Magnetic          |
| Deflection Angles (approx.)   |                   |
| Horizontal                    | 85 Degrees        |
| Diagonal                      | 90 Degrees        |
| Phosphor                      | Aluminized P4     |
| Fluorescence                  | White             |
| Persistence                   | Short to Medium   |
| Faceplate                     | Gray Filter Glass |
| Light Transmittance (approx.) | 74 Percent        |

### ELECTRICAL DATA

|                                              |                      |
|----------------------------------------------|----------------------|
| Heater Voltage                               | 6.3 Volts            |
| Heater Current                               | 0.30 $\pm$ 5% Ampere |
| Heater Warm-up Time 1                        | 11 Seconds           |
| Direct Interelectrode Capacitances (approx.) |                      |
| Cathode to All Other Electrodes              | 5 $\mu$ f            |
| Grid No. 1 to All Other Electrodes           | 6 $\mu$ f            |
| External Conductive Coating to Anode 2       | 2500 $\mu$ f Max.    |
|                                              | 1700 $\mu$ f Min.    |

### MECHANICAL DATA

|                                                       |                         |
|-------------------------------------------------------|-------------------------|
| Minimum Useful Screen Dimensions<br>(Maximum Assured) | 21 7/16 x 16 7/8 Inches |
| Minimum Useful Screen Area                            | 332 Sq. Inches          |
| Bulb                                                  | J192A or J192B          |
| Bulb Contact (Recessed Small Cavity Cap)              | J1-21                   |
| Base                                                  | B6-63                   |
| Basing                                                | 12L                     |



### RATINGS

### MAXIMUM RATINGS (Absolute Maximum Values)

|                                            |                     |    |
|--------------------------------------------|---------------------|----|
| Anode Voltage                              | 22,000 Volts        | dc |
| Grid No. 4 Voltage<br>(Focusing Electrode) | -550 to +1100 Volts | dc |
| Grid No. 2 Voltage                         | 550 Volts           | dc |
| Grid No. 1 Voltage                         |                     |    |
| Negative Bias Value                        | 155 Volts           | dc |
| Negative Peak Value                        | 220 Volts           |    |
| Positive Bias Value                        | 0 Volts             | dc |
| Positive Peak Value                        | 2 Volts             |    |
| Peak Heater-Cathode Voltage                |                     |    |
| Heater Negative with respect to Cathode    |                     |    |
| During Warm-up Period not to Exceed        |                     |    |
| 15 Seconds                                 | 450 Volts           |    |
| After Equipment Warm-up Period             | 200 Volts           |    |
| Heater Positive with Respect to Cathode    | 200 Volts           |    |

### QUICK REFERENCE DATA

Television Picture Tube  
24" Direct Viewed  
Rectangular Glass Type  
Spherical Faceplate  
Gray Filter Glass  
Aluminized Screen  
Electrostatic Focus  
90° Magnetic Deflection  
Short Neck Tube  
No Ion Trap  
External Conductive Coating  
6.3 Volt, 300 Ma Heater



12-1

SYLVANIA ELECTRIC  
PRODUCTS INC.  
TELEVISION PICTURE TUBE  
DIVISION  
SENECA FALLS, NEW YORK

Prepared and Released By The  
TECHNICAL PUBLICATIONS SECTION  
EMPORIUM, PENNSYLVANIA

January 13, 1958

Page 1 of 3

SYLVANIA

24ASP4

Page 2

#### TYPICAL OPERATING CONDITIONS

|                                                     |            |       |    |
|-----------------------------------------------------|------------|-------|----|
| Anode Voltage                                       | 18,000     | Volts | dc |
| Grid No. 4 Voltage for Focus                        | 0 to +400  | Volts | dc |
| Grid No. 2 Voltage                                  | 300        | Volts | dc |
| Grid No. 1 Voltage Required for Cutoff <sup>3</sup> | -35 to -72 | Volts | dc |

#### CIRCUIT VALUES

|                               |                  |
|-------------------------------|------------------|
| Grid No. 1 Circuit Resistance | 1.5 Megohms Max. |
|-------------------------------|------------------|

#### NOTES:

1. Heater warm-up time is the time required for the voltage across the heater terminals to reach 80% of its rated value after applying 4 times rated heater voltage to a circuit consisting of the tube heater in series with a resistance equal to 3 times rated heater voltage divided by rated heater current.
2. External conductive coating must be grounded.
3. Visual extinction of focused raster. Extinction of stationary focused spot will require that these values be about 5 volts more negative.

#### WARNING:

X-ray radiation shielding may be necessary to protect against possible danger of personal injury from prolonged exposure at close range if this tube is operated at higher than the manufacturer's Maximum Rated Anode Voltage or 16,000 volts, whichever is less.

