



CIRCUIT DIAGRAM—BUSH MODELS AC.91 AND DAC.91

**Values.**  
 V1 CCH35  
 V2 EF39  
 V3 EBC33  
 V4 CL33  
 V5 CY31  
 I.F. 465 kc/s.

**Capacitors.**

- C1 0.005
- C2 800 pF.
- C3 0.005
- C4 50 pF.
- C5 0.05
- C6 30 pF.
- C7 110 pF.
- C8 0.05
- C9 0.05
- C10 110 pF.
- C11 50 pF.
- C12 180 pF.

- C13 390 pF.
- C14 556 pF.
- C15 0.05
- C16 0.05
- C17 0.01
- C18 0.05
- C19 110 pF.
- C20 100 pF.
- C21 50
- C22 110 pF.
- C23 50 pF.
- C24 50 pF.

- C25 0.006
  - C26 0.01
  - C27 16
  - C28 0.01
  - C29 32
  - C30 0.1
- Variable Capacitors.*  
 VC1 } 2 × 533 pF.  
 VC2 } Ganged  
 TC1-6 } 3-40 pF.

**Resistor.**

- R1 15k
- R2 100
- R3 1M
- R4 33k
- R5 2.2M
- R6 220
- R7 47k
- R8 220
- R9 10k
- R10 100k
- R11 2.2M
- R12 68k
- R13 1000
- R14 1M
- R15 470k
- R16 47k
- R17 150
- R18 10k
- R19 150
- R20 600 + 100 + 100
- VR1 500k