

CDP-208

SERVICE MANUAL

*US Model
Canadian Model
AEP Model
UK Model
E Model*



SPECIFICATIONS

Compact disc player

System	Compact disc digital audio system
Laser	Semiconductor laser ($\lambda = 780 \text{ nm}$) Emission duration: continuous
Laser output	Max. $44.6 \mu\text{W}^*$ * This output is the value measured at a distance of about 200 mm from the objective lens surface on the Optical Pick-up Block.
Frequency response	2Hz - 20,000 Hz ($\pm 0.3 \text{ dB}$)
Signal-to-noise ratio	More than 102 dB
Dynamic range	More than 95 dB
Harmonic distortion	Less than 0.003% (1kHz)
Channel separation	More than 98 dB (1kHz)

Outputs

LINE OUT (Fixed) (phono jacks)	Output level 2 V (at 50 kilohms) Load impedance over 10 kilohms
DIGITAL OUT (OPTICAL) (optical output connector)	Wave length 660 nm Output level -18 dBm
HEADPHONES (stereo phono jack)	Output level max. 15 mW Load Impedance 32 ohms

General

Power requirements	120 V AC, 60Hz
Power consumption	12W
Dimensions (approx.) (w/h/d)	430 × 95 × 275 mm (17 × 3 1/4 × 10 1/2 inches) including projecting parts and controls
Weight (approx., net)	3.5 kg (7 lbs 11 oz)

Model Name Using Similar Mechanism	CDP-208ESD
CD Transport Mechanism Type	KSS-150A(RP)
Optical Pick-Up Block Type	BU-5C

Supplied accessories

Audio signal connecting cord	1 (2 phono plugs - 2 phono plugs)
Remote commander	1
Sony SUM-3 (NS) batteries	2

Remote commander

Remote control system	Infrared control
Power requirements	3 V DC with two size AA (R6) batteries
Dimensions	67 × 20 × 175 mm (w/h/d) (2 1/4 × 13/16 × 7 inches)
Weight	135 g (5 oz) including batteries

Design and specifications subject to change without notice.

SAFETY-RELATED COMPONENT WARNING!!

COMPONENTS IDENTIFIED BY MARK Δ OR DOTTED LINE WITH MARK Δ ON THE SCHEMATIC DIAGRAMS AND IN THE PARTS LIST ARE CRITICAL TO SAFE OPERATION. REPLACE THESE COMPONENTS WITH SONY PARTS WHOSE PART NUMBERS APPEAR AS SHOWN IN THIS MANUAL OR IN SUPPLEMENTS PUBLISHED BY SONY.

COMPACT DISC PLAYER
SONY[®]

TABLE OF CONTENTS

<u>Section</u>	<u>Title</u>	<u>Page</u>	<u>Section</u>	<u>Title</u>	<u>Page</u>
SECTION 1 GENERAL			SECTION 4 EXPLODED VIEWS		
1-1.	Location of Controls	3	3-4.	Explanation of IC601 (MSC6458-36SS)	15
SECTION 2 ELECTRICAL ADJUSTMENTS 4			3-4-1.	Pin Description	15
SECTION 3 DIAGRAMS			3-5.	IC Block Diagrams	17
3-1.	Semiconductor Lead Layouts	7	SECTION 5 ELECTRICAL PARTS LIST 21		
3-2.	Printed wiring Boards	8			
3-3.	Schematic Diagram	11			

SAFETY CHECK-OUT

After correcting the original service problem, perform the following safety check before releasing the set to the customer:

Check the antenna terminals, metal trim, "metallized" knobs, screws, and all other exposed metal parts for AC leakage. Check leakage as described below.

LEAKAGE TEST

The AC leakage from any exposed metal part to earth ground and from all exposed metal parts to any exposed metal part having a return to chassis, must not exceed 0.5 mA (500 microamperes). Leakage current can be measured by any one of three methods.

1. A commercial leakage tester, such as the Simpson 229 or RCA WT-540A. Follow the manufacturers' instructions to use these instruments.
2. A battery-operated AC milliammeter. The Data Precision 245 digital multimeter is suitable for this job.

3. Measuring the voltage drop across a resistor by means of a VOM or battery-operated AC voltmeter. The "limit" indication is 0.75 V, so analog meters must have an accurate low-voltage scale. The Simpson 250 and Sanwa SH-63Trd are examples of a passive VOM that is suitable. Nearly all battery operated digital multimeters that have a 2V AC range are suitable. (See Fig. A)




Fig. A. Using an AC voltmeter to check AC leakage.

SERVICING NOTE

NOTES ON HANDLING THE OPTICAL PICK-UP BLOCK OR BASE UNIT

The laser diode in the optical pick-up block may suffer electrostatic breakdown because of the potential difference generated by the charged electrostatic load, etc. on clothing and the human body.

During repair, pay attention to electrostatic breakdown and also use the procedure in the printed matter which is included in the repair parts.

The flexible board is easily damaged and should be handled with care.

CAUTION

Use of controls or adjustments or performance of procedures other than those specified herein may result in hazardous radiation exposure.


NOTES ON LASER DIODE EMISSION CHECK

The laser beam on this model is concentrated so as to be focused on the disc reflective surface by the objective lens in the optical pick-up block. Therefore, when checking the laser diode emission, observe from more than 30 cm away from the objective lens.

SECTION 1 GENERAL


1-1. LOCATION OF CONTROLS

Front Panel



- 1 POWER switch
- 2 Disc compartment
- 3 REPEAT button
- 4 REMOTE sensor
- 5 FADER (FADE IN/FADE OUT) button
- 6 EDIT/TIME FADE button
- 7 CHECK (program check) button
- 8 CLEAR (program clear) button
- 9 <>> (manual search) buttons
- 10 PROGRAM or PGM button
- 11 SHUFFLE button
- 12 Numeric buttons
- 13 HEADPHONE VOL control
- 14 PHONES jack
- 15 > 20 (over 20) button
- 16 CONTINUE/SINGLE button
- 17 <>>> (AMS*) buttons
- 18 ■ (stop) button
- 19 II (pause) button
- 20 ▶ (play) button
- 21 ▲ (open/close) button
- 22 AUTO SPACE button
- 23 TIME button

Remote Commander



This indicates a function available only on the main unit.



This indicates a function available only on the remote commander.


*AMS is the abbreviation of Automatic Music Sensor.

SECTION 2 ELECTRICAL ADJUSTMENTS


1. Perform adjustments in the order given.
2. Use YEDS-18 (Part No: 3-702-101-01) disc unless otherwise indicated.
3. Use the oscilloscope with more than $10 \text{ M}\Omega$ impedance.

RF PLL Frequency Adjustment/Lock Frequency Check

Procedure :



1. Connect test point TP (ASY) to ground with lead wire.
2. Turn POWER switch on.
3. Connect the frequency counter to test point TP (PCK) and TP (AG).
4. Adjust RV201 so that the reading on the frequency counter is $4.3218\text{MHz} \pm 30\text{kHz}$ (RF PLL frequency adjustment).
5. Remove lead wire connecting TP (ASY) to ground.
6. Put disc (YEDS-18) in and press ▷ button.
7. Confirm that the reading on frequency counter is 4.3218MHz (Lock frequency check).




Adjustment Location : main board



E-F Balance Adjustment

This adjustment should be made when replacing TOP (T-type Optical Pick-up).

Procedure :




1. Connect test point TP (ADJ) and test point TP (TEI) to ground with lead wire.
2. Connect oscilloscope to test point TP (TEO) and TP (AG).
3. Turn POWER switch on.
4. Put disc (YEDS-18) in and press ▷ button.
5. Adjust RV101 so that the traverse waveform is symmetrical above and below.
6. After adjustment, remove the lead wire connected in step 5.



Focus Bias Adjustment

This adjustment should be made when replacing TOP (T-type Optical Pick-up).

Procedure :



REFERENCE

Focus/Tracking Gain Adjustments

A frequency response analyzer is necessary in order to perform this adjustment exactly.

However, this gain has a margin, so even if it is slightly off, there is no problem. Therefore, do not perform this adjustment.

Focus/tracking gain determines the pick-up follow up (vertical and horizontal) relative to mechanical noise and shock when the 2-axis device operate.

However, as these reciprocate, the adjustment is at the point where both are satisfied.

- When gain is raised, the noise when the 2-axis device operates increases.
- When gain is lowered, mechanical shock and skipping occurs more easily.
- When gain adjustment is off, the symptoms below appear.


Symptoms	Gain	Focus	Tracking
• The time until music starts becomes longer for ■ → ▶ or automatic selection. (◀◀, ▶▶ buttons pressed.) (Normally takes about 1 seconds.)	low	low or high	
• Music does not start and disc continues to rotate for ■ → ▶ or automatic selection. (◀◀, ▶▶ buttons pressed.)	—	low	
• Disc table opens shortly after ■ → ▶ .	low or high	—	
• Sound is interrupted during PLAY or time counter display stops progressing.	—	low	
• More noise during 2-axis device operation.	high	high	

The following is a simple adjustment method.

- Primary Adjustment -

Note : Since exact adjustment cannot be performed, remember the positions of the controls before performing the adjustment. If the position after the primary adjustment are only a little different, return the controls to the original position.

Procedure :







1. Keep the set horizontal.
 (If the set is not horizontal, this adjustment cannot be performed due to the gravity against the 2-axis device.)
2. Insert disc (YEDS-18: Fifth Selection) and press ▶ button.
3. Connect oscilloscope to main board TP (FEO).
4. Adjust RV103 so that the waveform is as shown in the figure below. (focus gain adjustment)
5. Connect oscilloscope to main board TP (TEO).
6. Adjust RV104 so that the waveform is as shown in the figure below. (tracking gain adjustment)




• Incorrect Examples (fundamental wave appears)



• Incorrect Examples (DC level changes more than on adjusted waveform)



Adjustment Location : main board



SECTION 3 DIAGRAMS




• Incorrect Examples (fundamental wave appears)



high tracking gain
higher fundamental wave than for low gain)



Adjustment Location : main board



3-1. SEMICONDUCTOR LEAD LAYOUTS

CXA1081S	GP1F31T	M5231TL	BR4361F
CXA1082BS	GP1U52	M5294P PCM56P-S	HZS9B2L RD5.1ESB2 1SS132
CXA1291P	LC9600P-144	NJM4556S	US1060M 10E2
CXD1125Q	MSC6458-36SS	DTA144ES DTC114ES DTC143TS DTC144ES	
CXD2550P	M5218P M74HC6004P	DTC114EF	


3-2. PRINTED WIRING BOARDS


• Refer to page 7 for Semiconductor Lead Layouts.


• Semiconductor Location

Ref. No.	Location
D001	C-4
D002	C-4
D003	C-4
D004	C-5
D005	D-6
D006	D-5
D401	D-3
D501	C-12
D601	I-18
D602	I-17
D603	I-17
D604	I-17
D605	I-14
D606	I-14
D607	I-14
D608	J-14
IC001	E-4
IC002	D-5
IC101	E-6
IC201	H-5
IC202	H-7
IC203	I-7
IC301	G-3
IC302	F-3
IC303	F-2
IC304	A-2
IC305	E-3
IC401	E-2
IC402	E-2
IC403	C-3
IC501	B-12
IC601	I-16
IC602	I-13
Q001	E-5
Q101	G-6
Q201	I-4
Q202	I-3
Q301	G-4
Q401	B-3
Q402	B-2
Q403	C-4
Q404	I-2
Q407	B-3
Q408	B-2
Q601	I-15
Q602	I-15
Q603	I-15


- : parts extracted from the component side.
- : Jumper wire connected to the ground pattern on the component side.








[SL/SP MOTOR BOARD]



**UP
50A (RP))**



IC201
FOCUS/TRACKING/SLED/SPINDLE SERVO

R 202
PITCHING

C301
SIGNAL PROCESSOR

C302
RAM

C303
DIGITAL FILTER

C304
PHONE AMP

C305
INVERTER

C306
PHONE AMP

C307
PHONE AMP

C308
PHONE AMP

C309
PHONE AMP

C310
PHONE AMP

C311
PHONE AMP

C312
PHONE AMP

C313
PHONE AMP


C314
PHONE AMP

C315
PHONE AMP

C316
PHONE AMP

EXCEPT FOR US MODEL

[MAIN BOARD]



* NOT REPLACEABLE : BUILT IN TRANSFORMER.

E MODEL

UK MODEL

AC IN

EXCEPT FOR UK MODE

AC IN

DIGITAL OUT OPTICAL

IC304 GP1F31T

CNP401

L-CH

H-CH

US MUTE

CNP401

L-CH

R-CH

EXCEPT FOR JS MUTE

LINE OUT FIXED

-1 R

-2 L

Q401, 402 Q407, 408 MUTING

Q403 MS218P

Q403 MUTING SWITCH

Q404 2SC3399

Q404 MUTING SWITCH

Q405 2SC3399

Q405 2SC3399

Q406 2SC3399

Q406 2SC3399

Q407 2SC3399

Q407 2SC3399

Q408 2SC3399

Q408 2SC3399

Q409 2SC3399

Q409 2SC3399

Q410 2SC3399

Q410 2SC3399

Q411 2SC3399

Q411 2SC3399

Q412 2SC3399

Q412 2SC3399

Q413 2SC3399

Q413 2SC3399

Q414 2SC3399

Q414 2SC3399

Q415 2SC3399

Q415 2SC3399

Q416 2SC3399

Q416 2SC3399

Q417 2SC3399

Q417 2SC3399

Q418 2SC3399

Q418 2SC3399

Q419 2SC3399

Q419 2SC3399

Q420 2SC3399

Q420 2SC3399

Q421 2SC3399

Q421 2SC3399

Q422 2SC3399

Q422 2SC3399

Q423 2SC3399

Q423 2SC3399

Q424 2SC3399

Q424 2SC3399

Q425 2SC3399

Q425 2SC3399

Q426 2SC3399

Q426 2SC3399

Q427 2SC3399

Q427 2SC3399

Q428 2SC3399

Q428 2SC3399

Q429 2SC3399

Q429 2SC3399

Q430 2SC3399

Q430 2SC3399

Q431 2SC3399

Q431 2SC3399

Q432 2SC3399

Q432 2SC3399

Q433 2SC3399

Q433 2SC3399

Q434 2SC3399

Q434 2SC3399

Q435 2SC3399

Q435 2SC3399

Q436 2SC3399

Q436 2SC3399

Q437 2SC3399

Q437 2SC3399

Q438 2SC3399

Q438 2SC3399

Q439 2SC3399

Q439 2SC3399

Q440 2SC3399

Q440 2SC3399

Q441 2SC3399

Q441 2SC3399

Q442 2SC3399

Q442 2SC3399

Q443 2SC3399

Q443 2SC3399

Q444 2SC3399

Q444 2SC3399

Q445 2SC3399

Q445 2SC3399

Q446 2SC3399

Q446 2SC3399

Q447 2SC3399

Q447 2SC3399

Q448 2SC3399

Q448 2SC3399

Q449 2SC3399

Q449 2SC3399

Q450 2SC3399

Q450 2SC3399

Q451 2SC3399

Q451 2SC3399

Q452 2SC3399

Q452 2SC3399

Q453 2SC3399

Q453 2SC3399

Q454 2SC3399

Q454 2SC3399

Q455 2SC3399

Q455 2SC3399

Q456 2SC3399

Q456 2SC3399

Q457 2SC3399

Q457 2SC3399

Q458 2SC3399

Q458 2SC3399

Q459 2SC3399

Q459 2SC3399

Q460 2SC3399

Q460 2SC3399

Q461 2SC3399

Q461 2SC3399

Q462 2SC3399


Q462 2SC3399

Q463 2SC3399


Q463 2SC3399

Q464 2SC3399

Q464 2SC3399




• WAVEFORMS



- All capacitors are in μF unless otherwise noted. pF : μpF 50W or less are not indicated except for electrolytics and tantalums.
- All resistors are in Ω and $1/2\text{W}$ or less unless otherwise specified.
- \triangle : internal component.
- : B+ Line
- - - : B- Line
- [] : adjustment for repair.
- Voltage and waveforms are dc with respect to ground under no-signal conditions.
no mark : STOP
- Voltages are taken with a VOM (Input Impedance 10M Ω). Voltage variations may be noted due to normal production tolerances.
- Waveforms are taken with a oscilloscope.
Voltage variations may be noted due to normal production tolerances.
- Circled numbers refer to waveforms.
- Signal path.
- CD

Note:
The components identified by mark \triangle or dotted line with mark \triangle are critical for safety.
Replace only with part number specified.

Note:
Les composants identifiés par une marque \triangle ou une ligne pointillée avec une marque \triangle sont critiques pour la sécurité.
Ne les remplacer que par une pièce portant le numéro spécifié.



3-4. EXPLANATION OF IC601 (MSC6458-36SS)


IC601 have function of digit signal output to operation key, SUB Q signal taking in and management, tube (FLD) and control of servo system, etc.

3-4-1. Pin Description


Pin No.	Symbol	I/O	Description
1	PLL SW	O	In play "L", in serch "H".
2	CLK	O	Command transmission clock to SSP (IC201) and DSP (IC301).
3	DATA	O	Command transmission data to SSP (IC201) and DSP (IC301).
4	XLT	O	Command transmission ratch to SSP (IC201) and DSP (IC301).
5	PRGL	O	Command transmission ratch to DFIL (IC303).
6	SYNC OUT	O	NC
7	SENSE	I	SENSE information of SSP (IC201) and DSP (IC301).
8	—	I	NC
9	SIRCS	I	Remote control signal input.
10	SCOR	I	Q code read timing.
11	AF ADJ	I	NC
12	ADJ	I	Test mode on "L".
13	AMUTE	O	To MUTG of all mute DSP (IC301).
14	E MPS	O	NC
15	SUBQ	I	Subcode data.
16	SQCLK	O	Subcode data readout clock.
17	GFS	I	In CLV rock "H".
18	FOK	I	In FOCUS ON "H".
19	KEY 0	I	Key matrix input "H" active.
20	KEY 1	I	Key matrix input "H" active.
21	KEY 2	I	Key matrix input "H" active.
22	KEY 3	I	Key matrix input "H" active.
23	KEY 4	I	Key matrix input "H" active.
24	KEY 5	I	Key matrix input "H" active.
25	INSW	I	Loading in SW.
26	LDON	O	Laser ON/OFF.
27	OUT SW	I	Loading out SW.
28	LODOUT	O	Loading motor control.
29	LODIN	O	Loading motor control.
30	OSC I	I	Pulse input (4MHz)
31	OSC O	O	Pulse output (4MHz)
32	GND	—	GND
33	RESET	I	Reset input : In POWER ON "Input".
34	TEST	—	NC
35	VL DOWN	—	NC
36	VL UP	O	Volume up signal.

Pin No.	Symbol	I/O	Description
37	TIMER	O	NC
38	VL LAMP	O	Volume indicator.
39	8G	—	NC
40	7G	O	FLD timing output.
41	6G	O	FLD timing output.
42	5G	O	FLD timing output.
43	4G	O	FLD timing output.
44	3G	O	FLD timing output.
45	2G	O	FLD timing output.
46	1G	O	FLD timing output.
47	—	—	NC
48	o	O	FLD segment output.
49	n	O	FLD segment output.
50	m	O	FLD segment output.
51	+30V	—	+30V
52	l	O	FLD segment output.
53	k	O	FLD segment output.
54	j	O	FLD segment output.
55	i	O	FLD segment output.
56	h	O	FLD segment output.
57	g	O	FLD segment output.
58	f	O	FLD segment output.
59	e	O	FLD segment output.
60	d	O	FLD segment output.
61	c	O	FLD segment output.
62	b	O	FLD segment output.
63	a	O	FLD segment output.
64	VDD	—	Power supply (+5V)


IC101 CXA1081S



IC002 M5231



IC201 CXA1082BS



SECTION 4

NOT

- The mechanical parts with no reference number in the exploded views are not supplied.
 - The construction parts of an assembly part are indicated with a collation number in the remark column.
 - Items marked "*" are not stocked since they are seldom required for routine service. Some delay should be anticipated when ordering these items.


- Due to standardization, parts with part number suffix -XX and -X may be different from the parts specified in the components used on the set.

- Color Indication of Appearance Parts
 Example:
 (RED) ... KNOB, BALANCE (WHITE)
 ↑ ↑
 Cabinet's Color Parts' Color

The components identified by mark  or dotted line with mark  are critical for safety.
Replace only with part number specified.


Les composants identifiés par une marque  sont critiques pour la sécurité.
Ne les remplacer que par une pièce portant le numéro spécifié.

4-1. MAIN BLOCK



Ref.No	Part No.	Description	Remarks	Ref.No	Part No.	Description	Remarks
1	4-922-977-01	(EXCEPT FOR US)... KNOB (HP)		37	* 4-922-959-41	(AEP)... PLATE (JACK), INDICATION	
2	4-922-979-01	(EXCEPT FOR US)... INDICATOR			* 4-922-959-51	(E)... PLATE (JACK), INDICATION	
3	4-922-978-01	(EXCEPT FOR US)... HOLDER (FIBER)			* 4-922-959-61	(UK)... PLATE (JACK), INDICATION	
4	A-4665-024-A	(AEP, UK, E)... PANEL ASSY, FRONT		38	4-917-514-01	SPRING, TENSION	
	X-4922-921-1	(US)... PANEL ASSY, FRONT		39	4-922-508-01	GEAR (DRIVING)	
	X-4922-922-1	(Canadian)... PANEL ASSY, FRONT		40	4-917-519-01	LEVER, SET	
5	3-831-441-XX	CUSHION		41	* 4-925-346-01	CHASSIS	
6	4-922-966-01	PLATE, INDICATION		42	* 4-922-960-01	PLATE, BOTTOM	
7	4-922-921-01	BUTTON (POWER)		43	7-685-878-01	SCREW +BVTP 2.6X8 TYPE2 N-S	
8	7-685-134-19	SCREW +BTP 2.6X8 TYPE2 N-S		44	X-4922-917-1	(AEP, UK)... FOOT ASSY (F)	
9	7-685-647-79	SCREW +BVTP 3X10 TYPE2 N-S		45	X-4922-918-1	(AEP, UK)... FOOT ASSY (R)	
10	4-922-964-01	BUTTON (T/R), CONTROL		46	4-917-522-02	BELT	
11	4-922-963-01	BUTTON (B), CONTROL		47	* 4-922-980-01	(EXCEPT FOR US)... HOLDER (LED)	
12	4-922-962-01	BUTTON (A), CONTROL		48	4-922-942-01	(EXCEPT FOR UK)... FOOT (FELT)	
13	4-922-972-01	BUTTON (P/M)		49	4-922-531-01	(US)... KNOB (A TYPE), LOV	
14	4-922-976-01	BUTTON (C)		901	* 1-628-252-11	(EXCEPT FOR US)... PC BOARD, VOL	
15	4-922-976-01	BUTTON (M/C)		902	* 1-628-253-11	(EXCEPT FOR US)... PC BOARD, MOTOR	
16	* 4-925-307-01	TABLE, DISK		903	* 1-625-256-11	PC BOARD, IN/OUT SWITCH	
17	4-922-965-11	PANEL, LOADING		904	* 1-628-254-11	PC BOARD, POWER SWITCH	
18	* 4-922-529-01	DAMPER		905	* 1-628-249-11	PC BOARD, DISPLAY	
19	* 4-925-345-01	HOLDER (MG)		906	* A-4617-057-A	(US)... MOUNTED PCB, MAIN	
20	* 4-918-679-04	PULLEY, PRESS			* A-4617-062-A	(E)... MOUNTED PCB, MAIN	
21	A-4665-024-A	MAGNET ASSY			* A-4651-217-A	(Canadian, AEP, UK)... MOUNTED PCB, MAIN	
22	4-925-335-01	SPRING, COMPRESSION		907	* 1-628-251-11	PC BOARD, JACK	
23	4-925-348-01	CASE		908	* 1-628-255-11	PC BOARD, LOADING MOTOR	
24	7-685-650-79	SCREW (2), TAPPING		909	▲1-551-188-XX	(E)... CORD, POWER	
25	7-685-647-79	SCREW +BVTP 3X10 TYPE2 N-S			▲1-557-577-11	(US, Canadian)... CORD, POWER	
26	7-685-152-19	SCREW, STEP		910	1-526-565-00	AC PLUG ADAPTOR	
27	4-925-306-01	GEAR (LOADING)		913	▲1-556-035-00	(UK)... CORD, POWER	
28	3-703-571-11	(E)... BUSHING (S) (4516), CORD		914	* 1-628-257-11	(US)... PC BOARD, HP	
	* 3-703-244-00	(EXCEPT FOR E)... BUSHING (2104), CORD		915	▲1-555-795-00	(AEP)... CORD, POWER, EULO PLUG	
29	4-917-515-01	ROLLER		FLO601	1-519-475-11	INDICATOR TUBE, FLUORESCENT	
30	* 4-922-514-01	BRACKET (BU-5)		M103	A-4608-346-A	MOTOR ASSY, L (LOADING)	
31	4-917-526-01	SPRING, TENSION		RV501	1-238-314-11	(EXCEPT FOR US)... RES, VAR, CARBON 10K/10K (LINE OUT/PHONE LEVEL) (INCLUDING M901)	
32	4-917-507-01	SPRING (H)		RV502	1-238-478-11	(US)... RES, VAR, CARBON 20K/20K (HEADPHONE VOL)	
33	4-917-541-01	SPRING (B)		S701	1-571-300-11	SWITCH, ROTARY (IN/OUT)	
34	4-917-508-01	HOLDER, SP		T901	▲1-449-024-11	(US, Canadian)... TRANSFORMER, POWER	
35	7-685-535-11	SCREW +BTP 2.6X10 TYPE2 N-S		T901	▲1-449-025-11	(AEP, UK)... TRANSFORMER, POWER	
36	4-922-512-01	PULLEY		T901	▲1-449-026-11	(E)... TRANSFORMER, POWER	
37	* 4-922-959-11	(US)... PLATE (JACK), INDICATION					
	* 4-922-959-31	(Canadian)... PLATE (JACK), INDICATION					

**4-2. OPTICAL PICK-UP BLOCK
(BU-5C)**



Note:
The components identified by mark or dotted line with mark are critical for safety. Replace only with part number specified.

Note:
Les composants identifiés par une marque sont critiques pour la sécurité.
Ne les remplacer que par une pièce portant le numéro spécifié.

Ref.No	Part No.	Description	Remarks
51	4-917-566-01	SHAFT, SLED	
52	4-917-562-01	INSULATOR	
53	7-621-255-15	SCREW +P 2X3	
54	4-917-567-01	GEAR (M)	
55	4-917-564-01	GEAR (P), FLATNESS	
911	A.8-848-062-01	DEVICE, OPTICAL KSS-150A(RP)	

Ref.No	Part No.	Description	Remarks
912	* 1-626-304-11	PC BOARD, SL/SP MOTOR	
	* 1-564-720-11	PIN, CONNECTOR (SMALL TYPE) 4P	
M101	X-4917-504-1	MOTOR ASSY (SLED)	
M102	X-4917-523-1	MOTOR ASSY (SPINDLE)	
S101	1-571-274-11	SWITCH, LEAF (LIMIT IN)	

SECTION 5

ELECTRICAL PARTS LIST

NOTE:

- Due to standardization, replacements in the parts list may be different from the parts specified in the diagrams or the components used on the set.
- Items marked “★” are not stocked since they are seldom required for routine service. Some delay should be anticipated when ordering these items.
- If there are two or more same circuits in a set such as a stereophonic machine, only typical circuit parts may be indicated and capacitors and resistors in other same circuits may be omitted.

CAPACITORS:MF: μF , PF: μPF .**RESISTORS**

- All resistors are in ohms.
- F: nonflammable

COILS

- MMH: mH, UH: μH

SEMICONDUCTORS

In each case, U: μ , for example:
 UA...: μA ...; UPA...: μPA ...;
 UPC...: μPC , UPD...: μPD ...

The components identified by mark or dotted line with mark are critical for safety. Replace only with part number specified.

Les composants identifiés par une marque sont critiques pour la sécurité.

Ne les remplacer que par une pièce portant le numéro spécifié.

Ref.No	Part No.	Description	Ref.No	Part No.	Description
901	*1-628-252-11	(EXCEPT FOR US)...PC BOARD, VOL	C214	1-124-499-11	ELECT
902	*1-628-253-11	(EXCEPT FOR US)...PC BOARD, MOTOR	C215	1-124-499-11	ELECT
903	*1-625-256-11	PC BOARD, IN/OUT SWITCH	C216	1-124-499-11	ELECT
904	*1-628-254-11	PC BOARD, POWER SWITCH	C217	1-161-375-00	CERAMIC
905	*1-628-249-11	PC BOARD, DISPLAY	C218	1-162-291-31	CERAMIC
906	*A-4617-057-A	(US)...MOUNTED PCB, MAIN	C219	1-123-875-11	ELECT
	*A-4617-062-A	(E)...MOUNTED PCB, MAIN	C220	1-136-165-00	FILM
	*A-4651-217-A	(Canadian, AEP, UK)...MOUNTED PCB, MAIN	C225	1-126-101-11	ELECT
907	*1-628-251-11	PC BOARD, JACK	C226	1-126-101-11	ELECT
908	*1-628-255-11	PC BOARD, LOADING MOTOR	C227	1-126-101-11	ELECT
909	-1-551-188-XX	(E)...CORD, POWER	C228	1-126-101-11	ELECT
	-1-557-577-11	(US, Canadian)...CORD, POWER	C229	1-164-159-11	CERAMIC
910	1-526-565-00	AC PLUG ADAPTOR	C230	1-164-159-11	CERAMIC
911	-8-848-062-01	DEVICE, OPTICAL KSS-150A(RP)	C301	1-124-902-00	ELECT
912	*1-626-304-11	PC BOARD, SL/SP MOTOR	C302	1-136-159-00	FILM
913	-1-556-035-00	(UK)...CORD, POWER	C303	1-161-379-00	CERAMIC
914	*1-628-257-11	(US)...PC BOARD, HP	C304	1-124-902-00	ELECT
915	-1-555-795-00	(AEP)...CORD, POWER, EULO PLUG	C305	1-124-499-11	ELECT
	<u>CAPACITOR</u>				
C001	1-126-017-11	ELECT	6800MF	20%	16V
C002	1-124-887-00	ELECT	3300MF	20%	16V
C003	1-124-927-11	ELECT	4.7MF	20%	50V
C004	1-124-927-11	ELECT	4.7MF	20%	50V
C005	1-123-875-11	ELECT	10MF	20%	50V
C006	1-164-159-11	CERAMIC	0.1MF		
C007	1-124-472-11	ELECT	470MF	20%	10V
C008	1-124-472-11	ELECT	470MF	20%	10V
C009	1-124-572-11	ELECT	100MF	20%	63V
C010	1-124-122-11	ELECT	100MF	20%	50V
C101	1-161-375-00	CERAMIC	0.0022MF	30%	16V
C103	1-124-477-11	ELECT	47MF	20%	16V
C104	1-162-294-31	CERAMIC	0.001MF	10%	50V
C105	1-162-199-31	CERAMIC	10PF	5%	50V
C106	1-162-199-31	CERAMIC	10PF	5%	50V
C108	1-161-375-00	CERAMIC	0.0022MF	30%	16V
C109	1-136-153-00	FILM	0.01MF	5%	50V
C110	1-136-153-00	FILM	0.01MF	5%	50V
C111	1-126-233-11	ELECT	22MF	20%	25V
C112	1-126-233-11	ELECT	22MF	20%	25V
C113	1-136-159-00	FILM	0.033MF	5%	50V
C114	1-161-377-00	CERAMIC	0.0047MF	30%	16V
C201	1-136-165-00	FILM	0.1MF	5%	50V
C202	1-136-159-00	FILM	0.033MF	5%	50V
C203	1-123-382-00	ELECT	3.3MF	20%	50V
C204	1-136-165-00	FILM	0.1MF	5%	50V
C205	1-161-379-00	CERAMIC	0.01MF	20%	16V
C206	1-161-377-00	CERAMIC	0.0047MF	30%	16V
C207	1-124-927-11	ELECT	4.7MF	20%	50V
C208	1-124-477-11	ELECT	47MF	20%	16V
C209	1-162-294-31	CERAMIC	0.001MF	10%	50V
C210	1-162-282-31	CERAMIC	100PF	10%	50V
C211	1-126-233-11	ELECT	22MF	20%	25V
C212	1-126-233-11	ELECT	22MF	20%	25V
C213	1-126-233-11	ELECT	22MF	20%	25V
	<u>CAPACITOR</u>				
C308	1-126-233-11	ELECT	22MF	20%	25V
C310	1-162-204-31	CERAMIC	16PF	5%	50V
C311	1-162-203-31	CERAMIC	15PF	5%	50V
C312	1-164-159-11	CERAMIC	0.1MF		
C313	1-124-443-00	ELECT	100MF	20%	10V
C314	1-124-443-00	ELECT	100MF	20%	10V
C315	1-136-173-00	FILM	0.47MF	5%	50V
C316	1-164-159-11	(US)...CERAMIC	0.1MF		
C401	1-130-481-00	MYLAR	0.0068MF	5%	50V
C402	1-130-481-00	MYLAR	0.0068MF	5%	50V
C403	1-130-475-00	MYLAR	0.0022MF	5%	50V
C404	1-130-475-00	MYLAR	0.0022MF	5%	50V
C405	1-123-330-00	ELECT	22MF	20%	25V
C406	1-123-330-00	ELECT	22MF	20%	25V
C407	1-130-475-00	MYLAR	0.0022MF	5%	50V
C408	1-130-475-00	MYLAR	0.0022MF	5%	50V
C411	1-126-103-11	ELECT	470MF	20%	16V
C412	1-126-103-11	ELECT	470MF	20%	16V
C415	1-162-294-31	CERAMIC	0.001MF	10%	50V
C501	1-124-477-11	(EXCEPT FOR US)			
	<u>ELECT</u>				
C502	1-124-477-11	(EXCEPT FOR US)	47MF	20%	16V
C503	1-162-290-31	CERAMIC	470PF	10%	50V
C504	1-162-290-31	CERAMIC	470PF	10%	50V
C505	1-124-443-00	(EXCEPT FOR US)			
	<u>ELECT</u>				
C506	1-124-443-00	(EXCEPT FOR US)	100MF	20%	10V
	<u>ELECT</u>				
C551	1-124-589-11	(US)...ELECT	47MF	20%	16V
C552	1-124-589-11	(US)...ELECT	47MF	20%	16V
C601	1-164-159-11	CERAMIC	0.1MF		
C602	1-164-159-11	CERAMIC	0.1MF		
C603	1-162-290-31	CERAMIC	470PF	10%	50V
C604	1-162-290-31	CERAMIC	470PF	10%	50V

Ref.No	Part No.	Description				
C605	1-162-290-31	CERAMIC	470PF	10%	50V	
C606	1-164-159-11	CERAMIC	0.1MF		50V	
CNJ101 * 1-564-720-11	PIN, CONNECTOR (SMALL TYPE) 4P					
CNJ604 1-535-743-11	JUMPER, FILM (WITH TERMINAL)					
CNP001 * 1-564-340-00	PIN, CONNECTOR 6P					
CNP102 * 1-564-710-11	PIN, CONNECTOR (SMALL TYPE) 8P					
CNP201 * 1-564-706-11	PIN, CONNECTOR (SMALL TYPE) 4P					
CNP202 * 1-564-339-00	PIN, CONNECTOR 5P					
CNP203 * 1-564-336-61	(EXCEPT FOR US)...PIN, CONNECTOR 2P					
CNP204 1-566-908-11	SOCKET, CONNECTOR 32P					
CNP401 * 1-564-711-11	PIN, CONNECTOR (SMALL TYPE) 9P					
CNP501 * 1-564-336-00	(EXCEPT FOR US)...PIN, CONNECTOR 2P					
CNP602 * 1-564-497-11	PIN, CONNECTOR 4P					
CNP801 * 1-564-495-11	PIN, CONNECTOR 2P					
D001 Δ -8-719-200-02	DIODE 10E2					
D002 Δ -8-719-200-02	DIODE 10E2					
D003 Δ -8-719-200-02	DIODE 10E2					
D004 Δ -8-719-200-02	DIODE 10E2					
D005 Δ -8-719-200-02	DIODE 10E2					
D006 8-719-109-85	DIODE RD5.1ES-B2					
D401 8-719-107-94	DIODE ISS202-1					
D501 8-719-970-49	(EXCEPT FOR US)...DIODE BR4361F					
D601 8-719-000-26	DIODE US1060M					
D602 8-719-000-26	DIODE US1060M					
D603 8-719-000-26	DIODE US1060M					
D604 8-719-000-26	DIODE US1060M					
D605 8-719-000-26	DIODE US1060M					
D606 8-719-000-26	DIODE US1060M					
D607 8-719-000-26	DIODE US1060M					
D608 8-719-933-57	DIODE HZS9B2L					
FLD601 1-519-475-11	INDICATOR TUBE, FLUORESCENT					
IB101 1-233-171-11	COMPOSITION CIRCUIT BLOCK					
IB102 1-233-171-11	COMPOSITION CIRCUIT BLOCK					
IC001 8-759-631-40	IC M5294P					
IC002 8-759-605-43	IC M5231TL					
IC101 8-752-034-00	IC CXA1081S					
IC201 8-752-032-30	IC CXA1082BS					
IC202 8-752-035-28	IC CXA1291P					
IC203 8-752-035-28	IC CXA1291P					
IC301 8-752-328-62	IC CXD1125Q					
IC302 8-752-323-64	IC CXK5816M-12L					
IC303 8-752-328-72	IC CXD2550P					
IC304 8-759-977-71	IC GP1F3ET (DIGITAL OUT OPTICAL)					
IC305 8-759-605-44	IC M74HC6004P					
IC401 8-759-937-95	IC PCM56P-S					
IC402 8-759-937-95	IC PCM56P-S					
IC403 8-759-945-58	IC RC4558P					
IC501 8-759-981-89	IC RC4556S					
IC601 8-759-980-34	IC MSC6458-35SS					
IC602 8-749-920-03	IC GP1U52					
J401 * 1-562-999-21	JACK, PIN 2P (LINE OUT FIXED)					
J501 1-507-796-71	JACK, LARGE TYPE (PHONES)					
M101 X-4917-504-1	MOTOR ASSY (SLED)					
M102 X-4917-523-1	MOTOR ASSY (SPINDLE)					
M103 A-4608-346-A	MOTOR ASSY, L (LOADING)					
Q001 8-729-600-95	TRANSISTOR 2SK381-C					
Q101 8-729-801-83	TRANSISTOR 2SB1013					
Q201 8-729-900-80	TRANSISTOR DTC114ES					
Q202 8-729-900-89	TRANSISTOR DTC144ES					
Q301 8-729-900-89	TRANSISTOR DTC144ES					
Q401 8-729-900-74	TRANSISTOR DTC143ES					

Ref.No	Part No.	Description				
Q402	8-729-900-74	TRANSISTOR DTC143ES				
Q403	8-729-900-65	TRANSISTOR DTA144ES				
Q404	8-729-900-89	TRANSISTOR DTC144ES				
Q407	8-729-900-74	TRANSISTOR DTC143ES				
Q408	8-729-900-74	TRANSISTOR DTC143ES				
Q601	8-729-900-45	TRANSISTOR DTC114EF				
Q602	8-729-900-45	TRANSISTOR DTC114EF				
Q603	8-729-900-45	TRANSISTOR DTC114EF				
<u>RESISTOR</u>						
R001	1-249-439-11	CARBON	68K	5%	1/4W	
R002	1-249-423-11	CARBON	3.3K	5%	1/4W	
R003	1-249-417-11	CARBON	1K	5%	1/4W	
R004	1-249-429-11	CARBON	10K	5%	1/4W	
R101	1-247-864-11	CARBON	24K	5%	1/4W	
R104	1-249-397-11	CARBON	22	5%	1/4W	
R105	1-247-806-11	CARBON	91	5%	1/4W	
R106	1-249-433-11	CARBON	22K	5%	1/4W	
R108	1-249-432-11	CARBON	18K	5%	1/4W	
R109	1-249-432-11	CARBON	18K	5%	1/4W	
R110	1-249-425-11	CARBON	4.7K	5%	1/4W	
R111	1-249-425-11	CARBON	4.7K	5%	1/4W	
R112	1-249-417-11	CARBON	1K	5%	1/4W	
R201	1-247-882-11	CARBON	130K	5%	1/4W	
R202	1-249-432-11	CARBON	18K	5%	1/4W	
R203	1-249-432-11	CARBON	18K	5%	1/4W	
R204	1-249-440-11	CARBON	82K	5%	1/4W	
R205	1-247-889-00	CARBON	270K	5%	1/4W	
R206	1-249-435-11	CARBON	33K	5%	1/4W	
R207	1-249-423-11	CARBON	3.3K	5%	1/4W	
R208	1-249-425-11	CARBON	4.7K	5%	1/4W	
R209	1-247-896-11	CARBON	510K	5%	1/4W	
R210	1-249-417-11	CARBON	1K	5%	1/4W	
R211	1-249-414-11	CARBON	560	5%	1/4W	
R212	1-249-433-11	CARBON	22K	5%	1/4W	
R213	1-249-441-11	CARBON	100K	5%	1/4W	
R214	1-215-434-00	METAL	3.6K	1%	1/6W	
R215	1-249-441-11	CARBON	100K	5%	1/4W	
R216	1-249-429-11	CARBON	10K	5%	1/4W	
R217	1-247-881-00	CARBON	120K	5%	1/4W	
R218	1-249-427-11	CARBON	6.8K	5%	1/4W	
R219	1-249-435-11	CARBON	33K	5%	1/4W	
R220	1-249-437-11	CARBON	47K	5%	1/4W	
R221	1-247-882-11	CARBON	130K	5%	1/4W	
R222	1-247-883-00	CARBON	150K	5%	1/4W	
R223	1-247-882-11	CARBON	130K	5%	1/4W	
R224	1-247-883-00	CARBON	150K	5%	1/4W	
R225	1-249-429-11	CARBON	10K	5%	1/4W	
R226	1-249-441-11	(EXCEPT FOR US) ...CARBON	100K	5%	1/4W	
R227	1-249-441-11	(EXCEPT FOR US) ...CARBON	100K	5%	1/4W	
R228	1-249-441-11	(EXCEPT FOR US) ...CARBON	100K	5%	1/4W	
R229	1-249-441-11	(EXCEPT FOR US) ...CARBON	100K	5%	1/4W	
R230	1-249-393-11	CARBON	10	5%	1/4W	
R231	1-249-393-11	CARBON	10	5%	1/4W	
R232	1-249-425-11	CARBON	4.7K	5%	1/4W	
R236	1-249-417-11	CARBON	1K	5%	1/4W	
R237	1-249-417-11	CARBON	1K	5%	1/4W	
R238	1-249-417-11	CARBON	1K	5%	1/4W	
R239	1-249-417-11	CARBON	1K	5%	1/4W	
R301	1-247-903-00	CARBON	1M	5%	1/4W	
R302	1-249-433-11	CARBON	22K	5%	1/4W	
R303	1-249-429-11	CARBON	10K	5%	1/4W	

Note:
The components identified by mark Δ or dotted line with mark Δ are critical for safety.
Replace only with part number specified.

Note:
Les composants identifiés par une marque Δ sont critiques pour la sécurité.
Ne les remplacer que par une pièce portant le numéro spécifié.

Ref.No	Part No.	Description	Ref.No	Part No.	Description
R304	I-249-441-11	CARBON 100K 5% 1/4W	R560	I-249-402-11	(US)....CARBON 56 5% 1/4W
R305	I-249-441-11	CARBON 100K 5% 1/4W	R601	I-249-435-11	CARBON 33K 5% 1/4W
R306	I-249-429-11	CARBON 10K 5% 1/4W	R602	I-249-435-11	CARBON 33K 5% 1/4W
R307	I-215-469-00	METAL 100K 1% 1/6W	R603	I-249-435-11	CARBON 33K 5% 1/4W
R308	I-215-469-00	METAL 100K 1% 1/6W	R604	I-249-435-11	CARBON 33K 5% 1/4W
R310	I-249-421-11	CARBON 2.2K 5% 1/4W	R605	I-249-435-11	CARBON 33K 5% 1/4W
R311	I-249-421-11	CARBON 2.2K 5% 1/4W	R606	I-249-435-11	CARBON 33K 5% 1/4W
R312	I-249-421-11	CARBON 2.2K 5% 1/4W	R607	I-249-435-11	CARBON 33K 5% 1/4W
R314	I-249-413-11	CARBON 470 5% 1/4W	R609	I-249-411-11	(EXCEPT FOR US) ...CARBON 330 5% 1/4W
R315	I-249-413-11	CARBON 470 5% 1/4W	RV101	I-228-995-00	RES, ADJ, CARBON 22K
R316	I-249-413-11	CARBON 470 5% 1/4W	RV102	I-228-993-00	RES, ADJ, CARBON 4.7K
R318	I-249-429-11	CARBON 10K 5% 1/4W	RV103	I-228-995-00	RES, ADJ, CARBON 22K
R319	I-249-411-11	CARBON 330 5% 1/4W	RV104	I-228-995-00	RES, ADJ, CARBON 22K
R320	I-249-411-11	CARBON 330 5% 1/4W	RV201	I-228-990-00	RES, ADJ, METAL GLAZE 1K
R321	I-249-411-11	CARBON 330 5% 1/4W	RV501	I-238-314-11	(EXCEPT FOR US)...RES, VAR, CARBON 10K/10K (LINE OUT/PHONE LEVEL) (INCLUDING M901)
R401	I-249-415-11	CARBON 680 5% 1/4W	RV502	I-238-478-11	(US)...RES, VAR, CARBON 20K/20K (HEADPHONE VOL)
R402	I-249-415-11	CARBON 680 5% 1/4W	S001	ΔI-571-722-11	(E)...SWITCH, VOLTAGE SELECTION (VOLTAGE SELECTOR)
R403	I-249-415-11	CARBON 680 5% 1/4W	S101	I-571-274-11	SWITCH, LEAF (LIMIT IN)
R404	I-249-415-11	CARBON 680 5% 1/4W	S601	I-554-596-21	SWITCH, KEY BOARD (17)
R405	I-247-891-00	CARBON 330K 5% 1/4W	S602	I-554-596-21	SWITCH, KEY BOARD (18)
R406	I-247-891-00	CARBON 330K 5% 1/4W	S603	I-554-596-21	SWITCH, KEY BOARD (19)
R407	I-249-409-11	CARBON 220 5% 1/4W	S604	I-554-596-21	SWITCH, KEY BOARD (20)
R408	I-249-409-11	CARBON 220 5% 1/4W	S605	I-554-596-21	SWITCH, KEY BOARD (16)
R409	I-249-409-11	CARBON 220 5% 1/4W	S606	I-554-596-21	SWITCH, KEY BOARD (11)
R410	I-249-409-11	CARBON 220 5% 1/4W	S607	I-554-596-21	SWITCH, KEY BOARD (12)
R411	I-249-414-11	(EXCEPT FOR US) ...CARBON 560 5% 1/4W	S608	I-554-596-21	SWITCH, KEY BOARD (13)
R412	I-249-414-11	(EXCEPT FOR US) ...CARBON 560 5% 1/4W	S609	I-554-596-21	SWITCH, KEY BOARD (14)
R413	I-249-405-11	CARBON 100 5% 1/4W	S610	I-554-596-21	SWITCH, KEY BOARD (15)
R414	I-249-405-11	CARBON 100 5% 1/4W	S611	I-554-596-21	SWITCH, KEY BOARD (>20)
R415	I-249-441-11	CARBON 100K 5% 1/4W	S612	I-554-596-21	SWITCH, KEY BOARD (6)
R417	I-249-417-11	CARBON 1K 5% 1/4W	S613	I-554-596-21	SWITCH, KEY BOARD (7)
R418	I-249-417-11	CARBON 1K 5% 1/4W	S614	I-554-596-21	SWITCH, KEY BOARD (8)
R419	I-249-434-11	CARBON 27K 5% 1/4W	S615	I-554-596-21	SWITCH, KEY BOARD (9)
R420	I-249-434-11	CARBON 27K 5% 1/4W	S616	I-554-596-21	SWITCH, KEY BOARD (10)
R451	I-249-414-11	(US)...CARBON 560 5% 1/4W	S617	I-554-596-21	SWITCH, KEY BOARD (FADER)
R452	I-249-414-11	(US)...CARBON 560 5% 1/4W	S618	I-554-596-21	SWITCH, KEY BOARD (1)
R453	I-249-433-11	(US)...CARBON 22K 5% 1/4W	S619	I-554-596-21	SWITCH, KEY BOARD (2)
R454	I-249-433-11	(US)...CARBON 22K 5% 1/4W	S620	I-554-596-21	SWITCH, KEY BOARD (3)
R501	I-249-435-11	(EXCEPT FOR US) ...CARBON 33K 5% 1/4W	S621	I-554-596-21	SWITCH, KEY BOARD (4)
R502	I-249-435-11	(EXCEPT FOR US) ...CARBON 33K 5% 1/4W	S622	I-554-596-21	SWITCH, KEY BOARD (5)
R503	I-249-432-11	(EXCEPT FOR US) ...CARBON 18K 5% 1/4W	S623	I-554-596-21	SWITCH, KEY BOARD (◀)
R504	I-249-432-11	(EXCEPT FOR US) ...CARBON 18K 5% 1/4W	S624	I-554-596-21	SWITCH, KEY BOARD (▶)
R505	I-249-422-11	(EXCEPT FOR US) ...CARBON 2.7K 5% 1/4W	S625	I-554-596-21	SWITCH, KEY BOARD (EDIT/TIME FADE)
R506	I-249-422-11	(EXCEPT FOR US) ...CARBON 2.7K 5% 1/4W	S626	I-554-596-21	SWITCH, KEY BOARD (CHECK)
R507	I-249-431-11	(EXCEPT FOR US) ...CARBON 15K 5% 1/4W	S627	I-554-596-21	SWITCH, KEY BOARD (CLEAR)
R508	I-249-431-11	(EXCEPT FOR US) ...CARBON 15K 5% 1/4W	S628	I-554-596-21	SWITCH, KEY BOARD (◀)
R509	I-249-402-11	(EXCEPT FOR US) ...CARBON 56 5% 1/4W	S629	I-554-596-21	SWITCH, KEY BOARD (▶)
R510	I-249-402-11	(EXCEPT FOR US) ...CARBON 56 5% 1/4W	S630	I-554-596-21	SWITCH, KEY BOARD (OPEN/CLOSE)
R553	I-249-417-11	(US)...CARBON 1K 5% 1/4W	S631	I-554-596-21	SWITCH, KEY BOARD (▶)
R554	I-249-417-11	(US)...CARBON 1K 5% 1/4W	S632	I-554-596-21	SWITCH, KEY BOARD (■)
R555	I-249-429-11	(US)...CARBON 10K 5% 1/4W	S633	I-554-596-21	SWITCH, KEY BOARD (■)
R556	I-249-429-11	(US)...CARBON 10K 5% 1/4W	S634	I-554-596-21	SWITCH, KEY BOARD (TIME)
R557	I-249-422-11	(US)...CARBON 2.7K 5% 1/4W	S635	I-554-596-21	SWITCH, KEY BOARD (AUTO SPACE)
R558	I-249-422-11	(US)...CARBON 2.7K 5% 1/4W	S636	I-554-596-21	SWITCH, KEY BOARD (REPEAT)
R559	I-249-402-11	(US)...CARBON 56 5% 1/4W	S637	I-554-596-21	SWITCH, KEY BOARD (PROGRAM)
			S638	I-554-596-21	SWITCH, KEY BOARD (SHUFFLE)
			S639	I-554-596-21	SWITCH, KEY BOARD (CONTINUE/SINGLE)
			S640	I-571-305-11	SWITCH, PUSH (1 KEY) (POWER)
			S701	I-571-300-11	SWITCH, ROTARY (IN/OUT)
			T901	ΔI-449-024-11	(US, Canadian)...TRANSFORMER, POWER
			T901	ΔI-449-025-11	(AEP, UK)...TRANSFORMER, POWER

Note:
The components identified by mark **▲** or dotted line with mark **▲** are critical for safety.
Replace only with part number specified.

Note:
Les composants identifiés par une marque **▲** sont critiques pour la sécurité.
Ne les remplacer que par une pièce portant le numéro spécifié.

<u>Ref.No</u>	<u>Part No.</u>	<u>Description</u>
T901	A-1-449-026-11	(E)...TRANSFORMER, POWER
X301	I-567-926-11	VIBRATOR, CRYSTAL
X601	I-577-082-11	VIBRATOR, CERAMIC (4MHz)

ACCESSORY & PACKING MATERIAL

1-465-049-11 (EXCEPT FOR US)...REMOTE COMMANDER
1-465-051-11 (US)...REMOTE COMMANDER
1-558-543-11 CORD, CONNECTION
1-559-533-11 CORD, CONNECTION
*3-704-339-01 SHEET (STANDARD), PROTECTION
3-786-456-11 (EXCEPT FOR US)...MANUAL, INSTRUCTION
3-786-456-21 (US)...MANUAL, INSTRUCTION
3-786-456-41 (AEP)...MANUAL, INSTURCTION
*3-795-629-11 (AEP)...INSTRUCTION
4-928-079-01 COVER, BATTERY
*4-885-838-00 (AEP, UK, E)...LABEL, CLASS 1
*4-925-388-41 INDIVIDUAL CARTON
*4-925-389-01 CUSHION

Note:
The components identified by mark or dotted line with mark are critical for safety.
Replace only with part number specified.

Note:
Les composants identifiés par une marque sont critiques pour la sécurité.
Ne les remplacer que par une pièce portant le numéro spécifié.