

REF		DESIGNATION	Nº	REF		DESIGNATION	Nº	REF		DESIGNATION	Nº
R1	I2	10KΩ 2W	371	C1	F7	0,25 μF 500V/1500V	365.15	V1	I2	6AT7N	352
R2	I1	4700Ω 2W	"	C2	F7	0,1 μF 630V/1500V	365.16	V2	I3	6AT7N	"
R3	I2	47KΩ 1/2W	"	C3	G2	22000 pF 630/1500V	365.17	V3	G3	6CB6	"
R4	I4	150Ω 1/2W	"	C4	I3	220 pF ceram	369	V4	G3	6AU6	"
R5	I2	47KΩ 1/2W	"	C5	H6	10000 pF 630/1500V	365.18	V5	F2	6BD7	"
R6	G1	220KΩ 1/2W	"	C6	J1	1000 pF	369.1	V6	F4	EL83	"
R7	F1	75Ω 1/4W	373	C7	I3	220 pF ceram	369	V7	F2	6J6	"
R8	G3	39KΩ 1/2W	371	C8	I4	16 μF 450/550V	363.16	V8	B2	6BD7	"
R9	G3	47KΩ 1/2W	"	C9	I3	47 pF	369	V9	F6	EF80	"
R10	H3	33KΩ 1/2W	"	C10	H4	1500 pF ceram	369	V10	F7	EF80	"
R11	J4	22KΩ 1W	"	C11	H3	1500 pF ceram	"	V11	E5	6AL5	"
R12				C12	G3	1500 pF ceram	"	V12	D6	D97.32	354
R13	I3	47KΩ 1W	"	C13	F4	1500 pF ceram	"				
R14	I3	1500Ω 1/2W	"	C14	F2	Cloche Philips	551.10				
R15	I3	220Ω 1/2W	"	C15	G1	100 pF	369				
R16	I4	100KΩ 1/2W	"	C16	H1	47 pF	"				
R17	H4	1KΩ 1/2W	"	C17	I1	1500 pF	"	I1		Self 564.113	
R18	H4	220Ω 1/2W	"	C18	I1	22 pF	551.35	I2		" 564.112	
R19	H4	47Ω 1/2W	"	C19	J2	1500 pF	369	I3		" 563.61	
R20	H4	220Ω 1/2W	"	C20	I2	270 pF	367A	I4		"	
R21	G4	10KΩ 1/2W	"	C21	I2	11 pF	551.37	I5		"	
R22	G3	33KΩ 1/2W	"	C22	F2	22 pF	369	I6		" 564.107	
R23	H3	4700Ω 2W	"	C23	F3		451.55	I7		" 564.109	
R24	F3	10KΩ 1/2W	"	C24	D2	10 pF	369	I8		" 564.108	
R25	F4	220KΩ 1/2W	"	C25	F3	1500 pF	"	I9		"	
R26	D3	100Ω 1/4W 1%	373	C26	F3	1500 pF	"	I10		" 564.111	
R27	F3	750Ω 1/4W 5%	373 ^A	C27	C2	3 pF	"	I11		" 564.114	
R28	D3	100Ω 1/4W 1%	373	C28	C3	1500 pF	"	I12		"	
R29	D3	100Ω 1/4W 1%	"	C29	D3	22 pF	"	I13		" 564.110	
R30	G5	10KΩ 2W	371	C30	D3	22 pF	"	I14		" 562.21	
R31	B6	4700Ω 1/2W	"	C31	B2		551.54	I15		" 562.61	
R32	F3	1500Ω 1/2W	"	C32	B2	10 pF	369	I16		" 564.93	
R33	F4	470KΩ 1/2W	"	C33	C6	50 μF 380V	363.18				
R34	C2	1MΩ 1/2W	"	C34	B5	100 μF 150/163V	363.37				
R35	C3	75Ω 1/4W	373	C35	B5	100 μF 150/163V	363.37	G1	B2	Germanium	369.1
R36	C3	1000Ω 1/2W	371	C36	B6	8 μF 450/550V	363.17	G2	F7	"	359.1
R37	C3	4700Ω 2W	"	C37	B6	8 μF 450/550V	363.18	G3	F5	"	359.2
R38	B3	10KΩ 2W	"	C38	F5	22000 pF 630/1500V	365.17	G4	C3	"	359.1
R39	B2	10KΩ 1/2W	"	C39	D5	10000 pF 630/1500V	365.18	G5	F5	"	359.1
R40	C6	100Ω 1/4W 1%	373			5000 pF	365.51				
R41	C6	220Ω 1/4W 1%	"	C40	D5	10000 pF 630/1500V	365.18	D1	B6	Redresseur	567.1
R42	C4	150Ω 1/4W 1%	"			5000 pF	365.51	D2	B6	"	567.2

[illegible]