



C7, C8	.05 Mfd, 200 Volt, Tubular Paper	4100
C9, C12, C13, C15	100 Mmf ± 20%, Mica	4000
C10, C11, C23	.05 Mfd, 400 Volt, Tubular Paper	4101
C14, C16	.005 Mfd, 600 Volt, Tubular Paper	4102
C17	.01 Mfd, 600 Volt, Tubular Paper	4103
C18-C19-C20	Dry Electrolytic Condenser (20-20-20 Mfd 450-450-25 Volt)	4200
C21	.001 Mfd, 600 Volt, Tubular Paper	4104
C22	.01 Mfd, 600 Volt, Tubular Paper (Metal Can)	4105
L1	Oscillator Coil	5200
LS	Loudspeaker, 4" x 6" (1500-Ohm Field)	9000
R1, R8	22 Megohm ± 20%, ½ Watt	4500
R2	22,000 Ohm ± 20%, ½ Watt	4501
R3	2.2 Megohm ± 20%, ½ Watt	4502
R4	10,000 Ohm ± 10%, 2 Watt	4503
R5	47,000 Ohm ± 20%, ½ Watt	4504
R6	.5 Megohm Potentiometer (Volume)	4804
R7	10 Megohm ± 20%, ½ Watt	4505
R9	.47 Megohm ± 20%, ½ Watt	4506
R10	560 Ohm ± 10%, ½ Watt	4507
R11	.25 Megohm Potentiometer With Switch (Tone)	4805
R12	47 Ohm ± 20%, ½ Watt	4508
R13	330 Ohm ± 20%, ½ Watt	4509