


MODEL 160 Series Schematic



REF. PART No.	DESCRIPTION	REF. PART No.	DESCRIPTION	REF. PART No.	DESCRIPTION
1	30.31 CARB. RES.-10000 OHMS- $\frac{1}{2}$ W 20%	23	15.7 MICA COND.-.002 MFD $\pm 10\%$	45	130.5 WIRE RES.-250 OHMS- $\frac{1}{2}$ W 5%
2	30.31 " " " " " "	24	15.7 " " " " " "	46	130.5 " " " " " "
3	30.4 " " " " " "	25	15.3 " " " " " "	47	130.6 " " " " " "
4	30.3 " " " " " "	26	15.3 " " " " " "	48	100 H " " " " " "
5	30.26 " " " " " "	27	15.6 " " " " " "	49	105.4 " " " " " "
6	30.08 " " " " " "	28	15.2 " " " " " "	50	451 BAND SWITCH
7	30.20 " " " " " "	29	15.22 " " " " " "	51	ON-OFF " ON VOL. CONT.
8	30.20 " " " " " "	30	125.1 PHONO JACK	52	30.26 CARB. RES.-50000 OHMS- $\frac{1}{2}$ W 20%
9	30.5 " " " " " "	31	25.43 PADDING COND. 350-1200 MFD	53	10.2 TUBULAR COND.-1 MFD.-200 V
10	30.3 " " " " " "	32	55.1 TONE CONTROL	54	10.13 " " " " " "
11	30.22 " " " " " "	33	120.3 PILOT LIGHTS-6.0 V.-15 A.	55	30.39 CARB. RES.-5000 OHMS- $\frac{1}{2}$ W 20%
12	30.38 " " " " " "	34	10.7 TUBULAR COND.-.05 MFD.-400 V.		
13	30.37 " " " " " "	35	10.5 " " " " " "		
14	45.79 ANTENNA COIL - B & 5 W	36	10.5 " " " " " "		
15	45.81 O-SCILLATOR " " " "	37	10.7 " " " " " "		
16	44.88 1N 1 F COIL	38	10.9 " " " " " "		
17	44.90 2N 3	39	10.7 " " " " " "		
18	40.4 POWER TRANS - 115 V 50-60 ~	40	10.4 " " " " " "		
19	20.32 ELECTRO. COND. BLOCK - 2 MFD 50 WV	41	10.9 " " " " " "		
20	20.33 " " " " " "	42	10.14 " " " " " "		
21	20.33 " " " " " "	43	20.33 " " " " " "		
22	20.33 " " " " " "	44	50.13 VOLUME CONT. - 1 MEG.		