



## TUBES AND FUNCTIONS:

7H7.....Tuner  
 6SK7GT.....A.V.C. detector, 1st Audio  
 6SQ7GT.....A.V.C. detector, 1st Audio  
 6J5GT.....Translator  
 6K6GT.....IF  
 6X5GT.....Rectifier

POWER SUPPLY:  
 This unit uses 105-125 volts A.C. 50 watts. The frequency (cycles) is specified on the bottom of the cabinet.

POWER OUTPUT:  
 Type.....Pentode  
 Undistorted.....2 Watts  
 Maximum.....3.3 Watts

OPERATING CONTROLS:  
 Left knob....."On-Off" Volume  
 Center knob.....Tuning  
 Right knob....."P.B." "A.B."

6J5GT.....Oscillator  
 6K6GT.....Output  
 6X5GT.....Rectifier

## FREQUENCY RANGES:

Broadcast.....535 - 1610 KC  
 Short Wave.....5.7 - 16.2 MC

INTERMEDIATE FREQUENCY.....455 KC

## CONTROL OPERATION:

Turning right: power on; volume increases

Tuning ratio 12:1

The letter appearing in the vertical position indicates the position of the switch. "P.B." push-buttons, "A"-Broadcast, "B"-Short Wave.

## LOUD SPEAKER

Type.....Dynamic  
 Size.....5 Inch  
 Field.....P.M.

AUGUST 5, 1941