

MODEL RX

DIAG. NO.	PART NO.	DESCRIPTION	DIAG. NO.	PART NO.	DESCRIPTION
R-1	N-4088	220,000 OHM 20%	C-10	N-2712	.005 MFD. 600V.
R-2	N-4823	56,000 OHM 10%	C-11	N-1367	8MFD. 150 V. ELECT.
R-3	N-1063	10 MEGOHM 20%			
R-4	N-4277	2.2 MEGOHM 20%			
R-5	N-3411	1 MEG. VOL. CONTROL	1	N-4834	ANTENNA COIL
R-6	N-4277	2.2 MEGOHM 20%	2	N-4835	OSCILLATOR COIL
R-7	N-1262	1 MEGOHM 20%	3	N-3410	1ST. I.F. TRANS.
R-8	N-4277	2.2 MEGOHM 20%	4	N-2648	2ND. I.F TRANS.
R-9	N-4086	470 OHM 10%	5	N-3406	6" PM SPEAKER
R-10	N-4063	47,000 OHM 20%			OUTPUT TRANS.
		(ALL RESISTORS ARE .5 WATT SIZE.)	6	——	BATTERY SW. ON VOL. CONTROL
C-1		CAPACITY IN OSCILLATOR COIL		N-4824	GANG CONDENSER
C-2	N-1345	.05 MFD. 200 V.			
C-4	N-1345	.05 MFD. 200 V.		N-1525	BATTERY CABLE
C-5	N-1376	.02 MFD. 400 V.			
C-6	N-1342	50 MMFD. MICA			
C-7	N-2712	.005 MFD. 600 V.			
C-8	N-1342	50 MMFD. MICA			
C-9	N-1344	.01 MFD. 400 V.			

TUBE & TRIMMER LOCATIONS



Sonora
Clear as a Bell

I.F. 455 K.C.

NOTE: TUBE SOCKETS SHOWN FROM WIRING SIDE

4 TUBE - 1½ VOLT

SUPERHETERODYNE
SINGLE BAND

DRAWN APPROVED

AUGUST 1948

RX