




<u>Diag.</u> <u>No.</u>	<u>PART</u> <u>No.</u>	<u>DESCRIPTION</u>
9	2186511	MOLDED MICA CONDENSER (100 MUF) 20%
10	666003	CARBON RESISTOR (220,000-1/3-20)N.I.
11	666020	CARBON RESISTOR (47,000-4/3-20)N.I.
12	666101	CARBON RESISTOR (4700-1/3-20)N.I.
13	18A20829	VARIABLE BIAS CONTROL
14	40X11539	SLIDER SWITCH (SPST)
15	30K20095	LINK CORD & PLUG (3 CONDUCTOR)

**MODEL 22-A**

FREQ RANGE  
1250 TO 1720K.C



FREQ RANGE  
1250 TO 1720 K C


**AUTOMATIC  
CHANGE SWITCH**

MANUAL REJECT SWITCH  
(MOMENTARY CONTACT)

CH  
T1

ROUND  117V AC

13



### THREE POSITION SWITCH

1 POS	OFF	SW 1 & 2 OPEN
2 POS	TUBES	SW 1 CLOSED SW 2 OPEN
3 POS	MOTOR	SW 1 & 2 CLOSED

FOR AUTOMATIC  
RECORD-CHANGER.

SEE MODEL B2RC

Draw No.	Part No.	DESCRIPTION
1	71A02092	DET. COT. CERAMIC (Bare-Nud Pkt.)
2	2530-154	DETACHED VACUUM TIGHTNESS
3	2530-152	PHOTO THERMISTOR
4	2530-150	PLUMBING UNIT WITH PLATE
5	2530-151	PUMP PRISM AND ARM (Less Hse.)
6	2530-153	TECHNICAL & BRACKET "C" 100"
7	2530-157	ELECT. COT. CERAMIC (10-10-10/30V)
8-A	8079-16	TUMBLER CONDUCTOR (.05-100V)
8-B	8079-16	TUMBLER CONDUCTOR (.05-100V)
9	8185-11	WELDED WIRE CONDUCTOR (100 mm) 205
10	8185-11	WELDED WIRE CONDUCTOR (25 mm) 205
10-A	8185-15	HELIX WIRE CONDUCTOR (25 mm) 205
11	6800-05	CAPACITOR RESISTOR (220,000-1/2-20M, 1)
12	6800-08	CAPACITOR RESISTOR (10,000-1/2-20M, 1)
13	6800-09	CAPACITOR RESISTOR (1,000-1/2-20M, 1)
14	10A020-09	VARIABLE BIAS CONTROL
15	10A021-08	POWER SWITCH
16	10A021-06	PURE COT. CERAMIC (Bare-Nud Pkt.)
17	10A021-03	DETACHED VACUUM TIGHTNESS
18	10A021-02	PHOTO THERMISTOR
19	10A021-01	PLUMBING UNIT WITH PLATE

**MODELS 23-RC & 23-RCW**