
R.F. AMP.
7A7
OSC.-MOD.
7B8
DET.-AVC.
7E7
PHASE INV.
7F7
OUTPUT
7C5
7C5
TO HEATER & SPEAKER FIELD SUPPLY
PM
VOICE COIL: D.C. RES. 4 Ω
ELECTRO
VOICE COIL: D.C. RES. 4 Ω
FIELD COIL: D.C. RES. 5.7 Ω
UNITED SERVICE MOTORS
I.F. 262 KC.
VIBRATOR
60
RECTIFIER
OZ4
"A" FUSE CONNECTOR
TO HEATERS
TO SPEAKER FIELD
PARTS LAYOUT
*330 OHMS-1 WATT-ON SETS USING P M SPEAKERS
820 OHMS-2 WATTS-ON SETS USING ELECTRO-MAGNETIC SPEAKERS
**100 OHMS-1/2 WATT-ON EARLY PRODUCTION.
220 OHMS-1/2 WATT-ON LATER PRODUCTION.
***27,000 OHMS-1/2 WATT INSULATED-ON SETS UP TO SERIAL NO. 7119719
100,000 OHMS-1/2 WATT INSULATED-ON SETS AFTER SERIAL NO. 7119719
UNITED MOTORS PONTIAC MODEL 984171