



**Specifications**

**POWER SUPPLY POLARITY**—For operation on DC the power plug must be inserted in the outlet for correct polarity. If the set does not function reverse the plug. On AC reversal of the plug may reduce hum.

**Loudspeaker** (922258-1)  
Type V C Impedance  
3 4 ohms at 400 cycles  
4" x 6" PM  
Depth 7 1/2"  
Width 11 3/4"  
Height 7"  
Shipping Weight 9 lbs  
Tuning Drive Ratio 20:1

**Cabinet Dimensions**  
Cabinet (Outside)  
Shipping Weight  
Tuning Drive Ratio

**Power Supply Rating**  
105-125 volts AC, 50 or 60 cycles or DC  
10 watts

**Frequency Range**  
540 1600 kc  
455 kc

**Power Output**  
Undistorted Maximum  
10 watt  
1.5 watts

**Tube Complement**  
(1) RCA Radiotron 12SA7  
(2) RCA Radiotron 12SK7  
(3) RCA Radiotron 12SQ7  
(4) RCA Radiotron 50L6GT  
(5) RCA Radiotron 35Z5GT

**Pilot Lamp**  
Mazda No 51 6-8 volts 0.2 amp

**Converter**  
I-F Amplifier  
Power Output  
Rectifier

**2nd Det A V C and A-F Amplifier**

