



VOLTAGES MEASURED FROM SOCKET TERMINALS TO A.C.
LINE AT CHANGEOVER SWITCH.

Q46. N°	PART N°	DESCRIPTION	Q46. N°	PART N°	DESCRIPTION
C/1	22-1026	TWO GANG VARIABLE	R/1	63-773	180 M OHM
C/2	22-823	.05 MFD.	R/2	83-590	15 M OHM
C/3	22-827	1 MFD.	R/3	63-713	47 M OHM
C/4	22-988	20 M MFD.	R/4	63-722	2.2 MEGOHM
C/5	22-162	200 M MFD.	R/5	63-1121	VOLUME CONTROL
C/6	22-482	.002 MFD.	R/6	63-587	4700 OHM
C/7	22-470	.00015 MFD.	R/7	63-1083	15 MEGOHM
C/8	22-243	01 MFD.	R/8	63-1037	870 OHM WIREWOUND
C/9	22-449	.02 MFD.	R/9	63-371	1 MEGOHM
C/10	22-869	.05 MFD.	R/10	63-371	1 MEGOHM
C/11	22-1026	20 MFD. ELECTROLYTIC	R/11	63-1096	25 OHM WIREWOUND
C/12	22-1026	40 MFD.	R/12	63-439	2700 OHM
C/13	22-1027	20 MFD.	R/13	63-1039	33 OHM WIREWOUND
C/14	22-1027	20 MFD.	R/14	63-742	180 OHM

110 VOLT A.C.-BATTERY PACK
UNIVERSAL PORTABLE
I.F. FREQUENCY 455 KC.
5 TUBE SUPERHETERODYNE
CHASSIS N° 5A01

Antenna disconnected — volume control at minimum and condenser plates in full mesh.

Line voltage — 117v.