


MODEL 33-X, 362-X  
MODEL ZE-10  
MODEL ZE-13



(1928)

DET 1 AF 3 RF 2 RF 3 AF 1 RF

27 27 27 22 71A 27

RECT

20

PILOT 6.0 V.

FRONT

OX-380 used in separate power unit.

TUBE NO. OR TUBE #	TYPE OF TUBE	POSITION OF TUBE 1ST R.F. DET. ETC.	READING PENS IN SOCKET OF SET								
			TUBE GLV		TUBE IN TESTER						
			A VOLTS	B VOLTS	A VOLTS	B VOLTS	C VOLTS	CATHODE VOLTS	NORMAL PLATE V.	PLATE RES. GRID TEST	PLATE RES. CHANGE
1	227	1st. R.F.			2.05	102	6	=	2.9	4.1	1.2
2	227	2nd. R.F.			2.05	102	6	=	3.8	6.8	3.0
3	227	3rd. R.F.			2.05	102	6	=	3.8	6.8	3.0
4	227	Detector			2.00	40	0	=	2.3	2.5	0.2
5	227	1st. A.F.			2.05	94	6	=	2.6	3.7	1.1
6	171A	2nd. A.F.			4.90	170	36	=	17.0	13.0	4.0
7	280	Rectifier			4.60	-	-	=	20.0	-	-