



A. Kondensatoren

C	Drehkondensator	DUCATI EC	3416.12
C 1	DUCATI Trimmer	3558/14	
2	Glimmer	100 pF $\pm 10\%$	
3	DUCATI Trimmer	EC 3408/283	
4	DUCATI Trimmer	EC 3408/283	
5	DUCATI Trimmer	EC 3408/283	
6	DUCATI Trimmer	EC 3408/283	
7	Papier	0,05 mF 500 V.	
8	Papier	0,10 mF 1500 V.	
9	Papier	0,10 mF 1500 V.	
10	Papier	0,10 mF 1500 V.	
11	Glimmer	50 pF $\pm 10\%$	
12	Glimmer	150 pF $\pm 2,5\%$	
13	Glimmer	150 pF $\pm 2,5\%$	
14	Glimmer	250 pF $\pm 10\%$	
15	DUCATI Trimmer	EC 3408/283	
16	DUCATI Trimmer	EC 3408/283	
17	DUCATI Trimmer	EC 3408/283	
18	DUCATI Trimmer	EC 3408/283	
19	Glimmer	3200 pF $\pm 2,5\%$	
20	Glimmer	390 pF $\pm 1\%$	
21	Glimmer	120 pF $\pm 2,5\%$	
22	Glimmer	150 pF $\pm 2,5\%$	
23	Glimmer	150 pF $\pm 2,5\%$	
24	Glimmer	20 pF $\pm 10\%$	
25	Papier	0,05 mF 1500 V.	
26	Papier	0,05 mF 500 V.	
27	Elektrolyt	50 mF 12-15 V.	
28	Papier	0,10 mF 1500 V.	
29	Glimmer	100 pF $\pm 10\%$	
30	Glimmer	100 pF $\pm 10\%$	
31	Papier	0,05 mF 1500 V.	
32	Papier	0,05 mF 1500 V.	
33	Glimmer	200 pF $\pm 10\%$	
34	Elektrolyt	4 mF 450 V.	
35	Elektrolyt	50 mF 12-15 V.	
36	Elektrolyt	4 mF 450 V.	
37	Glimmer	200 pF $\pm 10\%$	
38	Papier	0,05 mF 1500 V.	
39	Papier od. Glimmer	900 pF 1500 V.	
40	Papier	0,03 mF 1500 V.	
41	Papier	3000 pF 1500 V.	
42	Elektrolyt	50 mF 12-15 V.	
43	Papier	0,10 mF 1500 V.	
44	Papier	5000 pF 2000 V.	
45	Elektrolyt	10 mF 450 V.	
46	Elektrolyt	20 mF 450 V.	

B. Widerstände

R	1	Widerstand	25	Ohm	1/4 Watt
2	"	0,1 m	"	1/4	"
3	"	0,03 m	"	1	"
4	"	2,5 k	"	1/2	"
5	"	0,03 m	"	1	"
6	"	150	"	1/4	"
7	"	0,05 m	"	1/4	"
8	"	1 m	"	1/4	"
9	"	0,1 m	"	1	"
10	"	1 m	"	1/4	"
11	"	300	"	1/4	"
12	"	0,1 m	"	1/4	"
13	"	0,5 m	"	1/4	"
14	"	0,05 m	"	1/4	"
15	"	2 m	"	1/4	"
16	"	3 k	"	1/4	"
17	"	0,1 m	"	1/2	"
18	"	40 k	"	1/4	"
19	"	2 m	"	1/4	"
20	"	2 m	"	1/4	"
21	"	0,2 m	"	1/4	"
22	"	0,3 m	"	1/4	"
23	"	0,1 m	"	1/4	"
24	"	2,5 k	"	1/4	"
25	"	150	"	1/2	"
26	"	100	"	1/4	"

P 1	Potentiometer	0,5 m Ohm
2	"	0,5 m SATOR

Wellenbereiche:

Kurzwellen I	13 — 24 Meter
Kurzwellen II	23 — 65 Meter
Mittelwellen	192 — 577 Meter
Langwellen	670 — 2000 Meter

Allgemeine Angaben: Zwischentfrequenz = 500 kHz

Sicherungen: 220—250 Volt = 600 m. Amp.

110—145 Volt = 1000 m. Amp.

Skalalämpchen: 6,3 Volt, 0,3 Amp. OSRAM

Röhren: ECH 4, EBF 2, EF 6, EL 3, AZ 1, EM 4

Sondyna Amati 42

Sondyna A.G.
Zürich